

Additional options include:

| Category | Description | Spec'd |
|-------------------|---|--------|
| Engine | MP7-325 HP | * |
| | MP7-355 HP | |
| | MP7-375 HP | |
| | MP7-395 HP | |
| | MP7-425 HP | |
| | MP8-425 HP | |
| | MP8-455 HP | |
| | MP8-505 HP | |
| Transmission | Fuller RTO-16908LL | * |
| | Fuller RTLO-18918B | |
| | 3000 RDS 6-Sp Allison Gen 5 w/ Prognostics, w/ PTO provision | |
| | 3000 RDS 6-Sp Allison Gen 6 w/ Prognostics, w/ PTO provision | |
| | 3000 RDS 6-Sp Allison Gen 5 w/ Prognostics, w/ output retarder w/PTO | |
| | 3000 RDS 6-Sp Allison Gen 5 w/o Prognostics, w/ output retarder w/PTO | |
| | 4500 RDS 5-Sp Allison Rugged Duty Series Gen 5 w/ Prognostics | |
| | 4500 RDS 5-Sp Allison Gen 6 w/ Prognostics, w/PTO | |
| | 4500 RDS 5-Sp Allison Gen 5 w/ Prognostics, w/ output retarder | |
| | 4500 RDS 5-Sp Allison Gen 6 w/ Prognostics, w/ output retarder, w/PTO | |
| | 4500 RDS 6-Sp Allison Gen 5 w/ Prognostics | |
| | 4500 RDS 6-Sp Allison Gen 6 w/ Prognostics, w/PTO | |
| | 4500 RDS 6-Sp Allison Gen 5 w/ Prognostics, w/ output retarder | |
| | 4500 RDS 6-Sp Allison Gen 6 w/ Prognostics, w/ output retarder, w/PTO | |
| Exhaust/Emissions | Idle emission certification, basic | * |
| | Idle emission certification, CARB 08 | |
| | DEF tank options - 6.6 gal - 11.8 gal, LH or RH | |
| Engine Equipment | Emergency start studs, battery box mounted - optional | |
| | Battery disconnect switch - optional | |
| | Engine brake - optional | |
| | Engine heaters - optional | |
| Front Axle Equip. | 12,000# Mack FXL12 Straight Spindle/Unitized Bearings | * |
| | 14,600# Mack FXL14.6 Straight Spindle/Unitized Bearings | |
| | 18,000# Mack FXL18 (Wide Pivot Center) Straight Spindle/Unitized Bearings | |
| | 20,000# Mack FXL20 Tapered Spindle/Tapered Bearings | |
| | 20,000# Mack FXL20 Wide Pivot Center Straight Spindle/Unitized Bearings | |
| | 23,000# Mack FXL23 Wide Pivot Center Straight Spindle/Unitized Bearings | |
| | Multileaf or Taperleaf springs | |
| | Drum brakes spec'd, air disc brakes optional | |
| Rear Axle Equip. | Front dust shields optional | * |
| | 38,000# Mack S38R Fabricated Steel Housing | |
| | 40,000# Mack S40 | |
| | 40,000# Mack S402R Cast Ductile Iron Housing | |
| | 44,000# Meritor MT-44-14X5D Hypoid (Low Entry) | |
| | 44,000# Mack S440 Fabricated Steel Housing | |
| | 46,000# Mack S460 Fabricated Steel Housing | |
| | 46,000# Mack S462R Cast Ductile Housing | |

52,000# Mack S522R Cast Ductile Housing
58,000# Mack S582 Cast Ductile Iron Housing
65,000# Mack S652 Cast Ductile Iron Housing
Suspension options include Camelback, mRide, Hendrickson, & Ridewell
Drum brakes spec'd, air disc brakes optional
Differential locks optional
Wheelbases available from 157"-450"
Fuel tanks available from 50gal-100gal, LH & RH

Frame Equip.

Please contact John Walsh at Shealy Truck Center for additional options and pricing, and be sure to mention the NCSA procurement program for preferred pricing.

a