



## KB-2 SERIES



CDL  
Exempt

KBF-2 with TKB-1820 Body

### Boom:

- ☆ 17' Fixed Boom
- ☆ 1 Piece Main Boom
- ☆ 270° Rotation
- ☆ Swing Controls

### Body:

- ☆ 20 Cu. Yd. Capacity
- ☆ 1 Piece 3/16" Floor
- ☆ 8" Main Sill
- ☆ 4" Joists on 12" Centers

### Grapple/Bucket:

- ☆ 360 Continuous Rotation
- ☆ 2,000 lbs Clamping Force
- ☆ Replaceable Cutting Edges



All design, specifications and components are subject to change at the manufacturer's sole discretion at any time without notice. Data published herein is for informational purposes only and shall not be construed to warrant suitability of the unit for any particular purpose, as performance may vary with conditions encountered. The only warranty is our standard written warranty for this product at time of shipment.

HOL-MAC CORPORATION • P.O. Box 349 • Bay Springs, MS 39422 • (601) 764-4121



www.e-pac-mac.com

# REFUSE AND RECYCLING EQUIPMENT



## GENERAL SPECIFICATIONS:

## GRAPPLE/BUCKET:

BODY:

RECOMMENDED CHASSIS:A side view of a red and black excavator. A black safety cage is positioned around the operator's area. The background shows a grassy field and trees.

**PAC-MAN**



[www.e-pac-mac.com](http://www.e-pac-mac.com)

## REFUSE AND RECYCLING EQUIPMENT



Low profile pedestal with "A-Frame" outriggers. The outriggers extend to a width of 9 ½ feet.



The boom is equipped with a continuous rotating grapple. The grapple is constructed with bolt-on heat-treated steel cutting edges for ease of replacement. The edges are overlapping to prevent scalping. The bucket is 36" wide with a 48" opening from lip to lip.

DISTRIBUTED BY