



REFUSE & RECYCLING BODY COMPANY

Sizes from 26 to 41 cu yd capacities
Single axle version also available

DOES NOT INCLUDE FREIGHT

ROUTE KING SERIES

Commercial Front Loader

*Easily Detachable Resi-Container
Allows Collection Of Both
Residential and Commercial
Routes At The Same Time*



*KANN Adapter Option For
Easy and Efficient Collection of Both
Front and Rear Load Containers With
One Front Load Truck*

KANN Manufacturing Corporation

210 Regent Street
PO Box 400
Guttenberg IA 52052 0400

Tel (563) 252 2035

Fax (563) 252 3069

E-mail sales@kannmfg.com

Web www.kannmfg.com

04/2006

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



REFUSE & RECYCLING BODY COMPANY

ROUTE KING SERIES

Commercial Front Loader



FEATURES

FUNCTION

- 23 sec lift arm cycle
- 35 sec compactor cycle
- 45-50 sec body eject
- Pack-on-the-go

GENERAL

- Full eject body
- 24 or 29 YD³ body capacity
- 12 YD³ hopper capacity
- 119 IN body height above chassis frame with arms up; 113 IN with arms down
- 96 IN body width
- Curved uniform body and hopper walls
- 55.6 FT² (8.3 FT x 6.7 FT) hopper opening
- 8000 LB lift arm capacity
- Up to 900 LB/YD³ payload
- Body access door
- Joystick control
- Front mount pump
- Tailgate ajar/overheight, arms overheight, and hydraulic overheat alarms
- White PPG paint
- Dual tailgate safety props
- Body clean-out
- Standard light package to comply with DOT and FMVSS standards
- Standard wiring package
- Hydraulic tailgate locks with manual overlock
- Hydraulic hopper cover
- 65 GAL reservoir
- 100 MESH suction strainer
- 10 MICRON return line filter
- Sight/temperature gauge
- Hydraulic suction line shut-off valve
- Crossed telescopic compactor cylinders

CHASSIS

- 66,000 GVW
- 20,000 front GVWR
- 46,000 rear GVWR

OPTIONS

SAFETY

- Camera (single, dual)
- 10 LB or 20 LB fire extinguisher
- Spill kit
- Shovel
- Cab shield extension
- Tool box

AXLE

- Tag
- Pusher
- Steerable tag
- Steerable pusher

ARMS

- 10,000 LB arms/forks
- Adjustable forks

ACCESSORIES

- Kann Adapter™ (rear load container collection)
- Roof access ladder
- Residential carry can (optional cart tipper)

HYDRAULICS

- 3 MICRON return line filter
- 6 MICRON return line filter

LIGHTS

- LED lights
- LED lights with strobe turn signals
- Safety work light package
- Strobe light

PAINT

- Standard PPG other than white
- Metallic
- Multi-color
- Striping

SCALES

- Vulcan
- Custom installation



The contoured blade follows the continuous uniform side walls from compactor through the body smoothly and completely clean.



The blade travels just above the body floor on cam followers to reduce floor wear. T1 strips hold commodity up, which prevents it from going under the blade and also reduces floor wear.

Proudly built in the USA

