

**DL550 T4 FINAL
US PRICE LIST**

**(Ex Works Wichita, KS)
Standard Equipment**

OPERATOR ENVIRONMENT:

E-H Cab LCD Display
Includes heat, AC, side windows,
front glass door with wiper,
Bluetooth radio with with speakers,
LCD display, Backup camera,
Creep Speed Mode, and keyless start
Tilt ROPS/FOPS
Rear window with emergency escape
Deluxe cloth, air suspension seat,
arm rests, w/ 2" (51 mm)
retractable 3 point lap seat belt
w/ heater and lumbar support

Dozer control handles
Hand and Foot throttle
Alarm package - back-up and horn
Rearview Mirror
Headliner
Electric Throttle
Dome Light
Top window
Cup holder
12V Power plug socket
Foot rest
Seat Pocket
Loader control lockout system
Electric parking brake control
Operator's compartment floor cleanout
Proportional auxiliary hydraulic control -
on joystick
Advanced Instrument Cluster w/
digital hour meter, tachometer, Fuel
level LCD bar graph w/ alarm,
diagnostic features and security
lockout

Warning lights with alarms:
Engine coolant temperature
Engine oil pressure
Engine malfunction
Hydraulic charge pressure
Hydraulic filter restriction
Hydraulic oil temperature
Critical system stop
Engine system

OPERATOR ENVIRONMENT (cont'd):

Hydraulic system
Electrical and diagnostic system
Warning alarms:
Battery voltage - plus display
Oil service
Indicator Light:
Engine preheat
Parking brake

ENGINE:

FPT 4-Cylinder engine
207 CID (3.4 L) Turbo
Tier 4 Final Certified
Selective Catalytic Reduction (SCR)
Muffler
Charged Air Cooler (CAC)
High Pressure Common Rail (HPCR)
Fuel Injection
Horsepower:
- Gross: 114 (95 kW)
- Peak torque 282 lb•ft (383 N•m)
145 amp alternator
Dual element air cleaner
Organic Acid Technology (OAT)
Anti-freeze solution to -34° F
Fuel tank - 30.8 gal. (U.S.)
3-stack after cooler/radiator/
oil cooler configuration
Glow Plugs
Integral engine oil cooler
Fuel filter with water trap
950 CCA 12V battery
Master electrical disconnect
Jump start terminal

POWERTRAIN:

2-speed hydrostatic four wheel drive
SAHR disc parking brake

**DL550 T4 FINAL
US PRICE LIST**

**(Ex Works Wichita, KS)
Standard Equipment**

HYDRAULICS:

Auxiliary hydraulics: @3,450 PSI
(238 bar) - 24.2 gpm (91.5 L/min)
High-flow auxiliary hydraulics: @ 3,450
PSI (238 bar) - 41.6 gpm- (157 L/min)
Enhanced High-flow auxiliary hydraulics
EHF: @ 4,100 PSI (283 bar) - 41.6
gpm (157 L/min)

6 micron oil filtration system
4 spool loader control valve
Auxiliary hydraulic disconnects, ISO flat-
face - connect-under-pressure w/
case drain
Hydraulic circuit pedal lock
Auxiliary function lockout override
Loader lift lockout override
Heavy duty hydraulic oil cooler
Loader arm float position
Loader function lockout system

DOZER BLADE:

90" blade on DL550
Variable mechanical pitch adjustment
(52° - 60°)
Single lever hydraulic control for lift,
angle, and tilt dozer

LOADER:

Auxiliary front electric control
Heavy Duty Hydraulic attachment
coupler
Second Auxiliary Hydraulics

For DL550:

Vertical lift geometry
ROC @ 50% of Tip: 5500 lbs.
Tipping load: 11,000 lbs.

TRACKS:

14 Inch Steel Tracks
(Single Grouser)

OTHER STANDARD FEATURES:

Electro-hydraulic controls
For drive/steering, loader functions
Switchable between Dozer & ISO
patterns
Halogen Lights - 2 front, 2 side, 2 rear
flood
Pre-wired for rotating beacon
Operator Security Codes
8 inch color LCD multifunction display
Machine Settings User Access Levels
Creep Speed Mode
Economy Modes
Ignition Timeout
Engine Protection Settings
Reversible Hydraulic Fan
Lockable service access hood
Single point daily service
Rear tail lights
Remote oil and fuel filters
Block Heater
Debris Ingression Sealing
Bucket Cylinder Guards
Heavy Duty Rear Door
CASE SiteWatch telematics
w/ advanced 1 year subscription
SiteConnect Module providing
remote diagnostics capability