

STANDARD EQUIPMENT

OPERATOR ENVIRONMENT

See page 1

ENGINE

Charge Air Cooler (CAC)
Dual element air cleaner
Organic Acid Technology (OAT)
Anti-freeze solution to -34° F
Over and under radiator and oil cooler
3-stack after cooler/radiator/oil cooler configuration
Glow plugs
Integral engine oil cooler
Fuel filter with water trap
Master electrical disconnect
Jump start terminal
Hydraulically driven reversible fan

DRIVETRAIN

2-speed hydrostatic four wheel drive
SAHR disc parking brake
Foot pedal modes - Accelerate, Trans and Decelerate

HYDRAULICS

Auxiliary hydraulics:
@ 3,450 psi (238 bar) – 24.2 gpm (91.5 L/min)
High-flow auxiliary hydraulics:
@ 3,450 psi (238 bar) – 41.6 gpm (157 L/min)
6 micron oil filtration system
3-spool loader control valve
Auxiliary hydraulic disconnects, ISO flat-face – connect-under-pressure with case drain
Hydraulic circuit pedal lock
Auxiliary function lockout override
Loader lift lockout override
Heavy-duty hydraulic oil cooler
Loader arm float position
Loader function lockout system
Auxiliary front electric control
Hydraulic one-way self leveling
Auto Ride Control
Creep Speed Mode
Auxiliary flow control within cab

LOADER

Hydraulic attachment coupler
Vertical lift geometry
Loader lift arm support pin

TRACKS

Heavy Duty Rubber Tracks

OTHER STANDARD FEATURES

LED lights - 2 front, 2 side, 2 rear flood
Pre-wired for rotating beacon
Lockable service access hood
Single-point daily servicing
Rear tail lights
Remote oil and fuel filters
Block heater
Debris ingress sealing

TELEMATICS

CASE SiteWatch™ Telematics – includes hardware and a 1-yr data subscription
SiteConnect Module providing remote diagnostics capability

6% Discount

OPTIONAL EQUIPMENT

OPERATOR ENVIRONMENT

Open Cab (ROPS/FOPS Level 1) w/ side screens; Keyed Start
Mechanical Suspension Seat - Vinyl
Demolition cab door with polycarbonate

HYDRAULICS

Enhanced High-Flow auxiliary hydraulics – EHF:
@ 4,100 psi (283 bar) – 41.6 gpm (157 L/min)
Second auxiliary hydraulics

OTHER

Language decals
Buckets – see page 3
Bolt-on bucket cutting edges
Special paint

SERVICE PARTS

Road lights
Four-corner LED strobe
Precleaner
FOPS Level 2
3 inch (76.2 mm) retractable seat belt
Bolt-on heavy-duty bucket teeth
Rotating beacon
Four point lift hook
Class III 48 in (1.22 m) pallet forks
1150 CCA battery for high altitude
Fire Extinguisher
Tamper resistant front door bracket
Attachment Hose Kit
Drawbar
Extra counterweights not offered for this model

CaseCE.com

©2021 CNH Industrial America LLC. All rights reserved. CASE is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. CNH Industrial Capital is a trademark in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Printed in U.S.A. Contains 10% post-consumer fiber.

IMPORTANT: CASE Construction Equipment Inc. reserves the right to change these specifications without notice and without incurring any obligation relating to such change. Availability of some models and equipment builds vary according to the country in which the equipment is used. The illustrations and text may include optional equipment and accessories and may not include all standard equipment. Your CASE dealer/distributor will be able to give you details of the products and their specifications available in your area.



CASE Construction Equipment is biodiesel-friendly. NOTE: All engines meet current EPA emissions regulations. All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.



Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs and use any safety features provided.

Form No. CCE202109TV620B
Replaces Form No. CCE202102TV620B

TV620B

4 of 4