

FARMALL COMPACT C SERIES II SPECIFICATIONS

MODEL	FARMALL 35C (NON-CAB)	FARMALL 40C (CAB)	FARMALL 45C (NON-CAB/CAB)	FARMALL 55C (NON-CAB/CAB)
ENGINE				
Type	Diesel, 3 cyl., 1.9 L (116 cu in.), turbocharged, Tier 4 B/Final			
Engine HP*	35	40	45	55
Air Cleaner	Replaceable dry element			
Fuel System	Electronically-controlled, indirect injection			
Fuel Capacity (Non-Cab /Cab)	10.5 gal. (40 L) non-cab only	12.4 gal. (47 L) cab only	10.5 gal. (40 L) / 12.4 gal. (47 L)	
Alternator	70 amp			
PTO				
PTO HP (Gear/ Hydro)	29.7 / 28	34 / 32	38.2 / 36	46.7 / 44
PTO Speed	540 rpm			
PTO Type	Independent with electro-hydraulic engagement			
Mid-PTO Speed (Optional)	2,000 rpm			
TRANSMISSION				
Type (Standard/Optional)	12 × 12 shuttle shift/ HST 3 range with cruise control		16 × 16/ HST 3 range with cruise control	
Maximum Forward Speed (Gear/Hydro)	14.2 mph (22.9 kph) / 14.8 mph (23.9 kph)		16.9 mph (27.3 kph) / 17.9 mph (28.7 kph)	
Gear/ Shuttle Type	Synchro			
Rear Diff. Lock Engagement	Mechanical			
Brake Type	Wet multi-disc			
HYDRAULIC SYSTEM				
Pump Flow	8.2 gpm (31.0 L/min)			
Steering Pump Flow	Gear: 4.2 gpm (15.9 L/min)/ HST: 5.3 gpm (20 L/min)			
Remote Valves	1	2	Optional: 1 (non-cab) or 2 (non-cab or cab)	
Type	Standard flex lower links and telescopic stabilizers			
3-Point Hitch	1			
Lift Capacity @ Ball End	1,808 lb. (820 kg)		2,756 lb. (1 250 kg)	
Lift Capacity @ 24 in. (61 cm) Behind Ball Ends	1,433 lb. (650 kg)		2,469 lb. (1 120 kg)	
DIMENSIONS				
Wheel Base (Non-Cab /Cab)	66 in. (168 cm)		73.2 in. (186 cm)	
Overall Width, with Standard Wheels /Tires	66.4 in. (169 cm)		69.1 in. (176 cm)	
Height to Top (Non-Cab /Cab)	93.5 in. (238 cm) to top of ROPS non-cab only		98.3 in. (250 cm) / 93.3 in. (237 cm)	
Weight (Non-Cab /Cab)	3,175 lb. (1 440 kg) non-cab only	3,803 lb. (1 725 kg) cab only	3,770 lb. (1 710 kg) / 4,453 lb. (2 020 kg)	

*at 2,600 ERPM rated engine speed

SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2019 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com CIH19051501

