

FARMALL TRACTORS

Make	Model	List Price	Discount
Farmall	45C	\$55,656.66	6%
Farmall	50C	\$56,673.11	6%
Farmall	55C	\$65,216.23	6%

6% discount provided on NCSA Heavy Equipment Procurement Bid 23-07-0421. products may be offered at a greater discount.

For more information, contact Jimmy Hicklin at jhicklin@hillsmachinery.com or call (803) 658-0200



FARMALL[®] COMPACT C

SERIES II TRACTORS

6% Discount







FARMALL COMPACT C SERIES II TRACTORS

4 Models | 35–55 HP | 28–47 PTO HP

BUYING A COMPACT TRACTOR DOESN'T MEAN SACRIFICING FEATURES FOR A COMPACT PRICE.

PLENTY OF POWER.

The Farmall compact C deluxe series tractors feature Tier 4 B/Final-compliant and fuel efficient engines, ranging from 35–55 engine horsepower. A 3-point hitch with a lift capacity of up to 2,756 pounds is ready to handle the implements of your choice. The fully independent PTO with electro-hydraulic engagement allows for simple, no-effort engagement every time.

A RANGE OF WAYS TO GET UP TO SPEED.

Farmall 35C and 40C offer a standard 12×12 gear transmission with synchronized shuttle, while the Farmall 45C and 55C offer a synchronized 16×16 gear transmission. All models offer a three-range hydrostatic transmission option, and mechanical front-wheel drive (MFD) gives you traction when you need it. When the going gets really tough, the differential-lock foot pedal locks both rear wheels together for additional traction.

BUILT TOUGH.

The deluxe series stands out with heavier frames, wider track widths and longer wheelbases for increased stability, plus exceptional loader lift and rear hitch capacity. Because of their size, maneuverability and physical capabilities, they are go-to workhorses — whether moving mulch with a loader, mowing a lawn with a mid-mount mower deck, moving bales to the feedlot, blowing snow or digging with a backhoe.



ALL WEATHER COMFORT & PRODUCTIVITY.

WELCOME THE FARMALL COMPACT C CAB MODELS.

In a market with no shortage of options, the Farmall compact C deluxe series stands out with three of the roomiest cab models available—the 40C*, 45C, and 55C. They offer the same deluxe features found in their non-cab counterparts, plus plenty more to help make your day more comfortable and productive, including:

- Easy entrance and exit on both sides
- Opening rear window for fresh air circulation and enhanced visibility
- A supportive, adjustable, cloth seat
- Wired for the radio of your choice
- 63 cu. ft. of interior space
- A comfort-creating HVAC system
- 47.9 sq. ft. of glass area for 360 degree views

DELUXE FEATURES THAT WORK HARD.

- 1 Opening rear window, supported by gas struts, with lower viewing window for increased visibility to drawbar, three-point hitch and remotes.
- 2 Convenient, easy-to-use controls with loader joystick integrated into the right-hand console (hydrostatic layout shown).
- 3 Roomy floor space with suspended brake pedals (hydrostatic layout shown) and thick rubber floor mat that dampens sounds and vibrations.
- 4 HVAC controls conveniently located in the headliner, including 4-speed fan, heat, A/C and defrost/defog controls, plus 8 HVAC vents throughout the headliner.



The large operator area with deluxe features on Farmall compact C cab and non-cab tractors provides outstanding operator comfort along with greater ease of operation. (Gear transmission layout shown here.)

* 40C offered in cab only



- A** Interior sun shade
- B** Multiple rear view mirrors
- C** Front windshield wiper and washer
- D** Standard loader joystick built into console
- E** Rubber floor mat
- F** Tilting steering wheel
- G** Easy-to-read digital dashboard and gauges
- H** Suspended brake pedals

Hydrostatic transmission controls layout shown here.

ULTIMATE OPERATOR ENVIRONMENT.

Farmall compact C deluxe tractors—both cab and non-cab models—provide an exceptional operating experience in a simple, easy-to-use machine. The large, roomy platform makes it easy to access and exit, and the enhanced control layout quickly turns novice users into expert operators. Both versions come with a generous list of standard equipment and features, including*:



*Ask your dealer about other options and available features.

A FULL LINE OF LOADERS, ATTACHMENTS AND IMPLEMENTS.

Choose from more than a dozen optional attachments that are quick and easy to switch out.



Model	Farmall 35C, 40C	Farmall 45C, 55C
Loader	L350A	L360A
Lift Capacity at Bucket Pivot Pin	2,000 lb. (907 kg)	2,500 lb. (1 134 kg)
Lift Capacity 19.7 in. (500 mm) from Bucket	1,540 lb. (699 kg)	1,830 lb. (830 kg)
Max Lift Height	105 in. (2 667 mm)	112.3 in. (2 852 mm)
Dump Angle at Full Height	58 degrees	49 degrees
Rollback Angle at Ground	30 degrees	39 degrees
Bucket	68 in. HD material bucket	72 in. HD material bucket

CASE IH LOADERS ARE READY TO WORK FOR YOU.

A loader turns a tractor into a versatile, powerful workhorse. And loaders are very easy to install on Farmall compact C series deluxe tractors: just drive the tractor into the loader, put in the pins, attach the hydraulics and start working! Curved-boom loader arms let you easily see to the top of the bucket and around the front tires.

QUICK AND EASY ATTACHMENTS AND IMPLEMENTS.

With a heavy-duty 3-point hitch, high-capacity responsive hydraulics and independent PTO, your Farmall C series deluxe tractor is ready for action.

- Side- and rear-discharge mowers (non-cab models only)
- Rear-mount finishing mower
- Front-mount rotary broom
- Rotary tiller
- Front-mount blade
- Front- and rear-mount snowblower
- Backhoe
- Rotary cutter
- Box blade
- Landscape rake
- Disk harrow
- Rear, 3-point mounted blade



FARMALL COMPACT C SERIES II SPECIFICATIONS

MODEL	FARMALL 35C (NON-CAB)	FARMALL 40C (CAB)	FARMALL 45C (NON-CAB/CAB)	FARMALL 55C (NON-CAB/CAB)
ENGINE				
Type	Diesel, 3 cyl., 1.9 L (116 cu in.), turbocharged, Tier 4 B/Final			
Engine HP*	35	40	45	55
Air Cleaner	Replaceable dry element			
Fuel System	Electronically-controlled, indirect injection			
Fuel Capacity (Non-Cab/Cab)	10.5 gal. (40 L) non-cab only	12.4 gal. (47 L) cab only	10.5 gal. (40 L)/12.4 gal. (47 L)	
Alternator	70 amp			
PTO				
PTO HP (Gear/Hydro)	29.7 / 28	34 / 32	38.2 / 36	46.7 / 44
PTO Speed	540 rpm			
PTO Type	Independent with electro-hydraulic engagement			
Mid-PTO Speed (Optional)	2,000 rpm			
TRANSMISSION				
Type (Standard/Optional)	12 × 12 shuttle shift/HST 3 range with cruise control		16 × 16/HST 3 range with cruise control	
Maximum Forward Speed (Gear/Hydro)	14.2 mph (22.9 kph) / 14.8 mph (23.9 kph)		16.9 mph (27.3 kph) / 17.9 mph (28.7 kph)	
Gear/Shuttle Type	Synchro			
Rear Diff. Lock Engagement	Mechanical			
Brake Type	Wet multi-disc			
HYDRAULIC SYSTEM				
Pump Flow	8.2 gpm (31.0 L/min)			
Steering Pump Flow	Gear: 4.2 gpm (15.9 L/min)/HST: 5.3 gpm (20 L/min)			
Remote Valves	1	2	Optional: 1 (non-cab) or 2 (non-cab or cab)	
Type	Standard flex lower links and telescopic stabilizers			
3-Point Hitch	1			
Lift Capacity @ Ball End	1,808 lb. (820 kg)		2,756 lb. (1250 kg)	
Lift Capacity @ 24 in. (61 cm) Behind Ball Ends	1,433 lb. (650 kg)		2,469 lb. (1120 kg)	
DIMENSIONS				
Wheel Base (Non-Cab/Cab)	66 in. (168 cm)		73.2 in. (186 cm)	
Overall Width, with Standard Wheels/Tires	66.4 in. (169 cm)		69.1 in. (176 cm)	
Height to Top (Non-Cab/Cab)	93.5 in. (238 cm) to top of ROPS non-cab only	88.5 in. (225 cm) cab only	98.3 in. (250 cm) / 93.3 in. (237 cm)	
Weight (Non-Cab/Cab)	3,175 lb. (1440 kg) non-cab only	3,803 lb. (1725 kg) cab only	3,770 lb. (1710 kg) / 4,453 lb. (2020 kg)	

*at 2,600 ERPM rated engine speed

SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2019 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com CIH19051501





FARMALL[®] COMPACT A

SERIES II TRACTORS







FARMALL COMPACT A SERIES II TRACTORS

2 Models | 32–36 HP | 35–40 PTO HP

RELIABLE. SIMPLE. VERSATILE. IT'S TIME TO GET BACK TO THE BASICS.

READY FOR ANY JOB.

Case IH Farmall compact A series tractors are rugged, reliable machines that tackle tough chores – plain and simple. A straightforward mechanical shuttle or hydrostatic transmission and easy-to-use controls let you focus on your task without distractions from complicated machine operations. The turbo diesel Tier 4 B/Final engine provides all the power you need for loading, blading, tilling, mowing and more. And the 3-point hitch and PTO allow you to attach a wide variety of implements.

The one-piece hood opens with the push of a button, allowing quick and easy access to all maintenance checkpoints. Cold weather starting is a snap with standard glow plugs.

The electronically-controlled indirect fuel injection provides:

- Faster throttle response and recovery under load
- Quieter engine operation with less vibration, reducing operator fatigue
- Greater torque rise creates greater lugging power to pull you through tough situations like moving heavy loads with a loader or cutting thick grass
- 300-hour engine oil service interval reduces downtime and maximizes uptime

IT'S TIME TO GET BACK TO THE BASICS.

With many standard features and numerous available options, the Farmall compact A series tractors are easy to operate, allowing you to complete those every day chores without hassle.



ROOM TO WORK. SIMPLE OPERATION.

The Farmall compact A series tractors open, semi-straddle operator's platform is stamped for good grip and to drain water and debris, with easy entrance from the right or left side. They feature a foldable ROPS for working in areas with low overheads. A FOPS canopy is also available for protection from sun, rain, etc.

All controls are within easy reach, and their functions and positions are common with those of the rest of the Farmall tractor series. The easy-to-read digital dashboard gauges feature temperature and fuel gauges, tachometer, hour meter and operational indicators just behind the standard tilt steering column.

PICK A TRANSMISSION THAT WORKS FOR YOU.

Choose from a straightforward mechanical shuttle or a hydrostatic transmission with easy-to-use controls that let you focus on your task without the distraction of complicated machine operations.

The standard 12×12 mechanical shuttle transmission has 3 ranges and 4 speeds for a total of twelve forward and twelve reverse gears.

An optional 3-range hydrostatic transmission offers infinitely variable speeds with a simple, comfortable 2-pedal operation – one forward and one reverse – as well as standard cruise control.

3-POINT HITCH.

The standard 3-point hitch has fixed lower links, single turnbuckle adjustment for leveling, and telescopic stabilizers. With a hitch lift capacity of 1,808 lbs. the Farmall compact A series tractors can pull a variety of implements from rear-mount finishing mowers to rotary tillers, disk harrows and more. Choose from the standard independent PTO with electro-hydraulic engagement with 540 rpm or the optional dealer-installed mid-PTO with 2,000 rpm for a mid-mount mower or front mount snow blower.

Two position drawbar comes standard on the Farmall compact A series tractors allowing you to customize hitched implements to your desired position.



- A** Clutch pedal
- B** Synchro shift control lever (gear models)
- C** Digital dashboard and gauges
- D** Electrohydraulic PTO engagement
- E** Brake pedals
- F** Parking brake
- G** Hand throttle
- H** Foot throttle
- I** Factory-installed loader joystick
- J** Differential lock pedal
- K** Transmission shift lever (gear models)
- L** Hitch lift control
- M** Adjustable suspension seat - flips forward to keep clean and dry
- N** 4WD lever
- O** Transmission range selector lever
- P** 3-point hitch drop rate control knob, under front of seat

Shuttle shift (gear transmission) model shown.

TIRE OPTIONS FOR ALL YOU DO.

Agricultural, turf and industrial tread pattern tires are available and recommended for Farmall compact A series tractors.



R-1 – AGRICULTURAL TREAD

Standard traction for agriculture applications.


Front Tires	Rear Tires
7×14 6PR (R1), opt.	11.2×24 4PR (R1), opt.



R-3 – TURF TREAD

Provide the least ground disturbance and are ideal for mowing and ground maintenance.

Front Tires	Rear Tires
25×8.50-14 4PR TL Turf (R3), opt.	41×14.00×20 4PR (R3), opt.



R-4 – INDUSTRIAL TREAD

Excellent utility tread that provides long life on hard surfaces like pavement plus a smoother ride while roading.

Front Tires	Rear Tires
25×8.50-14 6PR (R4), std.	43×16.00-20 4PR TL (R4), std.



A FULL LINE OF LOADERS, ATTACHMENTS AND IMPLEMENTS.

Choose from more than a dozen optional attachments that are quick and easy to switch out.



QUICK AND EASY ATTACHMENTS AND IMPLEMENTS.

With a heavy-duty 3-point hitch, high-capacity responsive hydraulics and independent PTO, your Farmall compact A series tractor is ready for action with the L340A loader and attachments, and any of the following implements:

- Side-discharge mid-mount mowers
- Rear-mount finishing mower
- Rotary tiller
- Backhoe
- Rotary cutter
- Box blade
- Landscape rake
- Disk harrow
- Rear, 3-point mounted blade
- Wheel rakes

CASE IH LOADERS ARE READY TO WORK FOR YOU.

A loader turns a tractor into a versatile, powerful workhorse. And loaders are very easy to install on Farmall compact A series tractors: just drive the tractor into the loader, put in the pins, attach the hydraulics and start working! The sleek design of the loader arms let you easily see to the top of the bucket and around the front tires.

A range of front and rear weights and ballast boxes are also available.

Model	Farmall 35A, 40A
Loader	L340A
Lift Capacity at Bucket Pivot Pin	1,250 lbs. (567 kg)
Lift Capacity 19.7 in. (500 mm) from Bucket	890 lbs. (404 kg)
Max Lift Height	98.4 in. (2 500 mm)
Dump Angle at Full Height	39 degrees
Rollback Angle at Ground	32 degrees
Bucket	68 in. HD material bucket

FARMALL COMPACT A SERIES II TRACTOR SPECIFICATIONS

MODEL	FARMALL COMPACT 35A		FARMALL COMPACT 40A
ENGINE			
Type	Diesel, 3 cyl., 1.9 L (116 cu in.), turbocharged, Tier 4 B/Final		
Engine HP*	35		40
Exhausts Treatment	Internal exhaust gas recirculation (EGR) with diesel oxidation catalyst (DOC) and Diesel Particulate Filter (DPF)		
Fuel Tank Capacity	7.4 gal. (28 L)		
System Rating / Alternator rating	12 volt/85 amp		
PTO			
PTO HP	28 – Hydrostatic transmission; 29.7 – Gear transmission		32 – Hydrostatic transmission; 34 – Gear transmission
PTO Speed	540 rpm		
PTO Type	Independent with electro-hydraulic engagement		
Mid-PTO (Optional) - Speed	2,000 rpm		
TRANSMISSION			
Type (Standard/Optional)	12×12 mechanical shuttle with synchro shift/3-range hydrostatic		
Maximum Forward Speed (Gear with R4 Tires)	14.2 mph (22.9 kph)		
Maximum Forward Speed (Hydrostatic with R4 Tires)	14.8 mph (23.8 kph)		
Differential Lock	Mechanical		
Brake Type	Wet multi disc		
HYDRAULIC SYSTEM			
System Type	Open center		
Pump Flow	8.2 gpm (31 L/min.)		
Steering Pump Flow	Gear: 4.2 gpm (15.9 L/min.)/HST: 5.3 gpm (19.9 L/min.)		
Remote Valves	Optional, 1 or 2		
3-POINT HITCH			
Type	CAT I with fixed link ends, turnbuckle lift link, and telescopic stabilizers		
Hitch Lift Capacity	1,808 lb. (820 kg)		
Lift Capacity at Ball End	1,433 lb. (650 kg)		
DIMENSIONS			
Length with 3-pt Hitch (Without Front Weights)	12.1 ft. (3.7 m)		
Wheelbase	5.6 ft. (1.7 m)		
Height to Top of ROPS	7.3 ft. (2.23 m)		
Width (Overall, Across Fenders)	3.6 ft. (1.1 m)		
Weight (ROPS with R4 Tires)	3,067 lb. (1 391 kg)		
TIRES			
Front Tire	25×8.5-14, R4		
Rear Tire	43×16.00-20, R4		

*At 2,600 rpm

SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2019 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com CIH19022101





FARMALL[®] COMPACT C

SERIES II TRACTORS







FARMALL COMPACT C SERIES II TRACTORS

4 Models | 35–55 HP | 28–47 PTO HP

BUYING A COMPACT TRACTOR DOESN'T MEAN SACRIFICING FEATURES FOR A COMPACT PRICE.

PLENTY OF POWER.

The Farmall compact C deluxe series tractors feature Tier 4 B/Final-compliant and fuel efficient engines, ranging from 35–55 engine horsepower. A 3-point hitch with a lift capacity of up to 2,756 pounds is ready to handle the implements of your choice. The fully independent PTO with electro-hydraulic engagement allows for simple, no-effort engagement every time.

A RANGE OF WAYS TO GET UP TO SPEED.

Farmall 35C and 40C offer a standard 12×12 gear transmission with synchronized shuttle, while the Farmall 45C and 55C offer a synchronized 16×16 gear transmission. All models offer a three-range hydrostatic transmission option, and mechanical front-wheel drive (MFD) gives you traction when you need it. When the going gets really tough, the differential-lock foot pedal locks both rear wheels together for additional traction.

BUILT TOUGH.

The deluxe series stands out with heavier frames, wider track widths and longer wheelbases for increased stability, plus exceptional loader lift and rear hitch capacity. Because of their size, maneuverability and physical capabilities, they are go-to workhorses — whether moving mulch with a loader, mowing a lawn with a mid-mount mower deck, moving bales to the feedlot, blowing snow or digging with a backhoe.



ALL WEATHER COMFORT & PRODUCTIVITY.

WELCOME THE FARMALL COMPACT C CAB MODELS.

In a market with no shortage of options, the Farmall compact C deluxe series stands out with three of the roomiest cab models available—the 40C*, 45C, and 55C. They offer the same deluxe features found in their non-cab counterparts, plus plenty more to help make your day more comfortable and productive, including:

- Easy entrance and exit on both sides
- Opening rear window for fresh air circulation and enhanced visibility
- A supportive, adjustable, cloth seat
- Wired for the radio of your choice
- 63 cu. ft. of interior space
- A comfort-creating HVAC system
- 47.9 sq. ft. of glass area for 360 degree views

DELUXE FEATURES THAT WORK HARD.

- 1 Opening rear window, supported by gas struts, with lower viewing window for increased visibility to drawbar, three-point hitch and remotes.
- 2 Convenient, easy-to-use controls with loader joystick integrated into the right-hand console (hydrostatic layout shown).
- 3 Roomy floor space with suspended brake pedals (hydrostatic layout shown) and thick rubber floor mat that dampens sounds and vibrations.
- 4 HVAC controls conveniently located in the headliner, including 4-speed fan, heat, A/C and defrost/defog controls, plus 8 HVAC vents throughout the headliner.



The large operator area with deluxe features on Farmall compact C cab and non-cab tractors provides outstanding operator comfort along with greater ease of operation. (Gear transmission layout shown here.)

* 40C offered in cab only



- A** Interior sun shade
- B** Multiple rear view mirrors
- C** Front windshield wiper and washer
- D** Standard loader joystick built into console
- E** Rubber floor mat
- F** Tilting steering wheel
- G** Easy-to-read digital dashboard and gauges
- H** Suspended brake pedals

Hydrostatic transmission controls layout shown here.

ULTIMATE OPERATOR ENVIRONMENT.

Farmall compact C deluxe tractors—both cab and non-cab models—provide an exceptional operating experience in a simple, easy-to-use machine. The large, roomy platform makes it easy to access and exit, and the enhanced control layout quickly turns novice users into expert operators. Both versions come with a generous list of standard equipment and features, including*:



*Ask your dealer about other options and available features.

A FULL LINE OF LOADERS, ATTACHMENTS AND IMPLEMENTS.

Choose from more than a dozen optional attachments that are quick and easy to switch out.



Model	Farmall 35C, 40C	Farmall 45C, 55C
Loader	L350A	L360A
Lift Capacity at Bucket Pivot Pin	2,000 lb. (907 kg)	2,500 lb. (1 134 kg)
Lift Capacity 19.7 in. (500 mm) from Bucket	1,540 lb. (699 kg)	1,830 lb. (830 kg)
Max Lift Height	105 in. (2 667 mm)	112.3 in. (2 852 mm)
Dump Angle at Full Height	58 degrees	49 degrees
Rollback Angle at Ground	30 degrees	39 degrees
Bucket	68 in. HD material bucket	72 in. HD material bucket


CASE IH LOADERS ARE READY TO WORK FOR YOU.

A loader turns a tractor into a versatile, powerful workhorse. And loaders are very easy to install on Farmall compact C series deluxe tractors: just drive the tractor into the loader, put in the pins, attach the hydraulics and start working! Curved-boom loader arms let you easily see to the top of the bucket and around the front tires.

QUICK AND EASY ATTACHMENTS AND IMPLEMENTS.

With a heavy-duty 3-point hitch, high-capacity responsive hydraulics and independent PTO, your Farmall C series deluxe tractor is ready for action.

- Side- and rear-discharge mowers (non-cab models only)
- Rear-mount finishing mower
- Front-mount rotary broom
- Rotary tiller
- Front-mount blade
- Front- and rear-mount snowblower
- Backhoe
- Rotary cutter
- Box blade
- Landscape rake
- Disk harrow
- Rear, 3-point mounted blade



FARMALL COMPACT C SERIES II SPECIFICATIONS

MODEL	FARMALL 35C (NON-CAB)	FARMALL 40C (CAB)	FARMALL 45C (NON-CAB/CAB)	FARMALL 55C (NON-CAB/CAB)
ENGINE				
Type	Diesel, 3 cyl., 1.9 L (116 cu in.), turbocharged, Tier 4 B/Final			
Engine HP*	35	40	45	55
Air Cleaner	Replaceable dry element			
Fuel System	Electronically-controlled, indirect injection			
Fuel Capacity (Non-Cab/Cab)	10.5 gal. (40 L) non-cab only	12.4 gal. (47 L) cab only	10.5 gal. (40 L)/12.4 gal. (47 L)	
Alternator	70 amp			
PTO				
PTO HP (Gear/Hydro)	29.7 / 28	34 / 32	38.2 / 36	46.7 / 44
PTO Speed	540 rpm			
PTO Type	Independent with electro-hydraulic engagement			
Mid-PTO Speed (Optional)	2,000 rpm			
TRANSMISSION				
Type (Standard/Optional)	12 × 12 shuttle shift/HST 3 range with cruise control		16 × 16/HST 3 range with cruise control	
Maximum Forward Speed (Gear/Hydro)	14.2 mph (22.9 kph) / 14.8 mph (23.9 kph)		16.9 mph (27.3 kph) / 17.9 mph (28.7 kph)	
Gear/Shuttle Type	Synchro			
Rear Diff. Lock Engagement	Mechanical			
Brake Type	Wet multi-disc			
HYDRAULIC SYSTEM				
Pump Flow	8.2 gpm (31.0 L/min)			
Steering Pump Flow	Gear: 4.2 gpm (15.9 L/min)/HST: 5.3 gpm (20 L/min)			
Remote Valves	1	2	Optional: 1 (non-cab) or 2 (non-cab or cab)	
Type	Standard flex lower links and telescopic stabilizers			
3-Point Hitch	1			
Lift Capacity @ Ball End	1,808 lb. (820 kg)		2,756 lb. (1250 kg)	
Lift Capacity @ 24 in. (61 cm) Behind Ball Ends	1,433 lb. (650 kg)		2,469 lb. (1120 kg)	
DIMENSIONS				
Wheel Base (Non-Cab/Cab)	66 in. (168 cm)		73.2 in. (186 cm)	
Overall Width, with Standard Wheels/Tires	66.4 in. (169 cm)		69.1 in. (176 cm)	
Height to Top (Non-Cab/Cab)	93.5 in. (238 cm) to top of ROPS non-cab only	88.5 in. (225 cm) cab only	98.3 in. (250 cm) / 93.3 in. (237 cm)	
Weight (Non-Cab/Cab)	3,175 lb. (1440 kg) non-cab only	3,803 lb. (1725 kg) cab only	3,770 lb. (1710 kg) / 4,453 lb. (2020 kg)	

*at 2,600 ERPM rated engine speed

SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2019 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com CIH19051501

