

6% Discount

RX-505 OPTIONS:	
Auxiliary Power	
4 kW Generator Set	
Additional Lighting	
24V LED Night Light Package	
Light set consisting of four 24V Lights, mounting hardware and wiring.	
Miscellaneous	
Automated Lubrication System	
Rear Object Detection System	
Automation - Grade and Slope Controls	
ACE Grade and Slope Automation with Auto-Cut	
Automates elevation of front and rear legs of milling machine by using grade sensors or a slope sensor for the right and left hand side of machine. System automates rear elevation of machine during entry of each cut. System includes 3 ACE Control panels that can be connected at the operator station and on the ground at the middle of the machine or in the rear to control both sides of the machine, 1 central microcontroller, 1 5-eye sonic sensor, plugs at side of machine for controls and sensors, mounting hardware, cables and junction boxes. Utilizes MOBA brand slope and sonic sensors.	
Prewiring for ACE Averaging Ski	
Includes junction boxes and cables to corners of machine for Averaging Ski, does not included sensors or mounting hardware.	
ACE - Single Averaging Ski - Requires Base System	
Provides averaging of grade for one side of machine. Junction box and sensor connections are installed on both sides of machine so sensors and arms can easily be swapped to either side of machine. Requires base ACE Grade and Slope Automation. Includes 2 sonic sensors with 5 transducers each. One for front and rear corner of machine, 2 junction boxes, cables and mounting hardware.	
ACE - Dual Averaging Ski - Requires both Single Ski and Base Systems	
Provides hardware to upgrade single averaging ski to dual averaging ski. Requires ACE Grade and Slope Automation and ACE Single Averaging Ski. Includes 2 sonic sensors with 5 transducers each. One for front and rear corner of machine, cables and mounting hardware.	
CUTTER HOUSINGS	
79" (2.0 m) Cutter Housing - CH505-79	

CH505-79 STANDARD FEATURES:	
Bolt-On Cutter Assembly With Mechanical V-Belt Drive	
O&K Cutter Gear Box	
Belt Lifting Device for Cutter Maintenance	
Drum Index	
Front & Rear Water Spray Bars with Flow and Pressure Control	
13" Depth of Cut with Sloped Front & Rear Moldboards	
Powered Wrap Around End Gates With Replaceable Wear Shoes	
"Ironclad" Cutter Housing Made of T-1 Steel with Chromium Clad Wear Liners	
CH505-79	
79" Housing (CUTTER HOUSING ONLY)	
CH505-79 OPTIONS	
Drum Options	
6'7" (79") (2.0 m) QX1 Single Hit Drum with 5/8" Spacing	
6'7" (79") (2.0 m) Kennametal Single Hit Drum with 5/8" Spacing	
86" (2.18 m) Cutter Housing - CH505-86	
CH505-86 STANDARD FEATURES:	
Bolt-On Cutter Assembly With Mechanical V-Belt Drive	
O&K Cutter Gear Box	
Belt Lifting Device for Cutter Maintenance	
Drum Index	
Front & Rear Water Spray Bars with Flow and Pressure Control	
13" Depth of Cut with Sloped Front & Rear Moldboards	
Powered Wrap Around End Gates With Replaceable Wear Shoes	
"Ironclad" Cutter Housing Made of T-1 Steel with Chromium Clad Wear Liners	
CH505-86	
86" Housing (CUTTER HOUSING ONLY)	
CH505-86 OPTIONS	
Drum Options	
7'2" (86") (2.18 m) QX1 Single Hit Drum with 5/8" Spacing	
7'2" (86") (2.18 m) Kennametal Single Hit Drum with 5/8" Spacing	
Warranties	
Roadtec Edge Extended Warranty (3 years or 3,000 hours total)	
Manufacturer's Extended Engine Warranty (5 years or 6,000 hours total)	