

<b>RX-600 STANDARD FEATURES:</b>
Engine Load Control
Automatic Traction Control
Front, Rear Auto-Center, Crab and Coordinated Steer
Direct Hydraulic Planetary Track Drives
Foot per minute meter
800 Gallon Water Tank with Three Fill Stations
High Pressure Wash Down System with Retractable Hose Reel
Hydraulic Variable Flow Water Pump
Auto on/off spray water system
32" Primary Conveyor With Endless Heavy Duty Belt
32" Secondary Conveyor With Endless Belt
Secondary Conveyor Has Full 120 Degree Swing Capability
Endless Belts with ¾" Tall Molded Rubber Cleats
Truck Rails on Secondary Conveyor
Self-Cleaning Head And Tail Pulleys
Left Side/Right Side Full Function Operators Control Stations
Lighted Instrument Console with Liquid Filled Gauges
Air Compressor With Reservoir
Operators Console Umbrella with Mounting Hardware
Ground Level Controls For Moldboard, End Gates & Elevation
Remote Grease Fittings Arranged In Zones
Light Package Consisting of Ten (10) 24 Volt Lights
Two magnetic base 24 VDC halogen work lights
Six 24 VDC power outlets.
Shock mounted operator's platform and console.
Polyurethane Bolt-On Replaceable Track Pads
Dust Extraction System
Safety Controls Including Emergency Engine Shut-Down,
Cutter Disengage and Engine Shut-Down when Cutter Door is Opened
Rear back-up camera
<b>RX-600e-4</b>
4 Track - Tier 4F Cummins QSX-15 Engine rated at 675 HP