

6% Discount

RP-170 OPTIONS:	
Undercarriage Options	
Front Wheel Assist	
Includes additional hydraulic motor on both rear bogie wheels.	
Screed Options	
Hydraulic Screed Assist Package	
Designed for use with Eagle Screed. Constant up pressure on screed essentially reducing its weight all the time while in Pave mode, whether in forward, neutral or reverse.	
Hydraulic Screed Boost Package	
Pressurizes the screed lift cylinders when the paver is in neutral and in pave mode to prevent depression in mat when paver stops. Lifting pressure is adjustable. Pressure is applied for adjustable time period once paver starts moving forward again. Time can be set at 0, 3 or 6 seconds.	
Electrical and Lighting Options	
24V LED Night Light Package	
Saber Light	
Two 92-watt, LED light panels provide over 10,000 lumens	
Airstar Balloon Light Assembly	
Includes Two 1,000 W Halogen Bulbs, Fan, Telescoping Pole, Two Brackets & Case	
Laser Pointer Alignment Guide	
High intensity laser mounted to tractor can be positioned along line of travel to aid operator in aligning paver correctly.	
Truck Dump Signal Light	
LED Signal light to indicate to truck driver whether to dump, stop or lower.	
One Additional Amber Beacon	
Material Feed System Options	
12" Left Hand ¾" Thick Ni-Hard Auger Extension	
12" Right Hand ¾" Thick Ni-Hard Auger Extension	
12" Tunnel Extension (Either Handed)	
12" Hydraulic Tunnel Extensions	
Auger Extension Remotes	
Remotes attached to fixed remote on left and right sides to controls augers and extensions. Includes a 6 ft cord and can be disconnected for storage.	
6' Tunnel and Auger Extension Package	

Extends Augers and Tunnels 3' to each side. Includes all necessary hardware to extend augers and tunnels 3' to each side including outboard auger bearing supports and tunnel extension braces. An additional 1' auger extension and 2- 1' tunnel extension segments can be added to each side. Does not include any screed extensions.	
Miscellaneous	
Guardian Telematics System	
Roadtec Guardian Telematics System to send and receive data remotely, with the ability to change function settings (One Year Free Subscription)	
Electrical Outlets	
4 outlets: 2 located on operator station and 2 located on back of tractor	
Truck Hitch In Lieu of Push Rollers	
Truck Hitch Plumbing	
Plumbing only for truck hitch	
Automated Lubrication System	
Reversing Distribution Augers	
Additional Umbrella	
Environmental Release Agent Spray Down System	
Includes 13 Gallon (49 L) Tank and Pump (Replaces Standard Wash-down)	
Soft Rubber Front Flashing	
Mass Flow Hopper Inserts	
RP-170/175 Self Relieving Hopper Insert	
RP-170/175 Hopper Insert Side Wall Extensions	
Mass Flow Low Profile Hopper Insert for 8' Pavers - Not Self Relieving	
Mass Flow Hopper Side Wall Extensions - for 8' Pavers	
Screed Automation - Grade And Slope Control	
TOPCON Sonic Grade And Slope Control	
Features Dual Sonic Grade Sensors And Single Slope Sensor.	
MOBA-MATIC II Sonic Grade And Slope Control	
Features MOBA MATIC II controller with Dual Sonic Grade Sensors And Slope Sensor.	
TOPCON Sonic Averaging Ski With Hardware	
Includes 3 Additional Sonic Trackers. (Requires Topcon Sonic Grade and Slope System)	
MOBA Sonic Averaging Ski With Hardware	
Includes 2 Additional Sonic Trackers. (Requires MOBA Sonic Grade and Slope System)	
MOBA Mounting Kit	
Provides hardware to easily install existing MOBA Grade & Slope System. Includes controller brackets, slope sensor, MOBA junction boxes, grade sensor mounts and arms. (Does not include sonics, controllers, or cables.)	
MOBA Slope Sensor	

MOBA Ski Hardware	
Provides physical ski, arms, sensor mounting poles, ski mounting hardware, and junction box to plug in sensors. (Does not include sensor cables.)	
TOPCON Mounting Kit	
Provides hardware to easily install existing TOPCON Grade & Slope. Includes controller brackets, slope sensor, MOBA junction boxes, grade sensor mounts and arms. (Does not include sonics, controllers, or cables.)	
TOPCON Slope Sensor	
SCREEDS	
S-8 FIXED WIDTH SCREED	
S-8 STANDARD FEATURES:	
8' (2.4m) Vibratory Standard Screed with 3' (0.9m) Hydraulic Strike-offs	
26" (660 mm) Long, ½" (12.5 mm) Thick 400 BHN Screed Plate	
Strike-off Articulation from 6.6% Positive to 3.3% Negative	
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM	
Power Crown, 3" (75 mm) Positive to 1" (25 mm) Negative	
Individual Lead and Tail Crown Adjustment	
18" (457 mm) Wide Full Width Hinged Heavy Duty Walkway	
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump	
Screed Plate Temperature Thermostatically Controlled with Adjustable Set Point	
4 KW @ 120 Volts Available for Accessory Use or Lighting	
Heater Hold-down System Allows Heater Change Without Removing the Screed Plate	
Spring Loaded Two Piece End Gates	
Sonic Feeder Control System	
Tow arms with mounting locations for automatic grade controls	
S-8	
S-8 OPTIONS:	
Angle of Attack Screws (Must Choose One)	
Clockwise Raise Angle of Attack Screws	
Counter-clockwise lowers	
Counter-Clockwise Raise Angle of Attack Screws	
Clockwise lowers - "Roadtec Standard"	
Screed Extensions	
6" Screed Extension	
12" Screed Extension With Heat	
24" Screed Extension With Heat and Vibration	
Attachments	

Left Hand Safety Edge Beveled Endgate	
Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	
Right Hand Safety Edge Beveled Endgate	
Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	
Remote Jumper Harnesses	
Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	
EZ-IV-8 FRONT EXTENDABLE SCREED	
EZ-IV-8 STANDARD FEATURES:	
8' (2.4 m) to 15' (4.5 m) Hydraulically Extendable Carlson Easy Screed IV with Wide Blade Electric Heat	
One 4' (1.2 m) Long & One 3' (0.9 m) Long Front Mounted Extensions	
Extensions Move on High Composite Bushings & Chrome Slide Track	
Extensions are 8" (203 mm) Wide, with Heat, Vibration and Adjustable Angle of Attack	
Front Mounted Extensions Provide 9% Positive Slope	
Electric Valves Control In/Out, Slope & Vertical Height	
Carlson's Patented "Front Taper Design" Main Screed	
Main Screed is 26" (660 mm) Long, ½" (12.5 mm) Thick 400 BHN Screed Plate	
Power Crown, 2½" (63 mm) Positive to ¾" (19 mm) Negative	
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump	
Thermostatically Controlled Plate Temperature with Analog Display	
5.5 KW @ 120 Volts Available for Accessory Use in 8 Outlets	
Heater Hold Down System Allows Heater Change Without Removing the Screed Plate	
Electrically Heated Oven for Warming Meals	
Spring Loaded Two Piece End Gates	
20" (508 mm) Wide Main Screed Hinged Heavy Duty Walkway	
12" (304 mm) Wide Hinged Extension Walkways	
Sonic Feeder Control System	
Tow arms with mounting locations for automatic grade controls	
EZ-IV-8	
EZ-IV-8 OPTIONS:	
Angle of Attack Screws (Must Choose One)	
Clockwise Raise Angle of Attack Screws	
Counter-clockwise lowers	
Counter-Clockwise Raise Angle of Attack Screws	
Clockwise lowers - "Roadtec Standard"	
Screed Options	

Pair of 12" Bolt-on Screed Extensions with Heat, Left and Right	
Pair of 18" Bolt-on Screed Extensions with Heat, Left and Right	
Pair of 24" Bolt-on Screed Extensions with Heat, Left and Right	
Beveled Edger for "Tapered Notch"	
For 12" Tapered Notched Wedge Joint One edger fits left or right side Heated	
Hydraulic Berm Builder with Electric Control Valves - 12" Left Hand	
Manual Adjust not Available - 12"	
Hydraulic Berm Builder with Electric Control Valves - 12" Right Hand	
Manual Adjust not Available - 12"	
Hydraulic Berm Builder with Electric Control Valves - 18" Left Hand	
Manual Adjust not Available - 18"	
Hydraulic Berm Builder with Electric Control Valves - 18" Right Hand	
Manual Adjust not Available - 18"	
Pair of Additional 6" Cut-off Shoes	
Left Hand Heated Safety Edge Beveled Endgate Shoe	
Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees. Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	
Right Hand Heated Safety Edge Beveled Endgate Shoe	
Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees. Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	
Pair of Heated End Gates	
Remote Jumper Harnesses	
Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	
EZ-R2-08 REAR EXTENDABLE SCREED	
EZ-R2-08 STANDARD FEATURES:	
8' to 15'6" Hydraulically Extendable Screed with Integral Rear Mounted Extensions	
Electric Heat with Thermostatically Controlled Temperature	
Screed Plates are 20" Wide, ½" Thick 450 BHN Material.	
Fully adjustable screed plates with adjustment cones on main and extensions.	
Fully adjustable Pre Strike-Off on Main and extensions	
Extensions Supported by Two 4" Guide tubes with Teflon Bushings.	
Exclusive Carlson slide track system allowing for adjustment of extension parallel	
Independent Angle of Attach Adjustments for Extensions.	
Extensions Provide 12% Positive Slope to 5% Negative Slope.	
Power Crown Provides 2" Positive to 1" Negative.	

Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM.	
18" Wide Full Width Telescoping Heavy Duty Walkway.	
Electric Valves Control Extensions, Slope, Crown & Vertical Height.	
Full Length Spring Loaded Two Piece End Gates.	
Rear Extensions	
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump	
4 kW @ 120 Volts Available for Accessory Use in Outlets	
Lighted Dual Screed Control Stations with Fixed Remote	
Material Height Control and Lockable Vandal Covers	
Sonic Feeder Control System	
Tow arms with mounting locations for automatic grade controls	
EZ-R2-08	
EZ-R2-08 OPTIONS:	
Angle of Attack Screws (Must Choose One)	
Clockwise Raise Angle of Attack Screws	
Counter-clockwise lowers	
Counter-Clockwise Raise Angle of Attack Screws	
Clockwise Lowers - "Roadtec Standard"	
Screed Options	
16" Screed Extension With Heat (each, can be left or right)	
28" Screed Extension With Heat (each, can be left or right)	
Pair of 1' RH & 1' LH Cut-off Shoes	
Pair of 2' RH & 2' LH Cut-off Shoes	
Left Hand Heated Safety Edge Beveled Endgate Shoe	
Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees. Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	
Right Hand Heated Safety Edge Beveled Endgate Shoe	
Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees. Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	
Heated Endgates	
Remote Jumper Harnesses	
Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	
Warranties	
Roadtec Edge Extended Warrantly - RP-170e (3 yr / 3000 hr Total)	
Roadtec Edge Extended Warrantly - RP-170ex (3 yr / 3000 hr Total)	
Manufacturer's Engine Ext. Warranty - RP-170e Tier 4 (5 yr / 6000 hr Total)	

Manufacturer's Engine Ext. Warranty - RP-170ex Tier 3 (5 yr / 6000 hr Total)