

RP-175 STANDARD FEATURES:				
Two (2) Comfort Drive Operators Stations with Common Control Operation Consoles and Total Control Joystick				
Total Control Joystick combines all tractor propel controls into single joystick				
Display at each operators station for engine diagnostics, paver diagnostics as well as speed and flow gate position				
Lighted Dual Screed Common Control "Pod" Stations for Head of Material and Screed Control				
Lighted Dual Screed Control Stations for head of material and screed control with Fixed Remotes and lockable vandal covers				
Operators stations hydraulically swing out past edge of machine for increased visibility				
1/2" (12.5 mm) Thick Grade 80 Continuous Side Sheet Frame Construction				
2 Hydraulically Driven Fans				
Oscillating Push Rollers				
Direct Hydraulic Planetary Drive				
Dual Brake System; Hydrodynamic, Parking				
11.5 Ton (10.4 MT) Capacity/200 ft ³ (5.7 m ³) Self Dumping Hopper				
Electric Flow Gates				
Independently Driven Variable Speed Feeder Conveyors				
1/2" (12.5 mm) cast head and tail plates with chromium carbide clad floor plates				
16" (406 mm) Cast Ni-hard Augers				
Hydraulically Raise, Lower and Tilting Auger Assembly				
Friction Drive Undercarriage				
24 Volt Electrical System with Master Disconnect Switch				
95 Amp Alternator				
Clearview FXS Fume Extraction System				
Amber Warning Beacon, Back Up Alarm and Fire Extinguisher				
One (1) Operators Umbrella				
Remote Central Point Tractor Lubrication				
Retractable Wash-down System with 30' (9.1 m) Hose Length (located on screed)				
81.5 Gallon (308.5 L) Fuel Tank Capacity				
Conveyor By-Pass Permits Independent Operation of Feeders				
8" (203 mm) Hydraulic Tunnel Extensions				
Road Light Package - Includes six 24V lights (2 hopper, 2 screed, 2 tunnel)				

Electrical wiring and hydraulic hoses for connection to screed				
RP-175e				
Cummins QSB6.7 Tier 4 Final @ 174 hp				