

6% Discount

<b>RP-175 OPTIONS:</b>	
<b>Screed Options</b>	
<b>Hydraulic Screed Assist Package</b>	
Designed for use with Eagle Screed. Constant up pressure on screed essentially reducing its weight all the time while in Pave mode, whether in forward, neutral or reverse.	
<b>Hydraulic Screed Boost Package</b>	
Pressurizes the screed lift cylinders when the paver is in neutral and in pave mode to prevent depression in mat when paver stops. Lifting pressure is adjustable. Pressure is applied for adjustable time period once paver starts moving forward again. Time can be set at 0, 3 or 6 seconds.	
<b>Additional Lighting</b>	
<b>24V LED Night Light Package</b>	
Includes Six 24V Lights	
<b>Saber Light</b>	
Two 92-watt, LED light panels provide over 10,000 lumens	
<b>Airstar Balloon Light Assembly</b>	
Includes Two 500 W Halogen Bulbs, Fan, Telescoping Pole, Two Brackets & Case	
<b>Laser Pointer Alignment Guide</b>	
High intensity laser mounted to tractor can be positioned along line of travel to aid operator in aligning paver correctly.	
<b>Truck Dump Signal Light</b>	
LED Signal light to indicate to truck driver whether to dump, stop or lower.	
<b>One Additional Amber Beacon</b>	
<b>Auger and Tunnel Extensions</b>	
<b>12" Left Hand ¾" Thick Ni-Hard Auger Extension</b>	
<b>12" Right Hand ¾" Thick Ni-Hard Auger Extension</b>	
<b>12" Tunnel Extension (Either Handed)</b>	
<b>Auger Extension Remotes</b>	
Remotes attached to fixed remote on left and right sides to controls augers and extensions. Includes a 6 ft cord and can be disconnected for storage.	
<b>6' Tunnel and Auger Extension Package</b>	
Extends Augers and Tunnels 3' to each side. Includes all necessary hardware to extend augers and tunnels 3' to each side including outboard auger bearing supports and tunnel extension braces. An additional 1' auger extension and 2- 1' tunnel extension segments can be added to each side. Does not include any screed extensions.	
<b>16' Auger and Tunnel Extension Package</b>	
Provides a total of 16' of augers and 16' of tunnels, can add additional 1' auger extension to each side for total of 18' of augers and additional 1' tunnel extension to each side for a total of 18' of tunnels	

<b>Miscellaneous</b>	
<b>Guardian Telematics System</b>	
Roadtec Guardian Telematics System to send and receive data at the machine or remotely, with the ability to change function settings (One Year Free Subscription)	
<b>Electrical Outlets</b>	
4 outlets: 2 located on operator station and 2 located on back of tractor	
<b>Truck Hitch In Lieu of Push Rollers</b>	
<b>Truck Hitch Plumbing</b>	
Plumbing only for truck hitch	
<b>Automated Lubrication System</b>	
<b>Reversing Distribution Augers</b>	
<b>Additional Umbrella</b>	
<b>Environmental Release Agent Spray Down System</b>	
Includes 20 Gallon (49 L) Tank and Pump (Replaces Standard Wash-down)	
<b>Soft Rubber front flashing</b>	
<b>Mass Flow Hopper Inserts</b>	
<b>RP-170/175 Self Relieving Hopper Insert</b>	
<b>RP-170/175 Hopper Insert Side Wall Extensions</b>	
<b>Mass Flow Low Profile Hopper Insert for 8' Pavers - Not Self Relieving</b>	
<b>Mass Flow Hopper Side Wall Extensions - for 8' Pavers</b>	
<b>Screed Automation - Grade And Slope Control</b>	
<b>TOPCON Sonic Grade And Slope Control</b>	
Features Dual Sonic Grade Sensors And Single Slope Sensor.	
<b>MOBA-MATIC II Sonic Grade And Slope Control</b>	
Features MOBA MATIC II controller with Dual Sonic Grade Sensors And Slope Sensor.	
<b>TOPCON Sonic Averaging Ski With Hardware</b>	
Includes 3 Additional Sonic Trackers. (Requires Topcon Sonic Grade and Slope System)	
<b>MOBA Sonic Averaging Ski With Hardware</b>	
Includes 2 Additional Sonic Trackers. (Requires MOBA Sonic Grade and Slope System)	
<b>MOBA Mounting Kit</b>	
Provides hardware to easily install existing MOBA Grade & Slope System. Includes controller brackets, slope sensor, MOBA junction boxes, grade sensor mounts and arms. (Does not include sonics, controllers, or cables.)	
<b>MOBA Slope Sensor</b>	
<b>MOBA Ski Hardware</b>	
Provides physical ski, arms, sensor mounting poles, ski mounting hardware, and junction box to plug in sensors. (Does not include sensor cables.)	

<b>TOPCON Mounting Kit</b>	
Provides hardware to easily install existing TOPCON Grade & Slope. Includes controller brackets, slope sensor, MOBA junction boxes, grade sensor mounts and arms. (Does not include sonics, controllers, or cables.)	
<b>TOPCON Slope Sensor</b>	
<b>SCREEDS</b>	
<b>S-8 FIXED WIDTH SCREED</b>	
<b>S-8 STANDARD FEATURES:</b>	
8' (2.4m) Vibratory Standard Screed with 3' (0.9m) Hydraulic Strike-offs	
24 Volt Electrical System (Tier 4 Final Machines Only)	
26" (660 mm) Long, ½" (12.5 mm) Thick 400 BHN Screed Plate	
Strike-off Articulation from 6.6% Positive to 3.3% Negative	
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM	
Power Crown, 3" (75 mm) Positive to 1" (25 mm) Negative	
Individual Lead and Tail Crown Adjustment	
18" (457 mm) Wide Full Width Hinged Heavy Duty Walkway	
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump	
Screed Plate Temperature Thermostatically Controlled with Adjustable Set Point	
4 KW @ 120 Volts Available for Accessory Use or Lighting	
Heater Hold-down System Allows Heater Change Without Removing the Screed Plate	
Spring Loaded Two Piece End Gates	
Sonic Feeder Control System	
Tow arms with mounting locations for automatic grade controls	
<b>S-8</b>	
<b>S-8 OPTIONS:</b>	
<b>Angle of Attack Screws (Must Choose One)</b>	
<b>Clockwise Raise Angle of Attack Screws</b>	
Counter-clockwise lowers	
<b>Counter-Clockwise Raise Angle of Attack Screws</b>	
Clockwise lowers - "Roadtec Standard"	
<b>Screed Options</b>	
<b>6" Screed Extension</b>	
<b>12" Screed Extension With Heat</b>	
<b>24" Screed Extension With Heat and Vibration</b>	
<b>Left Hand Safety Edge Beveled Endgate</b>	
Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	

<b>Right Hand Safety Edge Beveled Endgate</b>	
Special endgate with adjustable shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees.	
<b>Remote Jumper Harnesses</b>	
Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	
<b>EZ-IV-8 FRONT EXTENDABLE SCREED</b>	
<b>EZ-IV-8 STANDARD FEATURES:</b>	
8' (2.4 m) to 15' (4.5 m) Hydraulically Extendable Carlson Easy Screed IV with Wide Blade Electric Heat	
24 Volt Electrical System (Tier 4 Final Machines Only)	
One 4' (1.2 m) Long & One 3' (0.9 m) Long Front Mounted Extensions	
Extensions Move on High Composite Bushings & Chrome Slide Track	
Extensions are 8" (203 mm) Wide, with Heat, Vibration and Adjustable Angle of Attack	
Front Mounted Extensions Provide 9% Positive Slope	
Electric Valves Control In/Out, Slope & Vertical Height	
Carlson's Patented "Front Taper Design" Main Screed	
Main Screed is 26" (660 mm) Long, ½" (12.5 mm) Thick 400 BHN Screed Plate	
Power Crown, 2½" (63 mm) Positive to ¾" (19 mm) Negative	
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump	
Thermostatically Controlled Plate Temperature with Analog Display	
5.5 KW @ 120 Volts Available for Accessory Use in 8 Outlets	
Heater Hold Down System Allows Heater Change Without Removing the Screed Plate	
Electrically Heated Oven for Warming Meals	
Spring Loaded Two Piece End Gates	
20" (508 mm) Wide Main Screed Hinged Heavy Duty Walkway	
12" (304 mm) Wide Hinged Extension Walkways	
Sonic Feeder Control System	
Tow arms with mounting locations for automatic grade controls	
<b>EZ-IV-8</b>	
<b>EZ-IV-8 OPTIONS:</b>	
<b>Angle of Attack Screws (Must Choose One)</b>	
<b>Clockwise Raise Angle of Attack Screws</b>	
Counter-clockwise lowers	
<b>Counter-Clockwise Raise Angle of Attack Screws</b>	
Clockwise lowers - "Roadtec Standard"	
<b>Screed Options</b>	
<b>Pair of 12" Bolt-on Screed Extensions with Heat, Left and Right</b>	
<b>Pair of 18" Bolt-on Screed Extensions with Heat, Left and Right</b>	

<b>Pair of 24" Bolt-on Screed Extensions with Heat, Left and Right</b>	
<b>Beveled Edger for "Tapered Notch"</b>	
For 12" Tapered Notched Wedge Joint One edger fits left or right side Heated	
<b>Hydraulic Berm Builder with Electric Control Valves - 12" Left Hand</b>	
Manual Adjust not Available - 12"	
<b>Hydraulic Berm Builder with Electric Control Valves - 12" Right Hand</b>	
Manual Adjust not Available - 12"	
<b>Hydraulic Berm Builder with Electric Control Valves - 18" Left Hand</b>	
Manual Adjust not Available - 18"	
<b>Hydraulic Berm Builder with Electric Control Valves - 18" Right Hand</b>	
Manual Adjust not Available - 18"	
<b>Pair of Additional 6" Cut-off Shoes</b>	
<b>Left Hand Heated Safety Edge Beveled Endgate Shoe</b>	
Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees. Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	
<b>Right Hand Heated Safety Edge Beveled Endgate Shoe</b>	
Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees. Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	
<b>Pair of Heated End Gates</b>	
<b>Remote Jumper Harnesses</b>	
Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	
<b>EZ-R2-08 REAR EXTENDABLE SCREED</b>	
<b>EZ-R2-08 STANDARD FEATURES:</b>	
8' to 15'6" Hydraulically Extendable Screed with Integral Rear Mounted Extensions	
Electric Heat with Thermostatically Controlled Temperature	
Screed Plates are 20" Wide, ½" Thick 450 BHN Material.	
Fully adjustable screed plates with adjustment cones on main and extensions.	
Fully adjustable Pre Strike-Off on Main and extensions	
Extensions Supported by Two 4" Guide tubes with Teflon Bushings.	
Exclusive Carlson slide track system allowing for adjustment of extension parallel	
Independent Angle of Attach Adjustments for Extensions.	
Extensions Provide 12% Positive Slope to 5% Negative Slope.	
Power Crown Provides 2" Positive to 1" Negative.	
Eccentric Hydraulic Driven Vibrators, Adjustable 0-3000 VPM.	
18" Wide Full Width Telescoping Heavy Duty Walkway.	

Electric Valves Control Extensions, Slope, Crown & Vertical Height.	
Full Length Spring Loaded Two Piece End Gates.	
Rear Extensions	
Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump	
4 kW @ 120 Volts Available for Accessory Use in Outlets	
Lighted Dual Screed Control Stations with Fixed Remote	
Material Height Control and Lockable Vandal Covers	
Sonic Feeder Control System	
Tow arms with mounting locations for automatic grade controls	
<b>EZ-R2-08</b>	
<b>EZ-R2-08 OPTIONS:</b>	
<b>Angle of Attack Screws (Must Choose One)</b>	
<b>Clockwise Raise Angle of Attack Screws</b>	
Counter-clockwise lowers	
<b>Counter-Clockwise Raise Angle of Attack Screws</b>	
Clockwise Lowers - "Roadtec Standard"	
<b>Screed Options</b>	
<b>16" Screed Extension With Heat (each, can be left or right)</b>	
<b>28" Screed Extension With Heat (each, can be left or right)</b>	
<b>Pair of 1' RH &amp; 1' LH Cut-off Shoes</b>	
<b>Pair of 2' RH &amp; 2' LH Cut-off Shoes</b>	
<b>Left Hand Heated Safety Edge Beveled Endgate Shoe</b>	
Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees. Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	
<b>Right Hand Heated Safety Edge Beveled Endgate Shoe</b>	
Special adjustable endgate shoe to create beveled edge on mat. Manually adjustable from 90 degrees to 25 degrees. Includes heating element. Ships new in box with paver. Standard shoes installed on paver from factory.	
<b>Heated Endgates</b>	
<b>Remote Jumper Harnesses</b>	
Jumper harness that allows the fixed remote to be moved out from the left or right side when bolt on extensions are used on the screed.	
<b>Warranties</b>	
<b>Roadtec Edge Extended Warrantly - RP-175e (3 yr / 3000 hr Total)</b>	
<b>Roadtec Edge Extended Warrantly - RP-175ex (3 yr / 3000 hr Total)</b>	
<b>Manufacturer's Engine Ext. Warranty - RP-175e Tier 4 (5 yr / 6000 hr Total)</b>	
<b>Manufacturer's Engine Ext. Warranty for RP-175ex Tier 3 (5 yr / 6000 hr Total)</b>	