

**FARMALL 75C
US PRICE LIST****(Ex Works Port of Entry)
Standard Equipment****DIESEL ENGINE:****Farmall 75C**

74 Gross Engine hp
64 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
195 cu in (3.4 L) Displacement

US EPA Tier IV Emissions Compliant
Bosch Fuel Injection Pump
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Air Cleaner: Dry Type with Safety
Element
Fuel Sediment Filter with Water Sensor
23.8-gallon (90L) Fuel Tank with
Bottom Protection Shield

EXHAUST:

Under Hood Muffler with Vertical
Exhaust

TRANSMISSION:

11 Inch Clutch
Floor-mounted LH side Mechanical
Shuttle
(4) Synchronized Gears
(2) Non-synchronized Ranges
12 Forward and 12 Reverse Speeds
Forward Reverse Synchronized Shuttle
19 mph (30 kph) top speed
Speed varies with tire selection
Park Lock on Range Lever

AXLES:**MFD Front Axle:**

Electro-Hydraulic MFD Engagement
Adjustable Tread Width from 60.8 in.
to 76.6 in.
Limited Slip Differential Lock
Standard FAS Ready

AXLES: (Continued)**Rear Axle:**

Flange Type
Adjustable Tread Width 52.2 - 76.0 in.
Rear Differential Lock - MFD
mechanically engaged

TIRES:

Front MFD tires - 11.2-24 R1
Rear MFD tires - 16.9-30 R1

HYDRAULIC SYSTEM:

Open Center System - (1) Open
Center Remote Valve with detent
Dual Gear Pumps, (2) Couplers
Implement Pump: 12.5 gpm (47.5 L)
Steering Pump: 7.3 gpm (27.5 L)
Total Flow: 19.8 gpm (75L)

PTO:

540 rpm Mechanical PTO
(1-3/8 in. 6 splines)
Fully Independent, dry clutch
Mechanical Engagement
Flip-up PTO Shaft Guard

HITCH:

3-point Category II with flex lower links
and telescoping stabilizers
3664 lbs. Lift Capacity (SAE)
Swinging Drawbar
Mechanical Draft Control
Upper Link Draft Sensing

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulic assist wet brakes

INSTRUMENTATION:

Analog Instrumentation with warning
lights for air cleaner service,
alternator, oil pressure, fuel sediment
and water sensor, PTO engagement,
head light high beam, low fuel and
parking brake

**FARMALL 75C
US PRICE LIST**

**(Ex Works Port of Entry)
Standard Equipment**

INSTRUMENTATION: (continued)

Gauges for fuel level, engine temp.,
tachometer and hour meter
Horn

ELECTRICAL:

(1) 730 cca Heavy-duty Battery -ROPS
(1) 800 cca Heavy-duty Battery -Cab
Alternator: 120 amp
7-pin Outlet for trailer/implement
lighting and signals
4-pin Power Outlet (40 amp)

LIGHTING:

CAB

Front: (2) Halogen Headlights and
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

ROPS

Front: (2) Halogen Headlights
Rear: (1) Worklight,
Turn Signals/Flashers/Rear Lights

OPERATIVE PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, flat deck platform
with heat and air conditioning, tinted
windshield, retractable sun screen,
front wiper and washer, two doors
with locks, two external mirrors,
openable side windows, hinged rear
window (fully opens)
Steering Wheel - adjustable tilt
Seat - Cloth covered with mechanical
suspension, operator's presence
sensor, retractable seat belt, arm
rests
Suspended pedals
Radio, speakers and antenna

**OPERATIVE PROTECTIVE STRUCTURE:
(Continued)**

ROPS MODELS

2-Post Foldable ROPS with ISO
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Vinyl covered with mechanical
suspension, operator's presence
sensor, retractable seat belts,
arm rests
Suspended pedals
Locking brake pedals

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem, and Toolbox

NEBRASKA TEST REPORT STATUS:

Not available in Nebraska pending
Temporary Sales Permit

L620 Front Loader

STANDARD FEATURES:

Quick attach design:
Skid-Steer Style Tool Carrier
4-Bar bucket linkage
Bucket level indicator
Parking stand
Grille guard (included with front
mounting brackets)