



Description	
920 CATCH BASIN CLEANER 7'0" Retracted boom length 2-Piece boom extends and retracts hydraulically from 7'0" to 14' Hydraulic boom extender 2,000 lbs. – Winch single line lifting capacity 250 F.P.M. – Winch line speed 2,000 lbs. – Boom lifting capacity at 14' 5,700 lbs. – Boom lifting capacity at 5' Boom capacity limited to 1000 lb without stabilizer option 35' Maximum reach below ground (standard) Loader – telescopic boom Loader base has 3-point suspension design Fail-safe hydraulic planetary winch Lift cylinder and rod equipped with ball bushings Control valves and valve bracket with dual controls Open center hydraulic system All necessary hose and fittings Two hose reels with no less than 60' of ½" ID 2-wire rubber covered hoses Hose blocks, relief valves, etc. Paint: Two component acrylic polyurethane choice of black, white or orange. Cylinders, valve and bucket painted black. Contact factory for custom color requests Electric throttle control Grease manifold for upper and lower portion of single bronze bushing and swing rack back-up bushing 37 Gallon special heavy duty oil tank with baffles Body dumping from both sides of vehicle Body dumping safety device Boom up alarm 200° rack and pinion rotation Standard mast fits Ford F-550, 6 and IH CV. Submit chassis spec for review	
PTO- PUMP AND HYDRAULICS FOR CATCH BASIN CLEANER	
BASIN CLEANER DEBRIS BODY-- 304 STAINLESS STEEL	
8' Basin Cleaner Body 10 Ga. Stainless steel front, sides, and tailgate 7 Ga. Stainless steel 201 floor Crossmemberless, fabricated, fully boxed 8" longmembers 96" Long x 84" wide Water tight tailgate gasket Full perimeter splash shields Under-body hoist with OSHA safety prop Two (2) sets separate levers for identical operation of sectional control valve for body hoist cylinder, located on both sides of vehicle BACK UP ALARM	