



Description	
<b>950 CATCH BASIN CLEANER</b>	
<p>7'0" Retracted boom length</p> <p>2-Piece boom extends and retracts hydraulically from 7'0" to 13'</p> <p>Hydraulic boom extender</p> <p>2,000 lbs. – Winch single line lifting capacity</p> <p>250 F.P.M. – Winch line speed</p> <p>2,850 lbs. – Boom lifting capacity at 13'</p> <p>4,130 lbs. – Boom lifting capacity at 10'</p> <p>8,260 lbs. – Boom lifting capacity at 5'</p> <p>85" Height above frame with hose reel (travel)</p> <p>Boom capacity limited to 2000 lb without stabilizer option</p> <p>35' Maximum reach below ground (standard)</p> <p>Loader – telescopic boom</p> <p>Loader base has 3-point suspension design</p> <p>Fail-safe hydraulic planetary winch</p> <p>Lift cylinder and rod equipped with ball bushings</p> <p>Control valves and valve bracket with dual controls</p> <p>Open center hydraulic system</p> <p>All necessary hose and fittings</p> <p>Two hose reels with no less than 60' of ½" ID 2-wire rubber covered hoses</p> <p>Hose blocks, relief valves, etc.</p> <p>Paint: Two component acrylic polyurethane choice of black, white or orange.</p> <p>Cylinders, valve and bucket painted black. Contact factory for custom color requests</p> <p>Electric throttle control</p> <p>Grease manifold for upper and lower portion of single bronze bushing and swing rack back-up bushing</p> <p>37 Gallon special heavy duty oil tank with baffles</p> <p>Body dumping from both sides of vehicle</p> <p>Body dumping safety device</p> <p>Boom up alarm</p> <p>370° rack and pinion rotation</p> <p>Standard mast fits cab height up to 62" from top of frame to top of cab (for cab height over 62" see Tall Mast Option. Most cabs require Tall Mast)</p>	
<b>PTO- PUMP AND HYDRAULICS FOR CATCH BASIN CLEANER</b>	
<b>STANDARD BASIN CLEANER DEBRIS BODY-- 304 STAINLESS STEEL</b>	
<p>10' Basin Cleaner Body 6.7 CU Yards</p> <p>7 Gauge sides and ends (30")</p> <p>3/16" one-piece floor w/2" radius corners</p> <p>7 Cubic yard capacity</p> <p>120" Long x 84" wide side and end height</p> <p>Water tight tailgate gasket</p> <p>Full perimeter splash shields</p> <p>Class 50 hoist with OSHA safety prop</p> <p>Two (2) sets separate levers for identical operation of sectional control valve for body hoist cylinder, located on both sides of vehicle</p>	
<b>BACK UP ALARM</b>	
<b>BACK UP CAMERA</b>	