

Virginia Sheriffs' Association

Heavy Equipment Contract 23-04-0713

Item Number 250: MSAS Sign Alert Systems - ANY MUTCD#

<b><i>OPTIONS - Sign Alerts</i></b>		<b>MSRP</b>	<b>Discount</b>
<b>SA-ACPower</b>	Take away solar power pack and battery and add AC power supply and cabinet.	\$ (74.03)	10%
<b>ADD20W</b>	Additional 20 watt solar panel.	\$ 194.68	10%
<b>ADD-LED-KIT</b>	Includes LED, housing, and mounting bracket.	\$ 311.81	10%
<b>ADD-RRFB</b>	Add an additional RRFB with Confirmation Lights	\$ 481.16	10%
<b>BAT-12-18A</b>	18 amp, 12V, AGM battery; Dimensions:7.13"x2.99"x6.54"	\$ 71.11	10%
<b>BOLLARD</b>	Bollard - Height: 42"	\$ 270.27	10%
<b>BPMS</b>	Bollard Pedestrian Motion Sensor	\$ 297.30	10%
<b>DDB</b>	Drop-down box for controller.(Controller not included.)	\$ 154.36	10%
<b>SA-AG</b>	Anti-graffiti coating	\$ 68.87	10%
<b>SA-DG</b>	Use Diamond Grade sheeting instead of High Intensity sheeting.	\$ 60.15	10%
<b>SA-DG11</b>	Use Type 11 sheeting instead of High Intensity sheeting	\$ 106.05	10%
<b>SA-FYG</b>	Use flourescent yellow green sheeting instead of High Intensity sheeting.	\$ 106.05	10%
<b><i>Controls - Options</i></b>		<b>MSRP</b>	<b>Discount</b>
<b>Crosslink-USB-1</b>	USB Control Module with 900 mhz radio for programming crosstalks. (for use with units with radio only) Crosstalk Computer Software (CT-Computer-SW) required to operate.Approximate 1500 feet range.	\$ 375.38	10%
<b>CrossTalk-4-Upg</b>	Exchange Splasher for CrossTalk-4, add antenna kit (AntennaKit-1) and use appropriate size cabinet. (System requires minimum 20W solar.)	\$ 670.32	10%
<b>CrossTalk-CW-4-Upg</b>	Exchange Splasher for CrossTalk-CW-4, add antenna kit (AntennaKit-1) and use appropriate size cabinet.	\$ 799.09	10%
<b>CWKF-433-4</b>	Key Fob remote for Crosstalk/CWR for powering unit on; 700 ft line-of-sight range.	\$ 282.20	10%

<b>EC-HERC2MD</b>	Hercules Motion Detector, Mounting Height 6-1/2' to 23', Includes 23' of Cable, Voltage: 12-28VDC, 12-26VAC, Technology: Doppler Radar with Planar Module, Exterior	\$ 1,305.79	10%
<b>HWS</b>	High Water Sensor - 12V epoxy-coated sensor; housed in high impact PVC construction; will detect any conductive non-flammable liquid.	\$ 300.30	10%
<b>MS</b>	Moisture Sensor- Dual 12V epoxy-coated sensors; no mechanical parts; triggered by a moisture bridge across the sensor contacts.	\$ 225.23	10%
<b>DRSS400CFD</b>	SS400 Closed Frame Doppler Radar (300'+ range)	\$ 1,119.85	10%
<b>DR600CFD</b>	NEW DR600 Closed Frame Doppler Radar (2000'+ range; Replaced the DR500S)	\$ 1,226.89	10%
<b>SWK</b>	Switch, key operated.	\$ 105.11	10%
<b>THERMO</b>	Thermostat, NC-open on rise, 32 to 140F	\$ 110.79	10%

<b><i>Mounting Poles - Options</i></b>		<b>MSRP</b>	<b>Discount</b>
<b>CCTR-15</b>	COMPLETE 15' SPUN POLE KIT TO INCLUDE ALL MOUNTING HARDWARE. 15' crash tested 4" round aluminum spun pole with pedestal base, top cap, anchor bolts, signal mount and control box mount.	\$ 892.45	10%
<b>CCTS-12-2</b>	COMPLETE 12' GALVANIZED SQUARE POST KIT TO INCLUDE ALL MOUNTING HARDWARE. 12' crash tested 14 gauge; 2" with prepunched holes; 3' base (12 gauge; 2.25 " with bolt); 5/16 x 2 1/2" bolt (set of 2 per sign).	\$ 161.29	10%
<b>CCTUC-12</b>	COMPLETE 12' GALVANIZED U-CHANNEL POST TO INCLUDE ALL MOUNTING HARDWARE. 12' 3lb crash tested u-channel post with 3' 3lb u-channel post base (galvanized) and lap splice system (joins base post to top post. 5/16 x 2 1/2" bolt (set of 2 per sign).	\$ 182.80	10%
<b>MEZ31424A</b>	3" Z bar for 24" sign (2 qty) REQUIRES mounting hardware -CTR-MTK	\$ 91.65	10%
<b>MEZ31430A</b>	3" Z bar for 30" sign (2 qty) REQUIRES mounting hardware -CTR-MTK	\$ 105.89	10%
<b>MEZ31436A</b>	3" Z bar for 36" sign (2 qty) REQUIRES mounting hardware -CTR-MTK	\$ 128.26	10%
<b>MEZ31448A</b>	3" Z bar for 48" sign (2 qty) REQUIRES mounting hardware -CTR-MTK	\$ 164.81	10%