

Virginia Sheriffs' Association
Heavy Equipment Contract 23-04-0713
Item Number 259: MSAS Sign Alert Systems - YIELD

<i>OPTIONS - Sign Alerts</i>		MSRP	Discount
SA-ACPower	Take away solar power pack and battery and add AC power supply and cabinet.	\$ (74.03)	10%
ADD20W	Additional 20 watt solar panel.	\$ 194.68	10%
ADD-LED-KIT	Includes LED, housing, and mounting bracket.	\$ 311.81	10%
ADD-RRFB	Add an additional RRFB with Confirmation Lights	\$ 481.16	10%
BAT-12-18A	18 amp, 12V, AGM battery; Dimensions:7.13"x2.99"x6.54"	\$ 71.11	10%
BOLLARD	Bollard - Height: 42"	\$ 270.27	10%
BPMS	Bollard Pedestrian Motion Sensor	\$ 297.30	10%
DDB	Drop-down box for controller.(Controller not included.)	\$ 154.36	10%
SA-AG	Anti-graffiti coating	\$ 68.87	10%
SA-DG	Use Diamond Grade sheeting instead of High Intensity sheeting.	\$ 60.15	10%
SA-DG11	Use Type 11 sheeting instead of High Intensity sheeting	\$ 106.05	10%
SA-FYG	Use flourescent yellow green sheeting instead of High Intensity sheeting.	\$ 106.05	10%
<i>Controls - Options</i>		MSRP	Discount
Crosslink-USB-1	USB Control Module with 900 mhz radio for programming crosstalks. (for use with units with radio only) Crosstalk Computer Software (CT-Computer-SW) required to operate.Approximate 1500 feet range.	\$ 375.38	10%
CrossTalk-4-Upg	Exchange Splasher for CrossTalk-4, add antenna kit (AntennaKit-1) and use appropriate size cabinet. (System requires minimum 20W solar.)	\$ 670.32	10%
CrossTalk-CW-4-Upg	Exchange Splasher for CrossTalk-CW-4, add antenna kit (AntennaKit-1) and use appropriate size cabinet.	\$ 799.09	10%
CWKF-433-4	Key Fob remote for Crosstalk/CWR for powering unit on; 700 ft line-of-sight range.	\$ 282.20	10%

EC-HERC2MD	Hercules Motion Detector, Mounting Height 6-1/2' to 23', Includes 23' of Cable, Voltage: 12-28VDC, 12-26VAC, Technology: Doppler Radar with Planar Module, Exterior	\$ 1,305.79	10%
HWS	High Water Sensor - 12V epoxy-coated sensor; housed in high impact PVC construction; will detect any conductive non-flammable liquid.	\$ 300.30	10%
MS	Moisture Sensor- Dual 12V epoxy-coated sensors; no mechanical parts; triggered by a moisture bridge across the sensor contacts.	\$ 225.23	10%
DRSS400CFD	SS400 Closed Frame Doppler Radar (300'+ range)	\$ 1,119.85	10%
DR600CFD	NEW DR600 Closed Frame Doppler Radar (2000'+ range; Replaced the DR500S)	\$ 1,226.89	10%
SWK	Switch, key operated.	\$ 105.11	10%
THERMO	Thermostat, NC-open on rise, 32 to 140F	\$ 110.79	10%

<i>Mounting Poles - Options</i>		MSRP	Discount
CCTR-15	COMPLETE 15' SPUN POLE KIT TO INCLUDE ALL MOUNTING HARDWARE. 15' crash tested 4" round aluminum spun pole with pedestal base, top cap, anchor bolts, signal mount and control box mount.	\$ 892.45	10%
CCTS-12-2	COMPLETE 12' GALVANIZED SQUARE POST KIT TO INCLUDE ALL MOUNTING HARDWARE. 12' crash tested 14 gauge; 2" with prepunched holes; 3' base (12 gauge; 2.25 " with bolt); 5/16 x 2 1/2" bolt (set of 2 per sign).	\$ 161.29	10%
CCTUC-12	COMPLETE 12' GALVANIZED U-CHANNEL POST TO INCLUDE ALL MOUNTING HARDWARE. 12' 3lb crash tested u-channel post with 3' 3lb u-channel post base (galvanized) and lap splice system (joins base post to top post. 5/16 x 2 1/2" bolt (set of 2 per sign).	\$ 182.80	10%
MEZ31424A	3" Z bar for 24" sign (2 qty) REQUIRES mounting hardware -CTR-MTK	\$ 91.65	10%
MEZ31430A	3" Z bar for 30" sign (2 qty) REQUIRES mounting hardware -CTR-MTK	\$ 105.89	10%
MEZ31436A	3" Z bar for 36" sign (2 qty) REQUIRES mounting hardware -CTR-MTK	\$ 128.26	10%
MEZ31448A	3" Z bar for 48" sign (2 qty) REQUIRES mounting hardware -CTR-MTK	\$ 164.81	10%