



FEATURES

- ▶ Maintenance Free Batteries
- ▶ Long Lasting Battery Life
- ▶ Sealed Battery Box
- ▶ Single 140 Watt Solar Panel
- ▶ Meets MUTCD Standards
- ▶ Auto Dimming
- ▶ Super Bright LED Technology
- ▶ 360° of Rotation
- ▶ Durable Powder Coat Paint
- ▶ (4) Adjustable Corner Jacks and (1) Tongue Jack
- ▶ Sleek Frame Design

PORTABLE CHANGABLE MESSAGE BOARD

MODEL #MB8249

The MB8249 Full Matrix Message Board provides messaging functionality to display predefined and custom messages in three or four lines of alphanumeric text and MUTCD graphics/animations via an on-board controller. Our all LED display measures 82" x 49" and is mounted on a powder coat finished hydraulic style trailer.



Onboard Controller



MODEL #MB8249

PORTABLE MESSAGE BOARD

TRAILER MOUNT SERIES

TRAILER

Width: 68" fender to fender
Length with tongue: 148"
Length without tongue: 99"
Transport Height: 97"
Operating Height: 167"
Salt Spray: 1,000 hours
Paint: Powder Coat
Main frame: 2"x5"x1/8"
Front/Rear Cross members: 2"x3"x1/8"
Wheels: 15"
Axle: 3500 lbs double leaf spring
Fenders: High-density polyethylene
Jacks: (4) adjustable corner jacks & tongue jack with wheel
Tongue and Safety Chains: 2" ball hitch; 1/4" safety chains with hooks

SIGN DISPLAY

Pixel Matrix: 21x40 Pixel Arrangement
LED Module: Each is 5x7 matrix
LED's Per Pixel: 4
LED Type: Agilent amber 592NM
Viewing Angle: 30 degrees
Visibility: Up to 1 mile
Hours: 100,000 hour LED
Lines: Displays 3 lines of text and graphics
Characters per line: 8 characters (12 optional)
Character Height: 10"
**If one module fails, remainder of board is unaffected*

DISPLAY ENCLOSURE


Construction: Extruded Aluminum 6063 alloy
Length: 82"
Width: 49"
Depth: 6"
Paint: Powder coat paint
Salt Spray: 1000 hours
UV Resistant: 500 hours
Seal: Weather resistant
Venting: Vented top and bottom
Front face: 1/8" Lexan UV matte finish
Raising and lowering of display: Electro-hydraulic
Secondary raise and lowering: Manual hand pump

POWER AND CHARGING

Batteries: (4) 12 volt batteries for combined 400 amps
Battery Charger: 10 volt, 1000 watt, 60 amp
Recharge: 24 hours
Onboard diagnostics to monitor: Solar, battery, and load
Solar: (1) 140 watt solar panel
Regulator: 30 amp regulator with low voltage & high voltage disconnect.

CONTROLLER

Preprogrammed Messages: 260 including arrows and MUTCD symbols
User programmable: 100
Message Timing: Slow, medium, fast
Dimming: Auto or Manual
Protection: Password
Quick Message Selection: Thumbwheel to quickly select between 16 user programmable messages.
Controller Display: LCD
Data Entry: Mini Keyboard
Memory: Non volatile
**Pre-wired to accommodate radar, cell modem, and PC*
***"Auto Resume" after power failure*



K&K Systems' Quick Message Selection
Thumbwheel switches between the first 16 user defined messages. Roll the thumbwheel to desired message number to display a message.

OPTIONS

- ▶ Locking lug nuts
- ▶ Radar
- ▶ Pintle ring or bulldog hitch
- ▶ Electric or hydraulic brakes
- ▶ Custom Paint
- ▶ Outrigger Stability Supports
- ▶ Other Options available



888.414.3003 | (o) 662.566.2025 | (f) 662.566.7123
www.k-ksystems.com | sales@k-ksystems.com

