

Q12296-1

Quote Date: 7/11/2022
Expiration Date: 8/11/2022
Salesperson: Steve Tracy



Quote To Dealer:	End User:	Contact Information:
Direct Sale	Virginia Sheriff's Assn	Name:
Account Number:000001	901 E Byrd St	Phone: 8042257152
	Richmond, VA, 23219	Email:
		Account Number: 017454

Notes: VSA Heavy Equip Bid #23-04-0713
2 Ton Body & Crane Pkg.

---Service Body---

Body Type: H10025TT-2-84

Cost Variance Modifier (CVM), meaning that if inflation continues to accelerate, we will have no choice but to requote prior to line drawing approval and release for production. In the alternative, you may cancel orders (with applicable fees) any time prior to manufacture. Dealers, be sure to include this and notify your customers of the CVM possibility.

Delivery of service body units and lube units (installed on chassis or ship-out body) are to be arranged by either the selling dealer or end use customer; Maintainer does not arrange shipping of complete units

Chassis Disclaimer: All information and quote pricing shown with this proposal is based on a design utilizing the chassis make and model along with the specific features and options with the chassis as noted above. If any changes are made to the chassis type or options the proposal must be updated as they could change available unit features and options along with quote pricing. Any changes made without updating the quote will void this proposal.

Ex-factory delivery: 360-450 days after receipt of order with full order information subject to prior sales and chassis availability.

Config # C20775

Chassis: Kenworth T280 4x2 Allison 2000 87" CA Diesel (Cab Style not specified)

Factory Options Selected: Diesel Motor, Factory Backup Camera, Rear Spring Suspension, Vertical Exhaust, Single Fuel Tank

--- Maintainer Body ---

- Base price of Service body - 2-ton, 62" tall compartments, 54" x 31" wheel well opening with skirting, front body bulkhead, body access grab handles painted safety yellow (locations and number to vary with design)
- (11) Feet of Service Body - 2-ton, 62" tall Galvannealed compartments, with reinforced floors, clean out drains, 11 Gauge Deck Plate on Compartment Tops and Backs
- Factory Installation of body on a chassis. Note: On 2-ton chassis, we will no longer be modifying the dash for lights or switches. Will use OEM switches where applicable, any additional Maintainer switches will be on a bracket / panel mounted in separate location
- Tall Tower Crane reinforcement for MTS 1 or 2 ton service body (up to 75,000 ft*Lbs.)
- Crane Location : Curb Side

--- Chassis Equipment & Accessories ---

- Spring or spacer leveling package added to one side of chassis suspension (2-Ton)
- Electronic engine speed control - computer set - electronic engine
- 2.5 lb ABC fire extinguisher, and hazard reflectors
- Relocate chassis batteries - using existing cable length
- Back up alarm - 97 dB at 1 meter
- Camera, relocate existing chassis camera to rear of body Note: Requires factory installed monitor

--- Hydraulic Power Package ---

- Open center hydraulic power package NOTE: The Open-Center hydraulic system allows operation of only a single hydraulic component at a time. Multi-component operation requires a Closed-Center system and is not available on some chassis configurations. Contact factory for details. Contains HP Filter
- Open center hydraulic system pump (Chelsea) includes pressure reducer
- Oil reservoir - complete #022265, composite 28 gallons; Tank only, excluding oil
- (28) Hydraulic Oil (Standard oil, per gallon) Oil good for -25° F startup and 9° F to 187° F operating temperature
- No Reservoir Heater was selected.
- PTO for Allison automatic transmission

--- Welder / Generator / Inverter / Power Equipment ----- Air Compressor Equipment & Accessories ---

- No Air Compressor W/ Body

--- Outriggers & Accessories ---

- Outriggers for cranes up to 75,000 ft*Lbs., hydraulic up/down rear outriggers (2) with hydraulic extend in/out on crane side (48" extend)
- Outrigger pads, removable (with storage bracket)

--- Compartment Equipment & Accessories ---

- Pressurized Storage System (PSS), 2-blowers with filters
- (11) Feet of Master Compartment Locking System for steel body. Spring loaded with padlock guards for both side packs

--- Street Side Vertical Compartment #1 ---

- Dimensions:62" Tall X19" Wide X23" Deep
- Single 3/16" Aluminum Vertical hinge door, Includes Rubber Seal
- Standard Compartment 3-Point "D Ring" Door Latch
- Door Gas spring 65# (003184)

--- Street Side Vertical Compartment #2 ---

- Dimensions:62" Tall X35" Wide X23" Deep
- Vertical Double 3/16" Aluminum Doors (French Style), Includes Rubber Seal
- Standard Compartment 3-Point "D Ring" Door Latch
- (2) Door Gas spring 65# (003184)

--- Street Side Overwheel Compartment ---

- Dimensions:31" Tall X54" Wide X23" Deep
- Vertical Double 3/16" Aluminum Doors (French Style), Includes Rubber Seal
- Standard Compartment 3-Point "D Ring" Door Latch
- (2) Door Gas spring 65# (003184)

--- Street Side Rear Vertical Compartment ---

- Dimensions:62" Tall X24" Wide X23" Deep
- Single 3/16" Aluminum Vertical hinge door, Includes Rubber Seal
- Standard Compartment 3-Point "D Ring" Door Latch
- Door Gas spring 65# (003184)

--- Curb Side Vertical Compartment #1 ---

- Dimensions:62" Tall X19" Wide X23" Deep
- Single 3/16" Aluminum Vertical hinge door, Includes Rubber Seal
- Standard Compartment 3-Point "D Ring" Door Latch
- Door Gas spring 65# (003184)
- 2 Oxy/Act Bottle Storage Kit, contains Ratchet Strap, Vents in door,(2) "J" Hooks, reinforced floor and mounting side brackets

--- Curb Side Vertical Compartment #2 ---

- Dimensions:62" Tall X35" Wide X23" Deep
- Vertical Double 3/16" Aluminum Doors (French Style), Includes Rubber Seal
- Standard Compartment 3-Point "D Ring" Door Latch
- (2) Door Gas spring 65# (003184)

--- Curb Side Overwheel Compartment ---

- Dimensions:31" Tall X47" Wide X23" Deep
- Vertical Double 3/16" Aluminum Doors (French Style), Includes Rubber Seal
- Standard Compartment 3-Point "D Ring" Door Latch
- (2) Door Gas spring 65# (003184)

--- Curb Side Under Crane Compartment ---

- Dimensions:25" Tall X24" Wide X14" Deep
- Single 3/16" Aluminum Vertical hinge door, Includes Rubber Seal
- Standard Compartment 3-Point "D Ring" Door Latch

Q12296-1

- Door Gas spring 65# (003184)

--- Lighting / Electrical Equipment & Accessories ---

- Base electrical components - Can System Includes Wiring Harnesses, Power Distribution Module, & Main Body Controller
- 4.3" display CAN switch panel
- ~Grote FMVSS 108 LED lighting / reflector Kit: (2) Oval S/T/T/R, (2) Oval S/T/T, (5) Red 3/4" Marker lights, (2) Amber 3/4" Marker lights
- Exterior 12-Volt LED flood light 022232 (2,100 Lumens)
- ~Strobe Lightheads, L.E.D, oval, amber, recessed, 6.5" x 2.25" (pair)

--- Paint, Undercoating, & Protective Spray Coating (PSC) ---

- (11) Feet of Unit Painted Urethane "White" color. Not a base coat/clear coat or Metallic
- (11) Feet of Primer
- (11) Feet of Splatter Coating on interior of compartments
- (11) Feet of Undercoat
- (11) PSC-Cargo floor (per foot)
- (11) PSC-Cargo side walls (per foot)
- (11) PSC-Compartment Tops (per foot)
- (11) PSC-Bottom door frames of compartments (bottom faces)
- PSC-Compartment fronts
- PSC-Outside area of wheel wells
- PSC-Outer vertical outrigger tubes
- PSC-Cargo front bulkhead
- PSC-Tail gate front
- PSC-Bumper area vertical surfaces
- PSC-Bumper top surface
- PSC-Rear bumper face & step surface

--- Center Deck Equipment & Accessories ---

- Center Deck Dimensions:132" Long X49" Wide X1/8" Thickness
- (11) ~1/8" Cargo floor (deck plate)
- 10" Tall hinge-down "Slam Latch" Aluminum tailgate (12" total Height, 10" tall above deck)• 10" Tall tailgate extension panel
- (6) Flush mount "D" ring tie-downs in bed floor #003217, each

--- Rear Bumper & Accessories ---

- 26" steel workbench bumper with recessed step on curb side, 1 storage compartment. Includes: Bolt on Yellow grab handles and strip light for recessed step safety, Includes a stainless steel rear bumper shell.
- ~Bumper surface 3/16" smooth
- ~Transverse bar storage compartment in workbench bumper flush to the floor
- Vise / grinder removable mounting plate HD, includes drain slots in plate
- Class IV hitch receiver - 2" receiver - rated at 1,500 Lbs.. vert. 10,000 Lbs. Includes Safety Chain loops MGTW Note: customer is responsible to verify tow rating of chassis and available GVWR/GCWR remaining after loading of body and all other items.
- No trailer plug selected
- Step, Bolt-on, flexible sides with stainless steel step, Painted Safety Yellow #026127 (standard step)

--- Miscellaneous Equipment & Accessories ---

- Single axle wheel well extensions (3-piece bolt-on), aluminum w/ protective spray. Note: Kit includes flares for both sides of body
- Mud flaps, 2-ton, "Maintainer"
- Mud flap bracket for a 20" mudflap
- Parts and service manual (Online & condensed paper version)

---Maintainer Crane---

Config # C20776

Q12296-1

- H10025TT Crane 10,000 Lbs. max capacity (75,000 ft*Lbs.) with hydraulic extend hex-boom 13'-25' Note: Max capacity listed above is for 2-part line, for single-part line max capacity is 5,000 Lbs. Crane includes A2B, overload system, holding valves ACC 2.1 (crane lifting weight display, capacity & speed limiting, stability monitoring, warn / stop feature) Paint note: Ship-out crane-only: Requires additional paint charge Crane installed on body: No additional paint charge unless different color than body MIN GVW REQUIRED : 26,000
- Install hydraulic crane on body - includes boom saddle, and valve well with HD reinforced cover
- ~Load Block (No live swivel) H6-H10
- Planetary winch (H6-H10) TI2
- Crane remote, wireless, push button (H6-H14), with true independent proportional control, includes holder, external antenna, hour meter, engine start/stop
- Backup cable for wireless crane remote, 35ft (#022585)
- Annual crane inspection (initial inspection)
- Paint Crane to match Service Body
- Exterior 12v LED flood light on crane boom tip (2-Lights, Ecco E92006, 1365 Lumens) on pivot bracket

---Non-Standard Sales Kits---

- Price Adjustment for revision to Quote

---Notes---

~All prices are F.O.B. - Factory (Sheldon, IA)

~Additional items may be added, and changes are acceptable. Specs vary depending on chassis details. Please consult with your Maintainer representative for details and final pricing.

Maintainer Terms and Conditions

- All prices are F.O.B. Sheldon, IA and in USD; Delivery of service and lube units are the dealer / end user's responsibility. This quote does not include any applicable local, state or (F.E.T) federal taxes. Payment in full is required on delivery unless other terms are agreed upon prior to sale.
- Ex-factory delivery is 360-450 days after receipt of order with full order information subject to prior sales and chassis availability.
- Orders that are cancelled after booking will be subject to a \$500 cancellation processing fee, in addition to any restocking or costs for parts purchased for the cancelled unit. The fee will cover our incurred costs to process the order, plan production and released purchasing commitments. Orders are considered firm upon chassis confirmation, units are committed to a build slot, and serial numbers are assigned.
- Changes to booked orders are subject to change order fees. We have historically allowed flexibility on rearranging your builds order prior to week 10, if the swap is without changes to either spec. Units already released for production (weeks 8-10) will be reviewed on a case-by-case basis, but generally it is too late. It is possible they could be reassigned to the offline upfit department and you can get a quote for the changes.
- Maintainer reserves the right to make changes and/or substitute components and product is subject to change without notice; Maintainer is not responsible for any Local, State, Federal or other regulations that maybe pertinent to quote/order.
- The information contained in this quote, and all supporting documentation is confidential and may only be used by Maintainer, our dealer and/or the customer listed on this quote.
- We assume no liability for damage due to theft, vandalism, fire, weather, disaster, or damage due to gradual deterioration or inherent defect in such property.
- We assume no liability for damage any kind during the storage of your chassis or parts on our premises while awaiting modification or installation. The storage location of the property shall be determined by Maintainer in its discretion.
- Exception to above is when directly attributable to our own gross negligence in moving or modifying chassis or parts, and in that event only to the extent of the wholesale used value of the chassis or parts as of the date of storage.