

Prepared For:

Virginia Sheriffs' Association
Kaylyn Mitman
901 E Byrd St.
Richmond, VA 23219-4052
(804)225 - 7152
Reference ID: N/A

Presented By:

LILLEY INTERNATIONAL
TROY WARD
US HWY 17 BY PASS
WILLIAMSTON NC 27892 -
(252)792-4192

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2024 HX520 SFA (HX520)

AXLE CONFIG:	6X4
MISSION:	Requested GCWR: 66000. Calc. GCWR: 115000. Calc. GVWR: 59200 Calc. Geared Speed: 88.5 MPH
DIMENSION:	Wheelbase: 222.00, CA: 132.00, Axle to Frame: 59.00
ENGINE, DIESEL:	{Cummins X15 525} Performance Series, EPA 2021, 525HP @ 1900 RPM, 1850 lb-ft Torque @ 1000 RPM, 1900 RPM Governed Speed, 538 Peak HP (Max)
TRANSMISSION, MANUAL:	{Fuller RTLO-18913A} 13-Speed Manual, Double Overdrive, Air Shift, Internal Lube Oil Pump
CLUTCH:	{Eaton Fuller Advantage} Self-Adjusting, 15.5" Dia Two-Plate, Cast Angle Spring, Ceramic, 7-Spring Coaxial VCT Plus Damper, 2"-10 Tooth Spline, Mechanical Pull Type Control, 6-Button Disc, 2050 lb-ft Torque Capacity
AXLE, FRONT NON-DRIVING:	{Meritor MFS-13-143A} Wide Track, I-Beam Type, 13,200-lb Capacity
AXLE, REAR, TANDEM:	{Meritor RT-46-160} Single Reduction, 46,000-lb Capacity, Driver Controlled Locking Differential in Rear-Rear Axle, 200 Wheel Ends Gear Ratio: 3.73
CAB:	Conventional, Day Cab
TIRE, FRONT:	(2) 11R24.5 Load Range H ECOPLUS HS3+ (CONTINENTAL), 473 rev/mile, 75 MPH, All-Position
TIRE, REAR:	(8) 11R24.5 Load Range H G182 RSD (GOODYEAR), 473 rev/mile, 75 MPH, Drive
SUSPENSION, REAR, AIR, TANDEM:	{Hendrickson HAS-460-55} 46,000-lb Capacity, 55" Axle Spacing, 9.5" Ride Height, with Shock Absorbers, Mounted Inboard
PAINT:	Cab schematic 21ALY Location 1: 6M75, Spectrastar Blue Pearl Met (Custom) Location 2: 6E06, Blue Metallic (Prem) Chassis schematic N/A

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
HX52000	Base Chassis, Model HX520 SFA with 222.00 Wheelbase, 132.00 CA, and 59.00 Axle to Frame.	8886/7472	16358

AXLE CONFIGURATION

1AND	AXLE CONFIGURATION {Navistar} 6x4	0/0	0
	<u>Notes</u> : Pricing may change if axle configuration is changed.		

ENGINE

12ENZ	ENGINE, DIESEL {Cummins X15 525} Performance Series, EPA 2021, 525HP @ 1900 RPM, 1850 lb-ft Torque @ 1000 RPM, 1900 RPM Governed Speed, 538 Peak HP (Max)	0/0	0
12XCS	CARB EMISSION WARR COMPLIANCE Federal, Does Not Comply with CARB Emission Warranty	0/0	0
12WZE	CARB IDLE COMPLIANCE Federal, Does Not Comply with California Clean Air Idle Regulations	0/0	0
12VHZ	EMISSION, CALENDAR YEAR {Cummins X15} EPA, OBD and GHG Certified for Calendar Year 2022	0/0	0
12XBC	RADIATOR Aluminum, Welded, Down Flow, Front to Back System, 1325 SqIn, with 806 SqIn Charge Air Cooler	0/0	0
	<u>Includes</u> : RADIATOR HOSES Premium, Rubber		
12THT	FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed	0/0	0
	<u>Includes</u> : FAN Nylon		
12VBA	AIR CLEANER Dual, Polished Stainless Steel, One Mounted on Each Side of Cowl Ahead of The Doors	29/7	36
12703	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection	0/0	0
12WTA	FAN DRIVE SPECIAL EFFECTS Fan Cooling Ring with Fan Shroud Effects, Engine Mounted	0/0	0
12WCX	HOSE CLAMPS, RADIATOR HOSES {Gates} Shrink Band Type	0/0	0
12WYZ	RADIATOR DRAIN & FILL FITTING SPECIAL; To Vacuum Out or Fill the Cooling System from the Bottom of Radiator, for Use with Quick-Connect Radiator Drain Tool or Shop Coolant Evacuation-Fill System	0/0	0

TRANSMISSION

13GJS	TRANSMISSION, MANUAL {Fuller RTLO-18913A} 13-Speed Manual, Double Overdrive, Air Shift, Internal Lube Oil Pump	-103/-39	-142
13WAS	CLUTCH HOUSING Aluminum; Available with 1350 to 2050 lb-ft Capacity Fuller Transmissions	-41/-12	-53
13WGJ	OIL COOLER MANUAL TRANSMISSION Water to Oil Type Included in Radiator End Tank (REQUIRES TRANSMISSION LUBE PUMP)	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
13XAA	PTO CONTROL, DASH MOUNTED For Customer Provided PTO; Includes Switch, Electric/Air Solenoid, Piping and Wiring	0/0	0
13WLX	TRANSMISSION OIL {EmGard 40W} Synthetic; 22 thru 33.99 Pints	0/0	0
CLUTCH			
11MRR	CLUTCH {Eaton Fuller Advantage} Self-Adjusting, 15.5" Dia Two-Plate, Cast Angle Spring, Ceramic, 7-Spring Coaxial VCT Plus Damper, 2"-10 Tooth Spline, Mechanical Pull Type Control, 6-Button Disc, 2050 lb-ft Torque Capacity	-7/-1	-8
11WAK	CLUTCH EFFECTS Hydraulic Clutch Actuation System, with Air Assist	0/0	0
REAR AXLES, SUSPENSIONS			
14GRP	AXLE, REAR, TANDEM {Meritor RT-46-160} Single Reduction, 46,000-lb Capacity, Driver Controlled Locking Differential in Rear-Rear Axle, 200 Wheel Ends . Gear Ratio: 3.73	0/495	495
14ULT	SUSPENSION, REAR, AIR, TANDEM {Hendrickson HAS-460-55} 46,000-lb Capacity, 55" Axle Spacing, 9.5" Ride Height, with Shock Absorbers, Mounted Inboard	0/-68	-68
14862	PDL WARNING BUZZER Power Divider Lock	0/0	0
14899	SUSPENSION AIR CONTROL VALVE Pressure Release Control In Cab	0/0	0
FRONT AXLES			
2ASG	AXLE, FRONT NON-DRIVING {Meritor MFS-13-143A} Wide Track, I-Beam Type, 13,200-lb Capacity	60/0	60
FRONT SUSPENSIONS			
3ADD	SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 14,000-lb Capacity, with Shock Absorbers	13/0	13
CABS, COWLS, BODIES			
16030	CAB Conventional, Day Cab	0/0	0
	Includes		
	: CAB REAR SUSPENSION Air		
	: CLEARANCE/MARKER LIGHTS (5) LED Roof Mounted		
	: COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window		
	: CONSOLE, CENTER Includes Two Cup Holders and One Additional Storage Area		
	: CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger		
	: COURTESY LIGHT (2) Driver and Passenger Door Mounted		
	: DOME LIGHT, CAB Rectangular, Door and Instrument Panel Mounted Switch Activated, Timed Theater Dimming, Center Mounted, Integral to Console		
	: FLOOR COVERING Rubber, Black		
	: GLASS, ALL WINDOWS Tinted		
	: GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side		
	: GRAB HANDLE, CAB INTERIOR (4) "B" Pillar and Door Mounted, Two Each Side		
	: READING LIGHT, CAB Located in Overhead Console		
	: STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door		

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
16ZHZ	ACCESS, CAB AND FRAME Aluminum, Self-Cleaning, Open and Serrated Design, Driver & Passenger Sides, Two Steps per Door; Left Side Frame Access Step, Includes One Deck Plate and Grab Handle, for use with Day Cab, Extended Cab or Sleeper Cab	-11/47	36
16BAM	AIR CONDITIONER with Integral Heater and Defroster	0/0	0
	<u>Includes</u> : HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps		
16XCM	CAB DOOR LOCKS Power, Driver Side Only; Non-Locking When Door Open	0/0	0
16VVB	CAB INTERIOR TRIM Diamond Elite, for Day Cab	0/0	0
	<u>Includes</u> : DOOR TRIM, INTERIOR Bright Handle : INSTRUMENT PANEL TRIM Black with Woodgrain Accent, Black Gauges with Chrome Bezels : SUN VISOR (4) Padded Vinyl, 2 Moveable (Front-to-Side) Primary Visors and 2 Flip-down Auxiliary Visors; Vanity Mirrors and Toll Ticket Straps Driver and Passenger Sides		
16GDG	GAUGE CLUSTER Premium Level; English with English Speedometer and Tachometer, for Air Brake Chassis, Includes Engine Coolant Temperature, Primary and Secondary Air Pressure, Fuel and DEF Gauges, Oil Pressure Gauge, Includes 5 Inch LCD Color Display	0/0	0
16HHE	GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} with Black Bezel, Mounted in Instrument Panel	2/0	2
16AAH	GAUGE, AIR PRESSURE for Pressure in Rear Air Suspension, Mounted in Instrument Center Panel	0/0	0
16HGL	GAUGE, OIL TEMP, REAR AXLE	1/0	1
16SDC	GRAB HANDLE, EXTERIOR (2) Chrome, Towel Bar Type, with Anti-Slip Rubber Inserts, for Cab Entry Mounted Left and Right Side at B-Pillar	6/0	6
16564	HEATER SHUT-OFF VALVES (1) Ball Valve Type, Supply Line	5/0	5
16XJP	INSTRUMENT PANEL Wing Panel	0/0	0
16HKT	IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster	0/0	0
16WKZ	KEYLESS ENTRY SYSTEM REMOTE with Panic and Auxiliary Buttons, Includes One Key Fob (Transmitter)	2/0	2
16SNX	MIRROR, CONVEX, LOOK DOWN Right Side, Bright, 6" x 10.5"	3/0	3
16SNV	MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Turn Signals, Bright Heads, Black Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width	0/0	0
	<u>Notes</u> : Mirror Dimensions are Rounded to the Nearest 0.5"		
16XPT	MODESTY PANEL Chrome, with Clear Lens LED Lights, for Day Cab	0/0	0
16LWU	SEAT, DRIVER {ISRI} Series 500, Air Suspension, High Back, Synthetic Leather, Adjustable Bolsters, Double Chamber Lumbar, Heat, Ventilation, Inboard Armrest, Adjustable Shocks, Suspension Cover, Fore/Aft Isolator, Cushion Extension, Seat Tilt, Memory Quickdown	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
16SRL	SEAT, PASSENGER {National} Non Suspension, High Back with Integral Headrest, Synthetic Leather, with Fixed Back, with Under Seat Storage	27/13	40
16UZJ	STORAGE, REAR WALL Storage Pocket, Located on Back Wall Between Driver and Passenger Seats	3/0	3
16XWE	SUNSHADE, EXTERIOR Bright Finish, with Integral Clearance/Marker Lights	18/3	21
16WJU	WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature	0/0	0
16XDD	WINDOW, REAR Polycarbonate Plastic Window, Shatter Resistant	-4/-1	-5
16VSL	WINDSHIELD Heated, Single Piece	0/0	0

FRAMES

1CAG	FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.250" x 3.610" x 0.375" (260.4mm x 91.7mm x 9.5mm); 456.0" (11582mm) Maximum OAL	29/50	79
1LPH	BUMPER, FRONT "TEXAS Style", Aluminum, Stainless Steel Clad	8/0	8
1VBE	DECK PLATE (2) Sections, Aluminum, Self-Cleaning, Open and Serrated Design	14/19	33
1616	FRAME RAILS WITH TAPERED REAR	0/-7	-7
1WRW	TOW HOOK, FRONT (2) Frame Mounted; 80,000-lb. Total Capacity	15/0	15
1WXD	WHEELBASE RANGE 211" (535cm) Through and Including 256" (650cm)	126/-126	0

BRAKES

4092	BRAKE SYSTEM, AIR Dual System for Tractor Applications <u>Includes</u> : BRAKE LINES Color and Size Coded Nylon : GLAD HANDS (2) One for Service and One for Emergency; Trailer Hoses from Cab : HAND CONTROL VALVE, AIR Mounted in Instrument Panel : HAND CONTROL VALVE, AIR Mounted on Steering Column : PARKING BRAKE CONTROL Yellow and Red Knobs, Located on Instrument Panel : PARKING BRAKE VALVE Combination Valve for Tractor and Trailer : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for Forward Rear Axle : TRACTOR PROTECTION VALVE	19/-3	16
4AZY	AIR BRAKE ABS {Bendix AntiLock Brake System} 6-Channel (6 Sensor/6 Modulator) Electronic Stability Program, with Automatic Traction Control	0/0	0
4XDP	BRAKES, FRONT {Meritor 16.5X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 5", 14,700-lb Capacity	-23/0	-23
4EXV	BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 SqIn	4/0	4
4LAG	SLACK ADJUSTERS, FRONT {Gunite} Automatic	14/0	14
4XDS	BRAKES, REAR {Meritor 16.5X8.625 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 8.625", 23,000-lb Capacity per Axle	0/150	150
4EXU	BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqIn Spring Brake	0/14	14

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
4LGG	SLACK ADJUSTERS, REAR {Gunitex} Automatic	0/28	28
4XEE	PARK BRAKE CHAMBERS, ADDITIONAL (2) Spring Brake Type	0/30	30
4SPA	AIR COMPRESSOR {Cummins} 18.7 CFM	0/0	0
4EDM	AIR DRYER {Bendix AD-HF} with Heater, Includes Pressure Protection Circuits, Safety Valve, Integral Purge Tank, Governor Pressure Settings 110 psi Cut-In/130 psi Cut-Out, Integrated PuraGuard Coalescing Filtration	0/0	0
4VKC	AIR DRYER LOCATION Mounted Inside Left Rail, Back of Cab	0/0	0
4VHW	AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Left Rail, Under Cab; Perpendicular to Rail	0/0	0
4WXR	DRAIN VALVE (2) {Berg} with Pull Chains, for Air Tanks	0/0	0

STEERING

5PSA	STEERING GEAR {Sheppard M100} Power	0/0	0
5710	STEERING COLUMN Tilting and Telescoping	0/0	0
5CBE	STEERING WHEEL 4-Spoke; 18" Dia., Black Leather Wrapped	-7/-1	-8

DRIVELINES

6DGU	DRIVELINE SYSTEM {Dana Spicer} SPL250 Main Driveline with SPL170 Interaxle Shaft, for 6x4	0/0	0
------	---	-----	---

EXHAUST SYSTEMS

7DXW	EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Dual Vertical Tail Pipes, Cab Mounted, Left Side Pipe is Non-Functional/Aesthetic Only	47/18	65
7BES	AFTERTREATMENT COVER Polished Aluminum	9/2	11
7SAP	ENGINE COMPRESSION BRAKE {Cummins} Interbrake For Cummins Signature/ISX/X15 Engines; Furnished with Engine	0/0	0
7WBU	EXHAUST HEIGHT 11' 6"	4/0	4
7WDL	MUFFLER/TAIL PIPE GUARD (2) Bright Stainless Steel	0/0	0
7MAY	TAIL PIPE (2) Turnback Type, Chrome, 6" Diameter Belled Down to 5" at Muffler	-7/-3	-10

ELECTRICAL SYSTEMS

8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment	0/0	0
	Includes		
	: HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel		
	: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever		
	: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light		
	: STARTER SWITCH Electric, Key Operated		
	: STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector		
	: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever		
	: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted		

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
8GXJ	ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount	0/0	0
8RPR	ANTENNA for Increased Roof Clearance Applications	1/0	1
8WJN	BATTERY BOX Aluminum, with Plastic Cover, 30" Wide, 2-4 Battery Capacity, Mounted Left Side Under Cab	15/-6	9
8VUS	BATTERY BOX COVER Polished Aluminum, Universal Cover that Covers Both Battery Box & DEF Tank	28/12	40
8MSG	BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud	0/0	0
8RNB	CB RADIO Accommodation Package, Header Mounted, Feeds from Accessory Side of Ignition Switch, Includes Power Source, One Antenna and Antenna Base with Wiring on Left Side Mirror	0/0	0
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses	0/0	0
8XJH	FOG LIGHTS (2) Clear Lens, LED, Rectangular, with White Light Source	3/0	3
8WXB	HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position	0/0	0
8XNY	HEADLIGHTS Halogen	0/0	0
8WHJ	HORN, AIR (2) Rectangular Bell, Chrome	3/0	3
8VAY	HORN, ELECTRIC Disc Style	0/0	0
8WCK	POWER SOURCE, TERMINAL TYPE 2-Post	0/0	0
8RPU	RADIO AM/FM/WB/SiriusXM/Clock/Bluetooth/USB Input/Auxiliary Input	3/0	3
8RBZ	SPEAKER, AUXILIARY, CB RADIO with Jack for CB; Mounted Left Side Above Driver's Door	0/0	0
8RMV	SPEAKERS (2) 6.5" Dual Cone Mounted in Doors	0/0	0
8WXG	STARTING MOTOR {Mitsubishi Electric Automotive America 105P} 12-Volt, with Soft-Start	0/0	0
8TKC	STOP, TURN, TAIL & B/U LIGHTS {Truck Lite} Super 44, with LED Lights for Stop, Turn and Tail Lights, Truck Lite Super 40 Lamps for Backup Lights, Less Power Module, Includes Incandescent License Plate Light, with Separate Rear Reflectors, Less Rubber Mount	-1/9	8
8WEZ	TURN SIGNAL SWITCH Self-Canceling	0/0	0
FRONT END			
9ASE	FRONT END Tilting, Composite	0/0	0
9WBD	BUG DEFLECTOR Stainless Steel, Mounted on Hood	5/0	5
9WAC	BUG SCREEN Mounted Behind Grille	5/0	5
9HCN	GRILLE Chrome Vertical Accent Bars, with Black Mesh	0/0	0
9AAB	LOGOS EXTERIOR Model Badges	0/0	0
9AAE	LOGOS EXTERIOR, ENGINE Badges	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
9505	QUARTER FENDERS for Rear Wheels, Mirror-Finished Stainless Steel, Frame Mounted	9/26	35

SPEEDOMETER, TOOLS, MISC

10ADT	COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Two Year Data Plan	1/0	1
10HJC	FIFTH WHEEL, AIR SLIDE {Fontaine SL7LWB825024} 24" Slide, Cast Top Plate, 8.25" Above Top of Frame, Left Hand Release	0/546	546
810000	FIFTH WHEEL LOCATION On Rear Axle Centerline	0/0	0
10WPR	MUD FLAP HOLDER Spring Loaded, Painted Black, with Red and White Reflective Tape, Less Flaps	-6/28	22
10WSX	MUD FLAPS, REAR Black Poly, with International Logo, Less Holders	-3/13	10
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0
10771	PAINT CLASS Single Custom Color	0/0	0

FUEL TANKS

15DXD	FUEL TANK (2) Polished Aluminum, 24" Dia, 80 US Gal (303L); Total Capacity 160 US Gal (606L), with Dual Supply and Return Lines, Less Equalizer Line, Mounted Left and Right Side, Back of Cab	37/91	128
15WDY	DEF TANK 15.9 US Gal (60L) Capacity, Frame Mounted Outside Left Rail, Under Cab	4/0	4
15MAD	FUEL HEATER {Cummins} Omit Plumbing for TRV on Cummins Engines	-2/0	-2
15LKU	FUEL/WATER SEPARATOR {Racor} Fuel Pre-Filter and Filter Base, Includes Water-In-Fuel Sensor	0/0	0

WHEELS, TIRES - FRONT

27DEL	WHEELS, FRONT {Alcoa 98U63} DISC; 24.5x8.25 Rims, Mirror Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	-31/0	-31
7384225443	(2) TIRE, FRONT 11R24.5 Load Range H ECOPLUS HS3+ (CONTINENTAL), 473 rev/mile, 75 MPH, All-Position	26/0	26

WHEELS, TIRES - REAR

28DEL	WHEELS, REAR {Alcoa 98U63} DUAL DISC; 24.5x8.25 Rims, Mirror Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	0/-124	-124
7384220121	(8) TIRE, REAR 11R24.5 Load Range H G182 RSD (GOODYEAR), 473 rev/mile, 75 MPH, Drive	0/168	168

BODY & CHASSIS PAINT

35216	PAINT, CAB Two-Tone, with 3-4 Breaks on Cab	0/0	0
35223	PAINT HOOD, CONVENTIONAL CAB Two-Tone, with 3-4 Breaks on Hood.	0/0	0

Services Section:

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
WARRANTY			
40132	WARRANTY Standard for HX520, HX620, Effective with Vehicles Built January 1, 2021 or Later, CTS-2015B	0/0	0
Total Component Weight:		9238/8850	18088
Body/Allied Equipment			
<u>Code</u>	<u>Description</u>	<u>F/R Wt</u>	<u>Tot Wt</u>
Goods Purchased			
<u>Code</u>	<u>Description</u>	<u>F/R Wt</u>	<u>Tot Wt</u>

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.