

Prepared For:

Virginia Sheriffs' Association
Kaylyn Mitman
901 E Byrd St.
Richmond, VA 23219-4052
(804)225 - 7152
Reference ID: N/A

Presented By:

LILLEY INTERNATIONAL
TROY WARD
US HWY 17 BY PASS
WILLIAMSTON NC 27892 -
(252)792-4192

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2024 RH613 6x4 (RH61F)

MISSION:	Requested GCWR: 80000. Calc. GCWR: 110000. Calc. GVWR: 58350 Calc. Geared Speed: 88.6 MPH
DIMENSION:	Wheelbase: 187.00, CA: 124.20, Axle to Frame: 63.00
ENGINE, DIESEL:	{International A26} EPA 2021, 450HP @ 1700 RPM, 1700 lb-ft Torque @ 900 RPM, 1800 RPM Governed Speed, 450 Peak HP (Max)
TRANSMISSION, MANUAL:	{Eaton Endurant EEO-17F112C} 12-Speed Fully Automated Manual, Aluminum Clutch Housing, Overdrive, Mechatronic Shift Controls, Pneumatic Clutch Actuation, Internal Lube Oil Pump, Hill Start Aid
CLUTCH:	{Eaton Fuller 430MM} Maintenance Free, Self-Adjusting, 17" (430 mm) Dia Single Plate, Diaphragm Spring, Organic, 5-Spring Coaxial 254mm Damper with Pre-Damper, 2"-18 Tooth Spline, Pneumatic Push Type Control, 1850 lb-ft (2508 Nm) Torque Capacity
AXLE, FRONT NON-DRIVING:	{Meritor MFS-12-143A} Wide Track, I-Beam Type, 12,350-lb Capacity
AXLE, REAR, TANDEM:	{Meritor RT-46-160P} Single Reduction, 46,000-lb Capacity, with Lube Oil Pump, Driver Controlled Locking Differential in Rear-Rear Axle, 200 Wheel Ends Gear Ratio: 3.21
CAB:	Conventional, Day Cab
TIRE, FRONT:	(2) 11R22.5 Load Range H ENDURANCE RSA (GOODYEAR), 496 rev/mile, 75 MPH, All-Position
TIRE, REAR:	(8) 11R22.5 Load Range G G572 1AD (GOODYEAR), 496 rev/mile, 75 MPH, Drive
SUSPENSION, REAR, AIR, TANDEM:	{Hendrickson HAS-460-55} 46,000-lb Capacity, 55" Axle Spacing, 9.5" Ride Height, with Shock Absorbers
PAINT:	Cab schematic 100HW Location 1: 9219, Winter White (Std) Chassis schematic N/A

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
RH61F00	Base Chassis, Model RH613 6x4 with 187.00 Wheelbase, 124.20 CA, and 63.00 Axle to Frame.	8132/6200	14332

ENGINE

12BGD	ENGINE, DIESEL {International A26} EPA 2021, 450HP @ 1700 RPM, 1700 lb-ft Torque @ 900 RPM, 1800 RPM Governed Speed, 450 Peak HP (Max)	0/0	0
12XCS	CARB EMISSION WARR COMPLIANCE Federal, Does Not Comply with CARB Emission Warranty	0/0	0
12WZE	CARB IDLE COMPLIANCE Federal, Does Not Comply with California Clean Air Idle Regulations	0/0	0
12VJA	EMISSION, CALENDAR YEAR {International A26} EPA, OBD and GHG Certified for Calendar Year 2022	0/0	0
12XBC	RADIATOR Aluminum, Welded, Down Flow, Front to Back System, 1325 SqIn, with 806 SqIn Charge Air Cooler	0/0	0
12THJ	FAN DRIVE {Horton Drivemaster} Automatic On/Off Type, with Normally Closed Temperature Control	0/0	0
12VBC	AIR CLEANER Single Element <u>Includes</u> : GAUGE, AIR CLEANER RESTRICTION Air Cleaner Mounted	0/0	0
12703	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection	0/0	0
12WEG	COLD STARTING EQUIPMENT Automatic; with Engine ECM Control	0/0	0
12XBE	CRUISE CONTROL Predictive, Includes GPS Enhanced Cruise Control; Includes Module, Antenna and Wiring	0/0	0
12WCX	HOSE CLAMPS, RADIATOR HOSES {Gates} Shrink Band Type	0/0	0
12WYZ	RADIATOR DRAIN & FILL FITTING SPECIAL; To Vacuum Out or Fill the Cooling System from the Bottom of Radiator, for Use with Quick-Connect Radiator Drain Tool or Shop Coolant Evacuation-Fill System	0/0	0

TRANSMISSION

13GZB	TRANSMISSION, MANUAL {Eaton Endurant EEO-17F112C} 12-Speed Fully Automated Manual, Aluminum Clutch Housing, Overdrive, Mechatronic Shift Controls, Pneumatic Clutch Actuation, Internal Lube Oil Pump, Hill Start Aid	0/0	0
13XAR	PTO LOCATION Customer Intends to Install PTO at Bottom of Transmission	0/0	0
13XAX	SHIFT CONTROL PARAMETERS {Eaton Endurant} Automated Manual Transmission, Economy Calibration	0/0	0
13WLW	TRANSMISSION OIL {EmGard 40W} Synthetic; 1 thru 21.99 Pints	0/0	0
13WET	TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 & 2000 Series Transmission	1/0	1

CLUTCH

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
11MHM	CLUTCH {Eaton Fuller 430MM} Maintenance Free, Self-Adjusting, 17" (430 mm) Dia Single Plate, Diaphragm Spring, Organic, 5-Spring Coaxial 254mm Damper with Pre-Damper, 2"-18 Tooth Spline, Pneumatic Push Type Control, 1850 lb-ft (2508 Nm) Torque Capacity	0/0	0

REAR AXLES, SUSPENSIONS

14GRS	AXLE, REAR, TANDEM {Meritor RT-46-160P} Single Reduction, 46,000-lb Capacity, with Lube Oil Pump, Driver Controlled Locking Differential in Rear-Rear Axle, 200 Wheel Ends . Gear Ratio: 3.21 <u>Includes</u> : POWER DIVIDER LOCK Electric over Air Operated, Cab Control with Indicator Light	0/580	580
14ULB	SUSPENSION, REAR, AIR, TANDEM {Hendrickson HAS-460-55} 46,000-lb Capacity, 55" Axle Spacing, 9.5" Ride Height, with Shock Absorbers	0/144	144
14WMK	AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 65 thru 89.99 Pints	0/0	0
14WZY	AXLE SHAFT MODIFICATION Axle Shaft Flanges Modified for 0.625" Diameter Drive Studs with Solid Type Cone-Locks	0/0	0
14899	SUSPENSION AIR CONTROL VALVE Pressure Release Control In Cab	4/4	8

FRONT AXLES

2ASX	AXLE, FRONT NON-DRIVING {Meritor MFS-12-143A} Wide Track, I-Beam Type, 12,350-lb Capacity	6/0	6
------	---	-----	---

FRONT SUSPENSIONS

3AHN	SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 12,350-lb Capacity, with Shock Absorbers <u>Includes</u> : SPRING PINS Rubber Bushings, Maintenance-Free	0/0	0
------	--	-----	---

CABS, COWLS, BODIES

16030	CAB Conventional, Day Cab <u>Includes</u> : CLEARANCE/MARKER LIGHTS (5) Flush Mounted : COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window : CONSOLE, CENTER Includes Two Cup Holders and One Additional Storage Area : COURTESY LIGHT (2) Driver and Passenger Door Mounted : DOME LIGHT, CAB Rectangular, Door and Instrument Panel Mounted Switch Activated, Timed Theater Dimming, Center Mounted, Integral to Console : FLOOR COVERING Rubber, Black : GLASS, ALL WINDOWS Tinted : GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side : GRAB HANDLE, CAB INTERIOR (4) "B" Pillar and Door Mounted, Two Each Side : INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color : READING LIGHT, CAB Located in Overhead Console : STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door	0/0	0
-------	--	-----	---

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
16ZHL	ACCESS, CAB AND FRAME Aluminum, Driver & Passenger Sides, Two Steps per Door; Left Side Frame Access Step, Includes One Flush Mounted Deck Plate and Black Grab Handle, for use with Day Cab or Sleeper Cab	40/21	61
16XYM	AERODYNAMIC PACKAGE Includes Roof Air Deflector, Cab Side Extenders; for Day Cab, Paint and Install at the Plant	102/66	168
16BAM	AIR CONDITIONER with Integral Heater and Defroster	0/0	0
	<u>Includes</u> : HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps		
16VKB	CAB INTERIOR TRIM Classic, for Day Cab	0/0	0
	<u>Includes</u> : DOOR TRIM, INTERIOR Black Handle : INSTRUMENT PANEL TRIM Black, Black Gauges with Black Bezels : SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap		
16GED	GAUGE CLUSTER Base Level; English with English Electronic Speedometer	0/0	0
	<u>Includes</u> : GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/ Refill for : GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure : WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)		
16HGN	GAUGE, AIR APPLICATION	1/0	1
16HKE	GAUGE, LOAD INDICATING REAR Text Message in Cluster Display, for use with Rear Air Suspension	0/0	0
16HCS	GAUGE, TEMPERATURE, AMBIENT Sensor Wiring with Display Unit Mounted in Cluster	0/0	0
16HLX	GAUGE, VOLTMETER Auxiliary Gauge, Located in Center Panel. Standard Cluster Also Includes Digital Voltage Readout	0/0	0
16XJP	INSTRUMENT PANEL Wing Panel	0/0	0
16SNV	MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Turn Signals, Bright Heads, Black Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width	1/0	1
	<u>Notes</u> : Mirror Dimensions are Rounded to the Nearest 0.5"		
16SNH	MIRROR, CONVEX, HOOD MOUNTED (2) Right and Left Sides, Bright	12/-1	11
16VLV	MONITOR, TIRE PRESSURE Omit	-12/-1	-13
16VCC	SEAT BELT All Orange; 1 to 3	0/0	0
16KAN	SEAT, DRIVER {National 2000 Model 195} Air Suspension, High Back, with Mordura Cloth, 2 Arm Rests, Isolator, 7" Adjuster, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, 3-14 Degree Back Recline	2/0	2

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
16REM	SEAT, PASSENGER {National 2000} Non Suspension, High Back, Mordura Cloth, 2 Arm Rests 11 Degree Back Angle	7/1	8
16XWV	SUNSHADE, EXTERIOR Aerodynamic, Painted Roof Color, with Integral LED Clearance/Marker Lights	16/1	17
16WJU	WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature	0/0	0

FRAMES

1CBW	FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.250" x 3.610" x 0.375" (260.4mm x 91.7mm x 9.5mm); 466.5" (11850mm) Maximum OAL	88/157	245
1LRN	BUMPER, FRONT 3-Piece, Aerodynamic, Plastic, Molded Dark Gray, with Bright Overlay	15/0	15
1VBB	DECK PLATE Aluminum, (1) Section, Flush Mounted, Quick to Release	10/0	10
1616	FRAME RAILS WITH TAPERED REAR	0/0	0
1WKK	WHEELBASE RANGE 187" (475cm) Through and Including 219" (555cm)	0/0	0

BRAKES

4092	BRAKE SYSTEM, AIR Dual System for Tractor Applications <u>Includes</u> : BRAKE LINES Color and Size Coded Nylon : BRAKE PRESSURE INDICATOR Low Air Pressure Warning Light and Audible Alarm : DRAIN VALVE Manually Operated (On Wet Tank Only) : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : GLAD HANDS (2) One for Service and One for Emergency; Trailer Hoses from Cab : HAND CONTROL VALVE, AIR with Self Return Handle, for Trailer Brakes, Mounted in Instrument Panel : HOSE TENDER Back of Cab Mounted : PARKING BRAKE CONTROL Yellow and Red Knobs, Located on Instrument Panel : PARKING BRAKE VALVE Combination Valve for Tractor and Trailer : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for Forward Rear Axle : TRACTOR PROTECTION VALVE	0/0	0
4GBM	BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake	0/0	0
4AZX	AIR BRAKE ABS {Wabco AntiLock Brake System} 6-Channel (6 Sensor/6 Modulator) Electronic Stability Program, with Automatic Traction Control	1/0	1
4XDP	BRAKES, FRONT {Meritor 16.5X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 5", 14,700-lb Capacity	0/0	0
4EXV	BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 SqIn	0/0	0
4LAG	SLACK ADJUSTERS, FRONT {Gunite} Automatic	0/0	0
4XDS	BRAKES, REAR {Meritor 16.5X8.625 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 8.625", 23,000-lb Capacity per Axle	0/68	68

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
4EXU	BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqIn Spring Brake Includes : BRAKE CHAMBERS, POSITION (2) Rear Parking; WITH TRUCK BRAKES: All 4x2, 4x4; WITH TRACTOR BRAKES: All 4x2, 4x4; 6x4 & 6x6 with Rear Tandem Axles Less Than 46,000-lb. or GVWR Less Than 54,000-lb. : BRAKE CHAMBERS, POSITION (4) Rear Parking; WITH TRUCK BRAKES: All 6x4, 6x6; WITH TRACTOR BRAKES: 6x4 & 6x6 with Rear Tandem Axles 46,000-lb. or Greater or GVWR of 54,000-lb. or Greater	0/0	0
4LGG	SLACK ADJUSTERS, REAR {Gunite} Automatic	0/0	0
4XEE	PARK BRAKE CHAMBERS, ADDITIONAL (2) Spring Brake Type	0/30	30
4SPM	AIR COMPRESSOR {Bendix BA-921 Head Unload} 15.9 CFM	0/0	0
4EDM	AIR DRYER {Bendix AD-HF} with Heater, Includes Pressure Protection Circuits, Safety Valve, Integral Purge Tank, Governor Pressure Settings 110 psi Cut-In/130 psi Cut-Out, Integrated PuraGuard Coalescing Filtration	0/0	0
4VHW	AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Left Rail, Under Cab; Perpendicular to Rail	0/0	0
4UKP	AIR TANK, AUXILIARY for Transmission Air Supply, Frame Mounted Under Right Rail, Under Cab	19/5	24
4WXR	DRAIN VALVE (2) {Berg} with Pull Chains, for Air Tanks	2/0	2
4SUJ	TRAILER HOSES {Philatron} Coiled, Stallion Hose, 15' Working Length, 7" Tractor Lead Length, 7" Trailer Lead Length, Aluminum Glad Hands with Polyurethane Seals and Hand Holds	0/0	0
STEERING			
5PSM	STEERING GEAR {Sheppard HD94} Power	0/0	0
5WAJ	POWER STEERING OIL COOLER Remote Mounted	7/-1	6
5710	STEERING COLUMN Tilting and Telescoping	0/0	0
5CBE	STEERING WHEEL 4-Spoke; 18" Dia., Black Leather Wrapped	-1/0	-1
DRIVELINES			
6DGU	DRIVELINE SYSTEM {Dana Spicer} SPL250 Main Driveline with SPL170 Interaxle Shaft, for 6x4	0/0	0
EXHAUST SYSTEMS			
7BLW	EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab	75/18	93
7BEU	AFTERTREATMENT COVER Aluminum	8/3	11
7SDK	ENGINE COMPRESSION BRAKE by Jacobs; for N13/A26 Engines, with Selector Switch and On/Off Switch	0/0	0
7WCC	EXHAUST HEIGHT 13' 3"	3/0	3
7WDN	MUFFLER/TAIL PIPE GUARD (1) Aluminum	12/7	19
7WBA	TAIL PIPE (1) Turnback Type, Bright	1/0	1

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
ELECTRICAL SYSTEMS			
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment <u>Includes</u> : DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab : HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever : HORN, ELECTRIC Single : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light : POWER SOURCE Cigar Type Receptacle with Cap, USB Port, Located in Instrument Panel : STARTER SWITCH Electric, Key Operated : TURN SIGNAL SWITCH Manual Cancelling with Lane Change Feature : TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever : WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted : WIRING, CHASSIS Color Coded and Continuously Numbered	0/0	0
8GXJ	ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount	0/0	0
8THB	BACK-UP ALARM Electric, 102 dBA	0/3	3
8XHK	BATTERY BOX Aluminum, 30" Wide, 2-4 Battery Capacity, Mounted Left Side Under Cab	-33/-11	-44
8XHM	BATTERY BOX COVER Plastic	0/0	0
8WJV	BATTERY DISCONNECT SWITCH {Joseph Pollak} for Cab Power Disconnect Switch, Disconnects Power to Power Distribution Center (PDC), Does Not Disconnect Charging Circuits, Lever Operated, Cab Mounted	4/0	4
8MSG	BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud	0/0	0
8RNB	CB RADIO Accommodation Package, Header Mounted, Feeds from Accessory Side of Ignition Switch, Includes Power Source, One Antenna and Antenna Base with Wiring on Left Side Mirror	1/0	1
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses	0/0	0
8TUT	COLLISION MITIGATION SYSTEM Omit	-4/0	-4
8XMB	CONNECTOR, DASH, CENTER PANEL Cab Wiring for TMC RP1226 Vehicle Accessory Connector; Includes 14-pin Connector with Switched Power, Battery Power, Ignition Power, Ground & Body 250K Datalink, Connector Located Behind Instrument Panel Center Console	0/0	0
8WXB	HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position	0/0	0
8XKC	HEADLIGHTS Halogen, with Daytime Running Lights, Automatic Twilight Controlled	-12/1	-11
8WRB	HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on	0/0	0
8XHN	HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
8541	HORN, ELECTRIC (2) Disc Style	0/0	0
8WBW	JUMP START STUD Remote Mounted	2/0	2
	<u>Includes</u> : JUMP START STUD Mounted to Battery Box		
8WCM	POWER SOURCE, SPECIAL {Phillips} Socket, Single Terminal, for Power Lift Gate Feed, Battery Feed Thru 150 Amp Circuit Breaker, To Operate Lift Gate On Trailer, Includes a 15' Power Cable Coiled In Cab	15/0	15
8WCK	POWER SOURCE, TERMINAL TYPE 2-Post	1/0	1
8RPS	RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input	0/0	0
8RBZ	SPEAKER, AUXILIARY, CB RADIO with Jack for CB; Mounted Left Side Above Driver's Door	2/0	2
8RMW	SPEAKERS (2) 6.5" Coax Mounted in Doors, (2) 5.25" Coax Mounted in B-Pillars	4/0	4
8WTL	STARTING MOTOR {Delco Remy 39MT} 12 Volt, Gear Reduced, with Thermal Over-Crank Protection	0/0	0
8TKJ	STOP, TURN, TAIL & B/U LIGHTS {Truck Lite} Super 44, with LED Lights for Stop, Turn, Tail and Backup Lights, with Power Module, "International" Termination and Less Junction Box, Includes License Plate Light	-7/19	12
8XHX	SWITCH, MARKER INTERRUPT for Marker Lights and Headlights, Located in Steering Wheel	0/0	0
8WPZ	TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights	0/0	0
8THC	TRAILER LIGHTING CABLE {Phillips LECTRACOIL 30-9921S} Coiled, 15' Length, 48" Tractor Lead and 12" Trailer Lead, with Plastic Plug	15/8	23
8WGL	WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time	0/0	0

FRONT END

9WAY	FRONT END Tilting, Fiberglass, with Three Piece Construction	0/0	0
	<u>Includes</u> : BUG SCREEN Front End; Mounted Behind Grille : HOOD TILT ASSIST Includes Torsion Bar Spring System		
9WBN	FENDER EXTENSIONS Painted	0/0	0
9HAD	GRILLE Chrome	0/0	0
9AAB	LOGOS EXTERIOR Model Badges	0/0	0
9AAE	LOGOS EXTERIOR, ENGINE Badges	0/0	0
9505	QUARTER FENDERS for Rear Wheels, Mirror-Finished Stainless Steel, Frame Mounted	0/18	18

SPEEDOMETER, TOOLS, MISC

10AEU	INTELLIGENT FLEET CARE Telematics Device with Over the Air Programming; Includes Five Year Data Plan, Advanced Preventive Maintenance, Fleet Health Monitor Reporting and International 360	0/0	0
-------	---	-----	---

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
10HJB	FIFTH WHEEL, AIR SLIDE {Fontaine SL7LWB725024} 24" Slide, Cast Top Plate, 7.25" Above Top of Frame, Left Hand Release	0/94	94
810000	FIFTH WHEEL LOCATION On Rear Axle Centerline	0/0	0
10WPR	MUD FLAP HOLDER Spring Loaded, Painted Black, with Red and White Reflective Tape, Less Flaps	0/0	0
10WSX	MUD FLAPS, REAR Black Poly, with International Logo, Less Holders	0/8	8
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100	0/0	0
	<u>Includes</u> : PAINT SCHEMATIC ID LETTERS "HW"		
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0

FUEL TANKS

15EAE	FUEL TANK (2) Top Draw, Non-Polished Aluminum, 26" Dia, 100 US Gal (379L); Total Capacity 200 US Gal (757L), with Dual Supply and Return Lines, Less Equalizer Line, Mounted Left and Right Side, Back of Cab/Under Sleeper	50/66	116
15WDN	DEF TANK 15.9 US Gal (60L) Capacity, Frame Mounted Outside Left Rail, Back of Cab/Under Sleeper	3/1	4
15LKU	FUEL/WATER SEPARATOR {Racor} Fuel Pre-Filter and Filter Base, Includes Water-In-Fuel Sensor	-6/0	-6
	<u>Includes</u> : LOCATION FUEL/WATER SEPARATOR Mounted Left Rail in Wheel Well		

WHEELS, TIRES - FRONT

27DVR	WHEELS, FRONT {Accuride 42644} DISC; 22.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Aluminum Hubs	-24/0	-24
7382138132	(2) TIRE, FRONT 11R22.5 Load Range H ENDURANCE RSA (GOODYEAR), 496 rev/mile, 75 MPH, All-Position	14/0	14

WHEELS, TIRES - REAR

28DUW	WHEELS, REAR {Accuride 51408} DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	0/216	216
7372138121	(8) TIRE, REAR 11R22.5 Load Range G G572 1AD (GOODYEAR), 496 rev/mile, 75 MPH, Drive	0/64	64

WHEELS MISC OPTIONS

29CAG	WHEEL COVER, REAR Aerodynamic, 22.5", Black	0/0	0
-------	---	-----	---

BODY & CHASSIS PAINT

35860	PAINT FENDER EXTENSIONS Single Color; Same as Number Two Cab Schematic Color	0/0	0
-------	--	-----	---

Services Section:

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
WARRANTY			
40125	WARRANTY Standard for LT/RH Series, Effective with Vehicles Built January 2, 2016 or Later, CTS-2010A	0/0	0
40TRM	SRV CONTRACT, EXT ENGINE/AFTR {Navistar} To 72-Month/600,000 Miles (960,000 km), Includes Engine, Engine Electronics, Turbocharger, Water Pump and Fuel Injectors, Aftertreatment Coverage for International A26 Engines	0/0	0
Total Component Weight:		8577/7789	16366
Body/Allied Equipment			
<u>Code</u>	<u>Description</u>	<u>F/R Wt</u>	<u>Tot Wt</u>
Goods Purchased			
<u>Code</u>	<u>Description</u>	<u>F/R Wt</u>	<u>Tot Wt</u>

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.