

**INTERNATIONAL®****LT****SERIES HEAVY DUTY****LT625 4x2****STANDARD EQUIPMENT****MODEL CODE: LT62A00 LIST PRICE:****01 FRAMES**

- \* NOTE: APPLICATION AND COUNTRY RESTRICTION INFORMATION IS NOT SHOWN IN THE AVAILABLE EQUIPMENT SECTIONS. PLEASE REFER TO THE TOPS APPLICATION IN SALES TOOLS FOR THIS RESTRICTION INFORMATION.

01CBV - FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.125" x 3.580" x 0.312" (257.2mm x 90.9mm x 8.0mm); 367.4" (9333mm) Maximum OAL  
01LRL - BUMPER, FRONT 3-Piece, Aerodynamic, Plastic, Molded Dark Gray  
01616 - FRAME RAILS WITH TAPERED REAR  
01WKM - WHEELBASE RANGE 140" (355cm) Through and Including 156" (395cm)

**02 AXLE, FRONT**

02AVH - AXLE, FRONT NON-DRIVING {Hendrickson Steertek IADB} Wide Track, Fabricated Type, 12,350-lb Capacity, with Integrated Air Disc Brake Knuckle

**03A SUSPENSION, FRONT**

03AHN - SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 12,350-lb Capacity, with Shock Absorbers  
\* SPRING PINS Rubber Bushings, Maintenance-Free

**04 BRAKES**

04092 - BRAKE SYSTEM, AIR Dual System for Tractor Applications  
\* BRAKE LINES Color and Size Coded Nylon  
\* BRAKE PRESSURE INDICATOR Low Air Pressure Warning Light and Audible Alarm  
\* DRAIN VALVE Manually Operated (On Wet Tank Only)  
\* GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster  
\* GLAD HANDS (2) One for Service and One for Emergency; Trailer Hoses from Cab  
\* HAND CONTROL VALVE, AIR with Self Return Handle, for Trailer Brakes, Mounted in Instrument Panel  
\* HOSE TENDER Back of Cab Mounted

**04 BRAKES****(CONT.)**

\* PARKING BRAKE CONTROL Yellow and Red Knobs, Located on Instrument Panel  
\* PARKING BRAKE VALVE Combination Valve for Tractor and Trailer  
\* QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for Forward Rear Axle  
\* TRACTOR PROTECTION VALVE  
NOTE: Front and Rear Dust Shields not Included  
NOTE: Rear Axle is Limited to 20,000-lb GAWR with Code 04092 BRAKE SYSTEM, AIR and Standard Rear Air Cam Brakes Regardless of Axle/Suspension Ordered  
04AZS - AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Electronic Stability Program, with Automatic Traction Control  
04XCJ - BRAKES, FRONT {Bendix Spicer ADB22X} Air Disc Type, Extended Service, Size 22.5", 23,000-lb Capacity  
04XDW - BRAKE CHAMBERS, FRONT AXLE 18 SqIn, for Air Disc Brakes  
04XCK - BRAKES, REAR {Bendix Spicer ADB22X} Air Disc Type, Extended Service, Size 22.5", 26,000-lb Capacity per Axle  
04XEA - BRAKE CHAMBERS, REAR AXLE 18/24 SqIn Spring Brake, Double Diaphragm, for Air Disc Brakes  
04SPM - AIR COMPRESSOR {Bendix BA-921 Head Unload} 15.9 CFM  
04EDM - AIR DRYER {Bendix AD-HF} with Heater, Includes Pressure Protection Circuits, Safety Valve, Integral Purge Tank, Governor Pressure Settings 110 psi Cut-In/130 psi Cut-Out, Integrated PuraGuard Coalescing Filtration  
04VHW - AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Left Rail, Under Cab; Perpendicular to Rail

**04 BRAKES****(CONT.)**

04XAH - TRAILER HOSES AND CABLES {Erich Jaeger} Coiled, Phillips Nylon Hose, 15' Working Length, 24" Tractor Lead Length, 6" Trailer Lead Length, Aluminum Glad Hands with Rubber Seals, Lighting Cable with Polypropylene Composite Plug

**05 STEERING**

05PSM - STEERING GEAR {Sheppard HD94} Power  
05710 - STEERING COLUMN Tilting and Telescoping  
05CAW - STEERING WHEEL 4-Spoke; 18" Dia., Black

**06 DRIVELINES**

\* END YOKES Half-Round, Easy Service (All)  
\* SLIP JOINT SPLINES Nylon-Coated

06DGM - DRIVELINE SYSTEM {Dana Spicer} Service Free SPL250, for 4x2/6x2

**07 EXHAUST SYSTEM**

07BLV - EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Short Horizontal Tail Pipe, Frame Mounted Right Side Back of Cab  
07SDK - ENGINE COMPRESSION BRAKE by Jacobs; for N13/A26 Engines, with Selector Switch and On/Off Switch  
07WDR - TAIL PIPE (1) Horizontal, Short

**08 ELECTRICAL**

08000 - ELECTRICAL SYSTEM 12-Volt, Standard Equipment  
\* DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab  
\* HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel  
\* HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever  
\* HORN, ELECTRIC Single  
\* PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light  
\* POWER SOURCE Cigar Type Receptacle with Cap, USB Port, Located in Instrument Panel  
\* STARTER SWITCH Electric, Key Operated  
\* TURN SIGNAL SWITCH Manual Cancelling with Lane Change Feature

Refer To General Info for Metric Conversion Tables

**INTERNATIONAL®****LT****SERIES HEAVY DUTY****LT625 4x2****STANDARD EQUIPMENT****MODEL CODE: LT62A00****08 ELECTRICAL**

(CONT.)

- \* TURN SIGNALS, FRONT  
Includes Reflectors and  
Auxiliary Side Turn  
Signals, Solid State  
Flashers; Flush Mounted
- \* WINDSHIELD WIPER SWITCH  
2-Speed with Wash and  
Intermittent Feature (5  
Pre-Set Delays), Integral  
with Turn Signal Lever
- \* WINDSHIELD WIPERS Single  
Motor, Electric, Cowl  
Mounted
- \* WIRING, CHASSIS Color Coded  
and Continuously Numbered
- 08GXJ - ALTERNATOR  
{Leece-Neville AVI160P2013}  
Brush Type, 12 Volt, 160 Amp  
Capacity, Pad Mount
- 08XHL - BATTERY BOX Steel, 30"  
Wide, 2-4 Battery Capacity,  
Mounted Left Side Under Cab
- 08MSG - BATTERY SYSTEM  
{Fleetrite}  
Maintenance-Free, (3)  
12-Volt 1980CCA Total, Top  
Threaded Stud
- 08RJW - CB RADIO Omit Power  
Feeds, Power Source and  
Wiring
- 08XAH - CIRCUIT BREAKERS  
Manual-Reset (Main Panel)  
SAE Type III with Trip  
Indicators, Replaces All  
Fuses
- 08TRG - COLLISION MITIGATION  
SYSTEM {Bendix Wingman  
Fusion} Adaptive Cruise,  
Enhanced Collision  
Mitigation, Multilane Auto &  
Stat Vehicle Braking, Stat  
Obj Alert, Roadway Depart  
Alert & Braking, Lane Depart  
Warning Switch & Spkrs,  
Ovrspd Alert & Action, Frt  
Radar & Camera, Drvr  
Display, Safety Direct  
Capable, Less Safety Direct  
Cable
- 08XMB - CONNECTOR, DASH, CENTER  
PANEL Cab Wiring for TMC  
RP1226 Vehicle Accessory  
Connector; Includes 14-pin  
Connector with Switched  
Power, Battery Power,  
Ignition Power, Ground &  
Body 250K Datalink,  
Connector Located Behind  
Instrument Panel Center  
Console
- 08WXB - HEADLIGHT WARNING  
BUZZER Sounds When Head  
Light Switch is on and  
Ignition Switch is in "Off"  
Position

**08 ELECTRICAL**

(CONT.)

- 08XPA - HEADLIGHTS LED, with  
Daytime Running Lights,  
Automatic Twilight  
Controlled
- 08WRB - HEADLIGHTS ON W/WIPERS  
Headlights Will  
Automatically Turn on if  
Windshield Wipers are turned  
on
- 08XHN - HORN, AIR Single  
Trumpet, Black, with Lanyard  
Pull Cord
- 08RPU - RADIO  
AM/FM/WB/SiriusXM/Clock/Bluetooth/USB Input/Auxiliary  
Input
- 08RMV - SPEAKERS (2) 6.5" Dual  
Cone Mounted in Doors
- 08WVG - STARTING MOTOR  
{Mitsubishi Electric  
Automotive America 105P}  
12-Volt, with Soft-Start
- 08TPP - STOP, TURN, TAIL & B/U  
LIGHTS Multi-Function Lamp,  
with LED Lights for Stop,  
Turn, Tail and Backup  
Lights, Includes LED License  
Plate Light
- 08XHX - SWITCH, MARKER  
INTERRUPT for Marker Lights  
and Headlights, Located in  
Steering Wheel
- 08WPZ - TEST EXTERIOR LIGHTS  
Pre-Trip Inspection will  
Cycle all Exterior Lamps  
Except Back-up Lights

**09 FRONT END**

- 09WAY - FRONT END Tilting,  
Fiberglass, with Three Piece  
Construction
- \* BUG SCREEN Front End;  
Mounted Behind Grille
- \* HOOD TILT ASSIST Includes  
Torsion Bar Spring System
- 09HAD - GRILLE Chrome
- 09AAB - LOGOS EXTERIOR Model  
Badges
- 09AAE - LOGOS EXTERIOR, ENGINE  
Badges

**10 PAINT & MISCELLANEOUS**

- 10AEU - INTELLIGENT FLEET CARE  
Telematics Device with Over  
the Air Programming;  
Includes Five Year Data  
Plan, Advanced Preventive  
Maintenance, Fleet Health  
Monitor Reporting and  
International 360
- 10HZN - FIFTH WHEEL, AIR SLIDE  
{Fontaine SL6NWB675012} 12"  
Slide, 6.75" Above Top of  
Frame, Left Hand Release
- 10WPR - MUD FLAP HOLDER Spring  
Loaded, Painted Black, with  
Red and White Reflective  
Tape, Less Flaps

**10 PAINT & MISCELLANEOUS (CONT.)**

- 10060 - PAINT SCHEMATIC, PT-1  
Single Color, Design 100
- \* PAINT SCHEMATIC ID LETTERS  
"HX"
- 10761 - PAINT TYPE Base  
Coat/Clear Coat, 1-2 Tone
- 11 CLUTCH**
- 11MHM - CLUTCH {Eaton Fuller  
430MM} Maintenance Free,  
Self-Adjusting, 17" (430 mm)  
Dia Single Plate, Diaphragm  
Spring, Organic, 5-Spring  
Coaxial 254mm Damper with  
Pre-Damper, 2"-18 Tooth  
Spline, Pneumatic Push Type  
Control, 1850 lb-ft (2508  
Nm) Torque Capacity

**12 ENGINE**

- 12BGA - ENGINE, DIESEL  
{International A26} EPA  
2021, 410HP @ 1700 RPM, 1450  
lb-ft Torque @ 900 RPM, 1800  
RPM Governed Speed, 410 Peak  
HP (Max)
- 12XBC - RADIATOR Aluminum,  
Welded, Down Flow, Front to  
Back System, 1325 SqIn, with  
806 SqIn Charge Air Cooler
- 12THJ - FAN DRIVE {Horton  
Drivemaster} Automatic  
On/Off Type, with Normally  
Closed Temperature Control
- 12VBY - AIR CLEANER Single  
Element, Engine Mounted
- \* GAUGE, AIR CLEANER  
RESTRICTION Air Cleaner  
Mounted
- 12703 - ANTI-FREEZE Red,  
Extended Life Coolant; To  
-40 Degrees F/ -40 Degrees  
C, Freeze Protection
- 12XBE - CRUISE CONTROL  
Predictive, Includes GPS  
Enhanced Cruise Control;  
Includes Module, Antenna and  
Wiring
- 12WCX - HOSE CLAMPS, RADIATOR  
HOSES {Gates} Shrink Band  
Type
- 12WYZ - RADIATOR DRAIN & FILL  
FITTING SPECIAL; To Vacuum  
Out or Fill the Cooling  
System from the Bottom of  
Radiator, for Use with  
Quick-Connect Radiator Drain  
Tool or Shop Coolant  
Evacuation-Fill System
- 13 TRANSMISSION**
- 13GY - TRANSMISSION, MANUAL  
{Eaton Endurant EEO-14F112C}  
12-Speed Fully Automated  
Manual, Aluminum Clutch  
Housing, Overdrive,  
Mechatronic Shift Controls,  
Pneumatic Clutch Actuation,  
Internal Lube Oil Pump, Hill  
Start Aid

Refer To General Info for Metric Conversion Tables

**INTERNATIONAL®****LT****SERIES HEAVY DUTY****LT625 4x2****STANDARD EQUIPMENT****MODEL CODE: LT62A00**

<b>13 TRANSMISSION</b>	<b>(CONT.)</b>	<b>16 CAB</b>	<b>(CONT.)</b>	<b>16 CAB</b>	<b>(CONT.)</b>
13WLW - TRANSMISSION OIL {EmGard 40W} Synthetic; 1 thru 21.99 Pints		* FLOOR COVERING Rubber, Black		16HCS - GAUGE, TEMPERATURE, AMBIENT Sensor Wiring with Display Unit Mounted in Cluster	
<b>14A AXLE, REAR</b>		* GLASS, ALL WINDOWS Tinted		16XJP - INSTRUMENT PANEL Wing Panel	
14051 - AXLE, REAR, SINGLE {Meritor RS-23-160} Single Reduction, 23,000-lb Capacity, 200 Wheel Ends		* GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side		16SNS - MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Black Heads and Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width	
* RATIO: 2.50, 2.67, 2.80, 2.93, 3.07, 3.21, 3.42, 3.58, 3.73, 3.91, 4.10, 4.30, 4.56, 4.89, 5.38, 5.63, 6.14, 6.43, 6.83 OR 7.17		* GRAB HANDLE, CAB INTERIOR (4) "B" Pillar and Door Mounted, Two Each Side		<b>NOTE:</b> Mirror Dimensions are Rounded to the Nearest 0.5"	
14TBJ - SUSPENSION, REAR, AIR, SINGLE {International IROS} 20,000-lb Capacity, 9.25" Ride Height, with Shock Absorbers		* INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color		- For U.S. Only	
14WMG - AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 30 thru 39.99 Pints		* READING LIGHT, CAB Located in Overhead Console		16VVM - MONITOR, TIRE PRESSURE System Gives Warning that Tire Pressure is Below Set Pressure, Monitors Tire Pressure of Each Tire with Temperature Compensation, Data Displayed in the LCD of the Cluster, for 4x2, 6x4 and 6x2 Axle Configurations, Does Not Include Lift Axles or Spare Wheels	
<b>15 FUEL TANKS</b>		* STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door		16KAM - SEAT, DRIVER {National 2000 Model 295} Air Suspension, Intermediate Back, All Vinyl, 2 Arm Rests, Isolator, 7" Adjuster, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, 3-14 Degree Back Angle Adjust	
* FUEL LINE FITTINGS O-Ring Snap-On Quick-Connect Voss Fittings at Both Ends; Anchored to frame for Fuel Hoses		16ZBS - ACCESS, CAB Steel, Driver and Passenger Sides, Two Steps per Door, for use with Day Cab or Sleeper Cab		16REP - SEAT, PASSENGER {National 2000} Non Suspension, Intermediate Back, All Vinyl, 11 Degree Back Angle	
15SYK - FUEL TANK Top Draw, Non-Polished Aluminum, 26" Dia, 70 US Gal (265L), Mounted Left Side, Back of Cab/Under Sleeper		16BAM - AIR CONDITIONER with Integral Heater and Defroster		16WJU - WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature	
15WDM - DEF TANK 10.6 US Gal (40L) Capacity, Frame Mounted Outside Left Rail, Back of Cab/Under Sleeper		* HOSE CLAMPS, HEATER HOSE {Mubea} Constant Tension Clamps		<b>27/28 WHEELS &amp; TIRES</b>	
15LPR - FUEL/WATER SEPARATOR {Racor 6600} 12 VDC Electric Heater, Includes Pre-Heater, Fuel Heated with Fuel Blender Valve, with Sight Bowl, Includes Water-In-Fuel Sensor		16VKB - CAB INTERIOR TRIM Classic, for Day Cab		* WHEEL SEALS, FRONT {International} Oil Lubricated, Includes Wheel Bearings	
* LOCATION FUEL/WATER SEPARATOR Mounted Left Rail in Wheel Well		* DOOR TRIM, INTERIOR Black Handle		* WHEEL SEALS, REAR {International} Oil Lubricated, Includes Wheel Bearings	
<b>16 CAB</b>		* INSTRUMENT PANEL TRIM Black, Black Gauges with Black Bezels		27DVN - WHEELS, FRONT {Accuride 42644} DISC; 22.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	
16030 - CAB Conventional, Day Cab		* SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap		28DVN - WHEELS, REAR {Accuride 42644} DUAL DISC; 22.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	
* CLEARANCE/MARKER LIGHTS (5) Flush Mounted		16GEG - GAUGE CLUSTER Premium Level; English with English Electronic Speedometer			
* COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window		* GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for Fuel/DEF, DPF Level			
* CONSOLE, CENTER Includes Two Cup Holders and One Additional Storage Area		* GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure			
* COURTESY LIGHT (2) Driver and Passenger Door Mounted		* WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)			
* DOME LIGHT, CAB Rectangular, Door and Instrument Panel Mounted Switch Activated, Timed Theater Dimming, Center Mounted, Integral to Console					

Refer To General Info for Metric Conversion Tables



**INTERNATIONAL®**

**LT**

**SERIES HEAVY DUTY**

**LT625 4x2**

---

**STANDARD EQUIPMENT**

**MODEL CODE: LT62A00**

**27/28 WHEELS & TIRES (CONT.)**

770249 5443 (02) 295/75R22.5

14-PR LR-G SINGLE FRONT

RADIAL TIRES {Continental

Tire ECOPLUS HS3+}

770249 5443 (04) 295/75R22.5

14-PR LR-G DUAL REAR RADIAL

TIRES {Continental Tire

ECOPLUS HS3+}

**29 SPECIAL WHEELS**

29CAG - WHEEL COVER, REAR

Aerodynamic, 22.5", Black

**40 WARRANTY**

40125 - WARRANTY Standard for

LT/RH Series, Effective with

Vehicles Built January 2,

2016 or Later, CTS-2010A

---

Refer To General Info for Metric Conversion Tables

**INTERNATIONAL® LT SERIES SECTION 750 - STANDARD EQUIPMENT PRICES EFFECTIVE 04/01/2022**

**PLH-284 REVISION NO. 204A**

**PAGE 750-5**

**SUBJECT TO CHANGE WITHOUT NOTICE**

Printed in the United States of America

All Taxes Extra, when Applicable

**INTERNATIONAL®****LT****SERIES HEAVY DUTY****LT625 6x4****STANDARD EQUIPMENT****MODEL CODE: LT62F00****LIST PRICE: \$267,532.00****01 FRAMES**

- \* NOTE: APPLICATION AND COUNTRY RESTRICTION INFORMATION IS NOT SHOWN IN THE AVAILABLE EQUIPMENT SECTIONS. PLEASE REFER TO THE TOPS APPLICATION IN SALES TOOLS FOR THIS RESTRICTION INFORMATION.

- 01CBV - FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.125" x 3.580" x 0.312" (257.2mm x 90.9mm x 8.0mm); 367.4" (9333mm) Maximum OAL
- 01LRL - BUMPER, FRONT 3-Piece, Aerodynamic, Plastic, Molded Dark Gray
- 01616 - FRAME RAILS WITH TAPERED REAR
- 01WKJ - WHEELBASE RANGE 152" (385cm) Through and Including 185" (470cm)

**02 AXLE, FRONT**

- 02AVH - AXLE, FRONT NON-DRIVING {Hendrickson Steertek IADB} Wide Track, Fabricated Type, 12,350-lb Capacity, with Integrated Air Disc Brake Knuckle

**03A SUSPENSION, FRONT**

- 03AHN - SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 12,350-lb Capacity, with Shock Absorbers
- \* SPRING PINS Rubber Bushings, Maintenance-Free

**04 BRAKES**

- 04092 - BRAKE SYSTEM, AIR Dual System for Tractor Applications
- \* BRAKE LINES Color and Size Coded Nylon
- \* BRAKE PRESSURE INDICATOR Low Air Pressure Warning Light and Audible Alarm
- \* DRAIN VALVE Manually Operated (On Wet Tank Only)
- \* GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster
- \* GLAD HANDS (2) One for Service and One for Emergency; Trailer Hoses from Cab
- \* HAND CONTROL VALVE, AIR with Self Return Handle, for Trailer Brakes, Mounted in Instrument Panel
- \* HOSE TENDER Back of Cab Mounted

**04 BRAKES****(CONT.)**

- \* PARKING BRAKE CONTROL Yellow and Red Knobs, Located on Instrument Panel
- \* PARKING BRAKE VALVE Combination Valve for Tractor and Trailer
- \* QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for Forward Rear Axle
- \* TRACTOR PROTECTION VALVE NOTE: Front and Rear Dust Shields not Included
- NOTE: Rear Axle is Limited to 40,000-lb GAWR with Code 04092 BRAKE SYSTEM, AIR and Standard Rear Air Cam Brakes Regardless of Axle/Suspension Ordered
- 04AZS - AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Electronic Stability Program, with Automatic Traction Control
- 04XCJ - BRAKES, FRONT {Bendix Spicer ADB22X} Air Disc Type, Extended Service, Size 22.5", 23,000-lb Capacity
- 04XDW - BRAKE CHAMBERS, FRONT AXLE 18 Sqn, for Air Disc Brakes
- 04XCK - BRAKES, REAR {Bendix Spicer ADB22X} Air Disc Type, Extended Service, Size 22.5", 26,000-lb Capacity per Axle
- 04XEA - BRAKE CHAMBERS, REAR AXLE 18/24 Sqn Spring Brake, Double Diaphragm, for Air Disc Brakes
- 04SPM - AIR COMPRESSOR {Bendix BA-921 Head Unload} 15.9 CFM
- 04EDM - AIR DRYER {Bendix AD-HF} with Heater, Includes Pressure Protection Circuits, Safety Valve, Integral Purge Tank, Governor Pressure Settings 110 psi Cut-In/130 psi Cut-Out, Integrated PuraGuard Coalescing Filtration
- 04VHW - AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Left Rail, Under Cab; Perpendicular to Rail

**04 BRAKES****(CONT.)**

- 04XAH - TRAILER HOSES AND CABLES {Erich Jaeger} Coiled, Phillips Nylon Hose, 15' Working Length, 24" Tractor Lead Length, 6" Trailer Lead Length, Aluminum Glad Hands with Rubber Seals, Lighting Cable with Polypropylene Composite Plug

**05 STEERING**

- 05PSM - STEERING GEAR {Sheppard HD94} Power
- 05710 - STEERING COLUMN Tilting and Telescoping
- 05CAW - STEERING WHEEL 4-Spoke; 18" Dia., Black

**06 DRIVELINES**

- \* END YOKES Half-Round, Easy Service (All)
- \* SLIP JOINT SPLINES Nylon-Coated
- 06DGX - DRIVELINE SYSTEM {Dana Spicer} Service Free SPL250 Main Driveline with SPL170 Interaxle Shaft, for 6x4

**07 EXHAUST SYSTEM**

- 07BLV - EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Short Horizontal Tail Pipe, Frame Mounted Right Side Back of Cab
- 07SDK - ENGINE COMPRESSION BRAKE by Jacobs; for N13/A26 Engines, with Selector Switch and On/Off Switch
- 07WDR - TAIL PIPE (1) Horizontal, Short

**08 ELECTRICAL**

- 08000 - ELECTRICAL SYSTEM 12-Volt, Standard Equipment
- \* DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab
- \* HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel
- \* HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever
- \* HORN, ELECTRIC Single
- \* PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light
- \* POWER SOURCE Cigar Type Receptacle with Cap, USB Port, Located in Instrument Panel
- \* STARTER SWITCH Electric, Key Operated
- \* TURN SIGNAL SWITCH Manual Cancelling with Lane Change Feature

Refer To General Info for Metric Conversion Tables

**INTERNATIONAL®****LT****SERIES HEAVY DUTY****LT625 6x4****STANDARD EQUIPMENT****MODEL CODE: LT62F00****08 ELECTRICAL****(CONT.)**

- \* TURN SIGNALS, FRONT  
Includes Reflectors and  
Auxiliary Side Turn  
Signals, Solid State  
Flashers; Flush Mounted
- \* WINDSHIELD WIPER SWITCH  
2-Speed with Wash and  
Intermittent Feature (5  
Pre-Set Delays), Integral  
with Turn Signal Lever
- \* WINDSHIELD WIPERS Single  
Motor, Electric, Cowl  
Mounted
- \* WIRING, CHASSIS Color Coded  
and Continuously Numbered
- 08GXJ - ALTERNATOR  
{Leece-Neville AVI160P2013}  
Brush Type, 12 Volt, 160 Amp  
Capacity, Pad Mount
- 08XHL - BATTERY BOX Steel, 30"  
Wide, 2-4 Battery Capacity,  
Mounted Left Side Under Cab
- 08MSG - BATTERY SYSTEM  
{Fleetrite}  
Maintenance-Free, (3)  
12-Volt 1980CCA Total, Top  
Threaded Stud
- 08RJW - CB RADIO Omit Power  
Feeds, Power Source and  
Wiring
- 08XAH - CIRCUIT BREAKERS  
Manual-Reset (Main Panel)  
SAE Type III with Trip  
Indicators, Replaces All  
Fuses
- 08TRG - COLLISION MITIGATION  
SYSTEM {Bendix Wingman  
Fusion} Adaptive Cruise,  
Enhanced Collision  
Mitigation, Multilane Auto &  
Stat Vehicle Braking, Stat  
Obj Alert, Roadway Depart  
Alert & Braking, Lane Depart  
Warning Switch & Spkr, S, F  
Ovrspd Alert & Action, Frt  
Radar & Camera, Drvr  
Display, Safety Direct  
Capable, Less Safety Direct  
Cable
- 08XMB - CONNECTOR, DASH, CENTER  
PANEL Cab Wiring for TMC  
RP1226 Vehicle Accessory  
Connector; Includes 14-pin  
Connector with Switched  
Power, Battery Power,  
Ignition Power, Ground &  
Body 250K Datalink,  
Connector Located Behind  
Instrument Panel Center  
Console
- 08WXB - HEADLIGHT WARNING  
BUZZER Sounds When Head  
Light Switch is on and  
Ignition Switch is in "Off"  
Position

**08 ELECTRICAL****(CONT.)**

- 08XPA - HEADLIGHTS LED, with  
Daytime Running Lights,  
Automatic Twilight  
Controlled
- 08WRB - HEADLIGHTS ON W/WIPERS  
Headlights Will  
Automatically Turn on if  
Windshield Wipers are turned  
on
- 08XHN - HORN, AIR Single  
Trumpet, Black, with Lanyard  
Pull Cord
- 08RPU - RADIO  
AM/FM/WB/SiriusXM/Clock/Bluetooth/USB Input/Auxiliary  
Input
- 08RMV - SPEAKERS (2) 6.5" Dual  
Cone Mounted in Doors
- 08WVG - STARTING MOTOR  
{Mitsubishi Electric  
Automotive America 105P}  
12-Volt, with Soft-Start
- 08TPP - STOP, TURN, TAIL & B/U  
LIGHTS Multi-Function Lamp,  
with LED Lights for Stop,  
Turn, Tail and Backup  
Lights, Includes LED License  
Plate Light
- 08XHX - SWITCH, MARKER  
INTERRUPT for Marker Lights  
and Headlights, Located in  
Steering Wheel
- 08WPZ - TEST EXTERIOR LIGHTS  
Pre-Trip Inspection will  
Cycle all Exterior Lamps  
Except Back-up Lights

**09 FRONT END**

- 09WAY - FRONT END Tilting,  
Fiberglass, with Three Piece  
Construction
- \* BUG SCREEN Front End;  
Mounted Behind Grille
- \* HOOD TILT ASSIST Includes  
Torsion Bar Spring System
- 09HAD - GRILLE Chrome
- 09AAB - LOGOS EXTERIOR Model  
Badges
- 09AAE - LOGOS EXTERIOR, ENGINE  
Badges

**10 PAINT & MISCELLANEOUS**

- 10AEU - INTELLIGENT FLEET CARE  
Telematics Device with Over  
the Air Programming;  
Includes Five Year Data  
Plan, Advanced Preventive  
Maintenance, Fleet Health  
Monitor Reporting and  
International 360
- 10HZN - FIFTH WHEEL, AIR SLIDE  
{Fontaine SL6NWB675012} 12"  
Slide, 6.75" Above Top of  
Frame, Left Hand Release
- 10WPR - MUD FLAP HOLDER Spring  
Loaded, Painted Black, with  
Red and White Reflective  
Tape, Less Flaps

**10 PAINT & MISCELLANEOUS (CONT.)**

- 10060 - PAINT SCHEMATIC, PT-1  
Single Color, Design 100
- \* PAINT SCHEMATIC ID LETTERS  
"HX"
- 10761 - PAINT TYPE Base  
Coat/Clear Coat, 1-2 Tone
- 11 CLUTCH**
- 11MHM - CLUTCH {Eaton Fuller  
430MM} Maintenance Free,  
Self-Adjusting, 17" (430 mm)  
Dia Single Plate, Diaphragm  
Spring, Organic, 5-Spring  
Coaxial 254mm Damper with  
Pre-Damper, 2"-18 Tooth  
Spline, Pneumatic Push Type  
Control, 1850 lb-ft (2508  
Nm) Torque Capacity

**12 ENGINE**

- 12BGA - ENGINE, DIESEL  
{International A26} EPA  
2021, 410HP @ 1700 RPM, 1450  
lb-ft Torque @ 900 RPM, 1800  
RPM Governed Speed, 410 Peak  
HP (Max)
- 12XBC - RADIATOR Aluminum,  
Welded, Down Flow, Front to  
Back System, 1325 SqIn, with  
806 SqIn Charge Air Cooler
- 12THJ - FAN DRIVE {Horton  
Drivemaster} Automatic  
On/Off Type, with Normally  
Closed Temperature Control
- 12VBY - AIR CLEANER Single  
Element, Engine Mounted
- \* GAUGE, AIR CLEANER  
RESTRICTION Air Cleaner  
Mounted
- 12703 - ANTI-FREEZE Red,  
Extended Life Coolant; To  
-40 Degrees F/ -40 Degrees  
C, Freeze Protection
- 12XBE - CRUISE CONTROL  
Predictive, Includes GPS  
Enhanced Cruise Control;  
Includes Module, Antenna and  
Wiring
- 12WCX - HOSE CLAMPS, RADIATOR  
HOSES {Gates} Shrink Band  
Type
- 12WYZ - RADIATOR DRAIN & FILL  
FITTING SPECIAL; To Vacuum  
Out or Fill the Cooling  
System from the Bottom of  
Radiator, for Use with  
Quick-Connect Radiator Drain  
Tool or Shop Coolant  
Evacuation-Fill System
- 13 TRANSMISSION**
- 13GY - TRANSMISSION, MANUAL  
{Eaton Endurant EEO-14F112C}  
12-Speed Fully Automated  
Manual, Aluminum Clutch  
Housing, Overdrive,  
Mechatronic Shift Controls,  
Pneumatic Clutch Actuation,  
Internal Lube Oil Pump, Hill  
Start Aid

Refer To General Info for Metric Conversion Tables

**INTERNATIONAL®****LT****SERIES HEAVY DUTY****LT625 6x4****STANDARD EQUIPMENT****MODEL CODE: LT62F00**

<b>13 TRANSMISSION</b>	<b>(CONT.)</b>	<b>16 CAB</b>	<b>(CONT.)</b>	<b>16 CAB</b>	<b>(CONT.)</b>
13WLW - TRANSMISSION OIL {EmGard 40W} Synthetic; 1 thru 21.99 Pints		* DOME LIGHT, CAB Rectangular, Door and Instrument Panel Mounted Switch Activated, Timed Theater Dimming, Center Mounted, Integral to Console		* WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)	
<b>14A AXLE, REAR</b>		* FLOOR COVERING Rubber, Black		16HCS - GAUGE, TEMPERATURE, AMBIENT Sensor Wiring with Display Unit Mounted in Cluster	
14GVD - AXLE, REAR, TANDEM {Meritor MT-40-14X-3CFR} Single Reduction, Amboid Gearing in Rear-Rear Axle, 40,000-lb Capacity, .374"(9.5mm) Wall Housing Thickness, R Wheel Ends		* GLASS, ALL WINDOWS Tinted		16XJP - INSTRUMENT PANEL Wing Panel	
* RATIO: 2.47, 2.64, 2.79, 2.85, 3.08, 3.25, 3.36, 3.42, 3.55, 3.70, 3.90 OR 4.11		* GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side		16SNS - MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Black Heads and Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width	
* POWER DIVIDER LOCK Electric over Air Operated, Cab Control with Indicator Light		* GRAB HANDLE, CAB INTERIOR (4) "B" Pillar and Door Mounted, Two Each Side		<b>NOTE:</b> Mirror Dimensions are Rounded to the Nearest 0.5"	
14WMJ - AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 50 thru 64.99 Pints		* INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color		<b>NOTE:</b> Mirror Dimensions are Rounded to the Nearest 0.5"	
<b>14B SUSPENSION, REAR</b>		* READING LIGHT, CAB Located in Overhead Console		- For U.S. Only	
14UPZ - SUSPENSION, REAR, AIR, TANDEM {International} Ride Optimized Suspension (IROS), 40,000-lb Capacity, 52" Axle Spacing, 9.25" Ride Height, with Shock Absorbers		* STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door		16VVM - MONITOR, TIRE PRESSURE System Gives Warning that Tire Pressure is Below Set Pressure, Monitors Tire Pressure of Each Tire with Temperature Compensation, Data Displayed in the LCD of the Cluster, for 4x2, 6x4 and 6x2 Axle Configurations, Does Not Include Lift Axles or Spare Wheels	
<b>15 FUEL TANKS</b>		16ZBS - ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab or Sleeper Cab		16KAM - SEAT, DRIVER {National 2000 Model 295} Air Suspension, Intermediate Back, All Vinyl, 2 Arm Rests, Isolator, 7" Adjuster, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, 3-14 Degree Back Angle Adjust	
* FUEL LINE FITTINGS O-Ring Snap-On Quick-Connect Voss Fittings at Both Ends; Anchored to frame for Fuel Hoses		16BAM - AIR CONDITIONER with Integral Heater and Defroster		16REP - SEAT, PASSENGER {National 2000} Non Suspension, Intermediate Back, All Vinyl, 11 Degree Back Angle	
15SYK - FUEL TANK Top Draw, Non-Polished Aluminum, 26" Dia, 70 US Gal (265L), Mounted Left Side, Back of Cab/Under Sleeper		* HOSE CLAMPS, HEATER HOSE {Mubea} Constant Tension Clamps		16WJU - WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature	
15WDM - DEF TANK 10.6 US Gal (40L) Capacity, Frame Mounted Outside Left Rail, Back of Cab/Under Sleeper		16VKB - CAB INTERIOR TRIM Classic, for Day Cab		<b>27/28 WHEELS &amp; TIRES</b>	
15LPR - FUEL/WATER SEPARATOR {Racor 6600} 12 VDC Electric Heater, Includes Pre-Heater, Fuel Heated with Fuel Blender Valve, with Sight Bowl, Includes Water-In-Fuel Sensor		* DOOR TRIM, INTERIOR Black Handle		* WHEEL SEALS, FRONT {International} Oil Lubricated, Includes Wheel Bearings	
* LOCATION FUEL/WATER SEPARATOR Mounted Left Rail in Wheel Well		* INSTRUMENT PANEL TRIM Black, Black Gauges with Black Bezels		* WHEEL SEALS, REAR {International} Oil Lubricated, Includes Wheel Bearings	
<b>16 CAB</b>		* SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap			
16030 - CAB Conventional, Day Cab		16GEG - GAUGE CLUSTER Premium Level; English with English Electronic Speedometer			
* CLEARANCE/MARKER LIGHTS (5) Flush Mounted		* GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for Fuel/DEF, DPF Level			
* COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window		* GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure			
* CONSOLE, CENTER Includes Two Cup Holders and One Additional Storage Area					
* COURTESY LIGHT (2) Driver and Passenger Door Mounted					

Refer To General Info for Metric Conversion Tables



**INTERNATIONAL®**

**LT**

**SERIES HEAVY DUTY**

**LT625 6x4**

---

**STANDARD EQUIPMENT**

**MODEL CODE: LT62F00**

---

**27/28 WHEELS & TIRES (CONT.)**

27DVN - WHEELS, FRONT {Accuride  
42644} DISC; 22.5x8.25 Rims,  
Standard Polish Aluminum,  
10-Stud, 285.75mm BC,  
Hub-Piloted, Flanged Nut,  
with Steel Hubs

28DVN - WHEELS, REAR {Accuride  
42644} DUAL DISC; 22.5x8.25  
Rims, Standard Polish  
Aluminum, 10-Stud, 285.75mm  
BC, Hub-Piloted, Flanged  
Nut, with Steel Hubs

770249 5443 (02) 295/75R22.5  
14-PR LR-G SINGLE FRONT  
RADIAL TIRES {Continental  
Tire ECOPLUS HS3+}

770249 5443 (08) 295/75R22.5  
14-PR LR-G DUAL REAR RADIAL  
TIRES {Continental Tire  
ECOPLUS HS3+}

**29 SPECIAL WHEELS**

29CAG - WHEEL COVER, REAR  
Aerodynamic, 22.5", Black

**40 WARRANTY**

40125 - WARRANTY Standard for  
LT/RH Series, Effective with  
Vehicles Built January 2,  
2016 or Later, CTS-2010A

---

Refer To General Info for Metric Conversion Tables