

**INTERNATIONAL®****RH****SERIES HEAVY DUTY****RH613 4x2****STANDARD EQUIPMENT****MODEL CODE: RH61A00****LIST PRICE:****01 FRAMES**

- * NOTE: APPLICATION AND COUNTRY RESTRICTION INFORMATION IS NOT SHOWN IN THE AVAILABLE EQUIPMENT SECTIONS. PLEASE REFER TO THE TOPS APPLICATION IN SALES TOOLS FOR THIS RESTRICTION INFORMATION.

- 01CBV - FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.125" x 3.580" x 0.312" (257.2mm x 90.9mm x 8.0mm); 367.4" (9333mm) Maximum OAL
- 01LRL - BUMPER, FRONT 3-Piece, Aerodynamic, Plastic, Molded Dark Gray
- 01616 - FRAME RAILS WITH TAPERED REAR
- 01WKM - WHEELBASE RANGE 140" (355cm) Through and Including 156" (395cm)

02 AXLE, FRONT

- 02AUD - AXLE, FRONT NON-DRIVING {Hendrickson SteerTek NXT} Wide Track, Fabricated Type, 12,350-lb Capacity

03A SUSPENSION, FRONT

- 03AHN - SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 12,350-lb Capacity, with Shock Absorbers
- * SPRING PINS Rubber Bushings, Maintenance-Free

04 BRAKES

- 04092 - BRAKE SYSTEM, AIR Dual System for Tractor Applications
- * BRAKE LINES Color and Size Coded Nylon
- * BRAKE PRESSURE INDICATOR Low Air Pressure Warning Light and Audible Alarm
- * DRAIN VALVE Manually Operated (On Wet Tank Only)
- * GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster
- * GLAD HANDS (2) One for Service and One for Emergency; Trailer Hoses from Cab
- * HAND CONTROL VALVE, AIR with Self Return Handle, for Trailer Brakes, Mounted in Instrument Panel
- * HOSE TENDER Back of Cab Mounted
- * PARKING BRAKE CONTROL Yellow and Red Knobs, Located on Instrument Panel

04 BRAKES

- * PARKING BRAKE VALVE Combination Valve for Tractor and Trailer
 - * QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for Forward Rear Axle
 - * TRACTOR PROTECTION VALVE
 - 04AZS - AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Electronic Stability Program, with Automatic Traction Control
 - 04XDP - BRAKES, FRONT {Meritor 16.5X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 5", 14,700-lb Capacity
 - 04EXV - BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 SqIn
 - 04LAG - SLACK ADJUSTERS, FRONT {Gunitite} Automatic
 - 04XDE - BRAKES, REAR {Meritor 16.5X7 Q-PLUS LW} Air S-Cam Type, Fabricated Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 20,000-lb Capacity per Axle
 - 04EXU - BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqIn Spring Brake
 - * BRAKE CHAMBERS, POSITION (2) Rear Parking; WITH TRUCK BRAKES: All 4x2, 4x4; WITH TRACTOR BRAKES: All 4x2, 4x4; 6x4 & 6x6 with Rear Tandem Axles Less Than 46,000-lb. or GVWR Less Than 54,000-lb.
 - 04LGG - SLACK ADJUSTERS, REAR {Gunitite} Automatic
 - 04SPM - AIR COMPRESSOR {Bendix BA-921 Head Unload} 15.9 CFM
 - 04EDM - AIR DRYER {Bendix AD-HF} with Heater, Includes Pressure Protection Circuits, Safety Valve, Integral Purge Tank, Governor Pressure Settings 110 psi Cut-In/130 psi Cut-Out, Integrated PuraGuard Coalescing Filtration
 - 04VHW - AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Left Rail, Under Cab; Perpendicular to Rail
- 05 STEERING**
- 05PSM - STEERING GEAR {Sheppard HD94} Power
 - 05710 - STEERING COLUMN Tilting and Telescoping
 - 05CAW - STEERING WHEEL 4-Spoke; 18" Dia., Black

(CONT.)

06 DRIVELINES

- * END YOKES Half-Round, Easy Service (All)
- * SLIP JOINT SPLINES Nylon-Coated
- 06DGM - DRIVELINE SYSTEM {Dana Spicer} Service Free SPL250, for 4x2/6x2

07 EXHAUST SYSTEM

- 07BLV - EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Short Horizontal Tail Pipe, Frame Mounted Right Side Back of Cab
- 07SDK - ENGINE COMPRESSION BRAKE by Jacobs; for N13/A26 Engines, with Selector Switch and On/Off Switch
- 07WDR - TAIL PIPE (1) Horizontal, Short

08 ELECTRICAL

- 08000 - ELECTRICAL SYSTEM 12-Volt, Standard Equipment
- * DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab
- * HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel
- * HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever
- * HORN, ELECTRIC Single
- * PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light
- * POWER SOURCE Cigar Type Receptacle with Cap, USB Port, Located in Instrument Panel
- * STARTER SWITCH Electric, Key Operated
- * TURN SIGNAL SWITCH Manual Cancelling with Lane Change Feature
- * TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted
- * WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever
- * WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted
- * WIRING, CHASSIS Color Coded and Continuously Numbered
- 08GXJ - ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount

Refer To General Info for Metric Conversion Tables

**INTERNATIONAL®****RH****SERIES HEAVY DUTY****RH613 4x2****STANDARD EQUIPMENT****MODEL CODE: RH61A00****08 ELECTRICAL****(CONT.)**

- 08XHL - BATTERY BOX Steel, 30" Wide, 2-4 Battery Capacity, Mounted Left Side Under Cab
- 08MSG - BATTERY SYSTEM {Fleetrite}
Maintenance-Free, (3)
12-Volt 1980CCA Total, Top Threaded Stud
- 08RJW - CB RADIO Omit Power Feeds, Power Source and Wiring
- 08XAH - CIRCUIT BREAKERS
Manual-Reset (Main Panel)
SAE Type III with Trip Indicators, Replaces All Fuses
- 08TRG - COLLISION MITIGATION SYSTEM {Bendix Wingman Fusion} Adaptive Cruise, Enhanced Collision Mitigation, Multilane Auto & Stat Vehicle Braking, Stat Obj Alert, Roadway Depart Alert & Braking, Lane Depart Warning Switch & Spkrs, Ovrspd Alert & Action, Frt Radar & Camera, Drvr Display, Safety Direct Cable, Less Safety Direct Cable
- 08XMB - CONNECTOR, DASH, CENTER PANEL Cab Wiring for TMC RP1226 Vehicle Accessory Connector; Includes 14-pin Connector with Switched Power, Battery Power, Ignition Power, Ground & Body 250K Datalink, Connector Located Behind Instrument Panel Center Console
- 08WXB - HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position
- 08XPA - HEADLIGHTS LED, with Daytime Running Lights, Automatic Twilight Controlled
- 08WRB - HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on
- 08XHN - HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord
- 08RPU - RADIO
AM/FM/WB/SiriusXM/Clock/Bluetooth/USB Input/Auxiliary Input
- 08RMV - SPEAKERS (2) 6.5" Dual Cone Mounted in Doors

08 ELECTRICAL**(CONT.)**

- 08WXG - STARTING MOTOR {Mitsubishi Electric Automotive America 105P}
12-Volt, with Soft-Start
 - 08TTP - STOP, TURN, TAIL & B/U LIGHTS Multi-Function Lamp, with LED Lights for Stop, Turn, Tail and Backup Lights, Includes LED License Plate Light
 - 08XHX - SWITCH, MARKER INTERRUPT for Marker Lights and Headlights, Located in Steering Wheel
 - 08WPZ - TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights
- 09 FRONT END**
- 09WAY - FRONT END Tilting, Fiberglass, with Three Piece Construction
* BUG SCREEN Front End; Mounted Behind Grille
* HOOD TILT ASSIST Includes Torsion Bar Spring System
 - 09HAD - GRILLE Chrome
 - 09AAB - LOGOS EXTERIOR Model Badges
 - 09AAE - LOGOS EXTERIOR, ENGINE Badges
- 10 PAINT & MISCELLANEOUS**
- 10AEU - INTELLIGENT FLEET CARE Telematics Device with Over the Air Programming; Includes Five Year Data Plan, Advanced Preventive Maintenance, Fleet Health Monitor Reporting and International 360
 - 10HZN - FIFTH WHEEL, AIR SLIDE {Fontaine SL6NWB675012} 12" Slide, 6.75" Above Top of Frame, Left Hand Release
 - 10WPR - MUD FLAP HOLDER Spring Loaded, Painted Black, with Red and White Reflective Tape, Less Flaps
 - 10060 - PAINT SCHEMATIC, PT-1 Single Color, Design 100
* PAINT SCHEMATIC ID LETTERS "HW"
 - 10761 - PAINT TYPE Base Coat/Clear Coat, 1-2 Tone
- 11 CLUTCH**
- 11MHM - CLUTCH {Eaton Fuller 430MM} Maintenance Free, Self-Adjusting, 17" (430 mm) Dia Single Plate, Diaphragm Spring, Organic, 5-Spring Coaxial 254mm Damper with Pre-Damper, 2"-18 Tooth Spline, Pneumatic Push Type Control, 1850 lb-ft (2508 Nm) Torque Capacity

12 ENGINE

- 12BGA - ENGINE, DIESEL {International A26} EPA 2021, 410HP @ 1700 RPM, 1450 lb-ft Torque @ 900 RPM, 1800 RPM Governed Speed, 410 Peak HP (Max)
 - 12XBC - RADIATOR Aluminum, Welded, Down Flow, Front to Back System, 1325 SqIn, with 806 SqIn Charge Air Cooler
 - 12THJ - FAN DRIVE {Horton Drivemaster} Automatic On/Off Type, with Normally Closed Temperature Control
 - 12VBC - AIR CLEANER Single Element
* GAUGE, AIR CLEANER RESTRICTION Air Cleaner Mounted
 - 12703 - ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection
 - 12XBE - CRUISE CONTROL Predictive, Includes GPS Enhanced Cruise Control; Includes Module, Antenna and Wiring
 - 12WCX - HOSE CLAMPS, RADIATOR HOSES {Gates} Shrink Band Type
 - 12WYZ - RADIATOR DRAIN & FILL FITTING SPECIAL; To Vacuum Out or Fill the Cooling System from the Bottom of Radiator, for Use with Quick-Connect Radiator Drain Tool or Shop Coolant Evacuation-Fill System
- 13 TRANSMISSION**
- 13GYG - TRANSMISSION, MANUAL {Eaton Endurant EEO-14F112C} 12-Speed Fully Automated Manual, Aluminum Clutch Housing, Overdrive, Mechatronic Shift Controls, Pneumatic Clutch Actuation, Internal Lube Oil Pump, Hill Start Aid
 - 13WLW - TRANSMISSION OIL {EmGard 40W} Synthetic; 1 thru 21.99 Pints

14A AXLE, REAR

- 14051 - AXLE, REAR, SINGLE {Meritor RS-23-160} Single Reduction, 23,000-lb Capacity, 200 Wheel Ends
* RATIO: 2.50, 2.67, 2.80, 2.93, 3.07, 3.21, 3.42, 3.58, 3.73, 3.91, 4.10, 4.30, 4.56, 4.89, 5.38, 5.63, 6.14, 6.43, 6.83 OR 7.17

Refer To General Info for Metric Conversion Tables

**INTERNATIONAL®****RH****SERIES HEAVY DUTY****RH613 4x2****STANDARD EQUIPMENT****MODEL CODE: RH61A00**

14A AXLE, REAR (CONT.)	16 CAB (CONT.)	16 CAB (CONT.)
14TBJ - SUSPENSION, REAR, AIR, SINGLE {International IROS} 20,000-lb Capacity, 9.25" Ride Height, with Shock Absorbers	16ZBS - ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab or Sleeper Cab	16VVM - MONITOR, TIRE PRESSURE System Gives Warning that Tire Pressure is Below Set Pressure, Monitors Tire Pressure of Each Tire with Temperature Compensation, Data Displayed in the LCD of the Cluster, for 4x2, 6x4 and 6x2 Axle Configurations, Does Not Include Lift Axles or Spare Wheels
14WVG - AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 30 thru 39.99 Pints	16BAM - AIR CONDITIONER with Integral Heater and Defroster	16KAM - SEAT, DRIVER {National 2000 Model 295} Air Suspension, Intermediate Back, All Vinyl, 2 Arm Rests, Isolator, 7" Adjuster, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, 3-14 Degree Back Angle Adjust
15 FUEL TANKS	* HOSE CLAMPS, HEATER HOSE {Mubea} Constant Tension Clamps	16REP - SEAT, PASSENGER {National 2000} Non Suspension, Intermediate Back, All Vinyl, 11 Degree Back Angle
* FUEL LINE FITTINGS O-Ring Snap-On Quick-Connect Voss Fittings at Both Ends; Anchored to frame for Fuel Hoses	16VKB - CAB INTERIOR TRIM Classic, for Day Cab	16WJU - WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature
15SYK - FUEL TANK Top Draw, Non-Polished Aluminum, 26" Dia, 70 US Gal (265L), Mounted Left Side, Back of Cab/Under Sleeper	* DOOR TRIM, INTERIOR Black Handle	27/28 WHEELS & TIRES
15WDM - DEF TANK 10.6 US Gal (40L) Capacity, Frame Mounted Outside Left Rail, Back of Cab/Under Sleeper	* INSTRUMENT PANEL TRIM Black, Black Gauges with Black Bezels	* WHEEL SEALS, FRONT {International} Oil Lubricated, Includes Wheel Bearings
15LPR - FUEL/WATER SEPARATOR {Racor 6600} 12 VDC Electric Heater, Includes Pre-Heater, Fuel Heated with Fuel Blender Valve, with Sight Bowl, Includes Water-In-Fuel Sensor	* SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap	* WHEEL SEALS, REAR {International} Oil Lubricated, Includes Wheel Bearings
16 CAB	16GEG - GAUGE CLUSTER Premium Level; English with English Electronic Speedometer	27DVN - WHEELS, FRONT {Accuride 42644} DISC; 22.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
16030 - CAB Conventional, Day Cab	* GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for Fuel/DEF, DPF Level	28DVN - WHEELS, REAR {Accuride 42644} DUAL DISC; 22.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
* CLEARANCE/MARKER LIGHTS (5) Flush Mounted	* GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure	770249 5443 (02) 295/75R22.5 14-PR LR-G SINGLE FRONT RADIAL TIRES {Continental Tire ECOPLUS HS3+}
* COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window	* WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)	770249 5443 (04) 295/75R22.5 14-PR LR-G DUAL REAR RADIAL TIRES {Continental Tire ECOPLUS HS3+}
* CONSOLE, CENTER Includes Two Cup Holders and One Additional Storage Area	16HCS - GAUGE, TEMPERATURE, AMBIENT Sensor Wiring with Display Unit Mounted in Cluster	29 SPECIAL WHEELS
* COURTESY LIGHT (2) Driver and Passenger Door Mounted	16XJP - INSTRUMENT PANEL Wing Panel	29CAG - WHEEL COVER, REAR Aerodynamic, 22.5", Black
* DOME LIGHT, CAB Rectangular, Door and Instrument Panel Mounted Switch Activated, Timed Theater Dimming, Center Mounted, Integral to Console	16SNS - MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Black Heads and Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width	40 WARRANTY
* FLOOR COVERING Rubber, Black	NOTE: Mirror Dimensions are Rounded to the Nearest 0.5"	40125 - WARRANTY Standard for LT/RH Series, Effective with Vehicles Built January 2, 2016 or Later, CTS-2010A
* GLASS, ALL WINDOWS Tinted	- For U.S. Only	
* GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side		
* GRAB HANDLE, CAB INTERIOR (4) "B" Pillar and Door Mounted, Two Each Side		
* INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color		
* READING LIGHT, CAB Located in Overhead Console		
* STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door		

Refer To General Info for Metric Conversion Tables

**INTERNATIONAL®****RH****SERIES HEAVY DUTY****RH613 6x4****STANDARD EQUIPMENT****MODEL CODE: RH61F00****LIST PRICE:****\$256,348.00****01 FRAMES**

- * NOTE: APPLICATION AND COUNTRY RESTRICTION INFORMATION IS NOT SHOWN IN THE AVAILABLE EQUIPMENT SECTIONS. PLEASE REFER TO THE TOPS APPLICATION IN SALES TOOLS FOR THIS RESTRICTION INFORMATION.

01CBV - FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.125" x 3.580" x 0.312" (257.2mm x 90.9mm x 8.0mm); 367.4" (9333mm) Maximum OAL
01LRL - BUMPER, FRONT 3-Piece, Aerodynamic, Plastic, Molded Dark Gray
01616 - FRAME RAILS WITH TAPERED REAR
01WKJ - WHEELBASE RANGE 152" (385cm) Through and Including 185" (470cm)

02 AXLE, FRONT

02AUD - AXLE, FRONT NON-DRIVING {Hendrickson Steertek NXT} Wide Track, Fabricated Type, 12,350-lb Capacity

03A SUSPENSION, FRONT

03AHN - SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 12,350-lb Capacity, with Shock Absorbers
* SPRING PINS Rubber Bushings, Maintenance-Free

04 BRAKES

04092 - BRAKE SYSTEM, AIR Dual System for Tractor Applications
* BRAKE LINES Color and Size Coded Nylon
* BRAKE PRESSURE INDICATOR Low Air Pressure Warning Light and Audible Alarm
* DRAIN VALVE Manually Operated (On Wet Tank Only)
* GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster
* GLAD HANDS (2) One for Service and One for Emergency; Trailer Hoses from Cab
* HAND CONTROL VALVE, AIR with Self Return Handle, for Trailer Brakes, Mounted in Instrument Panel
* HOSE TENDER Back of Cab Mounted
* PARKING BRAKE CONTROL Yellow and Red Knobs, Located on Instrument Panel

04 BRAKES

* PARKING BRAKE VALVE Combination Valve for Tractor and Trailer
* QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for Forward Rear Axle
* TRACTOR PROTECTION VALVE
04AZS - AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Electronic Stability Program, with Automatic Traction Control
04XDP - BRAKES, FRONT {Meritor 16.5X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 5", 14,700-lb Capacity
04EXV - BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 SqIn
04LAG - SLACK ADJUSTERS, FRONT {Gunitite} Automatic
04XDE - BRAKES, REAR {Meritor 16.5X7 Q-PLUS LW} Air S-Cam Type, Fabricated Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 20,000-lb Capacity per Axle
04EXU - BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqIn Spring Brake
* BRAKE CHAMBERS, POSITION (2) Rear Parking; WITH TRUCK BRAKES: All 4x2, 4x4; WITH TRACTOR BRAKES: All 4x2, 4x4; 6x4 & 6x6 with Rear Tandem Axles Less Than 46,000-lb. or GVWR Less Than 54,000-lb.
* BRAKE CHAMBERS, POSITION (4) Rear Parking; WITH TRUCK BRAKES: All 6x4, 6x6; WITH TRACTOR BRAKES: 6x4 & 6x6 with Rear Tandem Axles 46,000-lb. or Greater or GVWR of 54,000-lb. or Greater
04LGG - SLACK ADJUSTERS, REAR {Gunitite} Automatic
04SPM - AIR COMPRESSOR {Bendix BA-921 Head Unload} 15.9 CFM
04EDM - AIR DRYER {Bendix AD-HF} with Heater, Includes Pressure Protection Circuits, Safety Valve, Integral Purge Tank, Governor Pressure Settings 110 psi Cut-In/130 psi Cut-Out, Integrated PuraGuard Coalescing Filtration
04VHW - AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Left Rail, Under Cab; Perpendicular to Rail

(CONT.)

05 STEERING

05PSM - STEERING GEAR {Sheppard HD94} Power
05710 - STEERING COLUMN Tilting and Telescoping
05CAW - STEERING WHEEL 4-Spoke; 18" Dia., Black

06 DRIVELINES

* END YOKES Half-Round, Easy Service (All)
* SLIP JOINT SPLINES Nylon-Coated
06DGX - DRIVELINE SYSTEM {Dana Spicer} Service Free SPL250 Main Driveline with SPL170 Interaxle Shaft, for 6x4

07 EXHAUST SYSTEM

07BLV - EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Short Horizontal Tail Pipe, Frame Mounted Right Side Back of Cab
07SDK - ENGINE COMPRESSION BRAKE by Jacobs; for N13/A26 Engines, with Selector Switch and On/Off Switch
07WDR - TAIL PIPE (1) Horizontal, Short

08 ELECTRICAL

08000 - ELECTRICAL SYSTEM 12-Volt, Standard Equipment
* DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab
* HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel
* HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever
* HORN, ELECTRIC Single
* PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light
* POWER SOURCE Cigar Type Receptacle with Cap, USB Port, Located in Instrument Panel
* STARTER SWITCH Electric, Key Operated
* TURN SIGNAL SWITCH Manual Cancelling with Lane Change Feature
* TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted
* WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever

Refer To General Info for Metric Conversion Tables

**INTERNATIONAL®****RH****SERIES HEAVY DUTY****RH613 6x4****STANDARD EQUIPMENT****MODEL CODE: RH61F00****08 ELECTRICAL****(CONT.)**

- * WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted
- * WIRING, CHASSIS Color Coded and Continuously Numbered
- 08GXJ - ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount
- 08XHL - BATTERY BOX Steel, 30" Wide, 2-4 Battery Capacity, Mounted Left Side Under Cab
- 08MSG - BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud
- 08RJW - CB RADIO Omit Power Feeds, Power Source and Wiring
- 08XAH - CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses
- 08TRG - COLLISION MITIGATION SYSTEM {Bendix Wingman Fusion} Adaptive Cruise, Enhanced Collision Mitigation, Multilane Auto & Stat Vehicle Braking, Stat Obj Alert, Roadway Depart Alert & Braking, Lane Depart Warning Switch & Spkrs, Ovrspd Alert & Action, Frt Radar & Camera, Drvr Display, Safety Direct Capable, Less Safety Direct Cable
- 08XMB - CONNECTOR, DASH, CENTER PANEL Cab Wiring for TMC RP1226 Vehicle Accessory Connector; Includes 14-pin Connector with Switched Power, Battery Power, Ignition Power, Ground & Body 250K Datalink, Connector Located Behind Instrument Panel Center Console
- 08WXB - HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position
- 08XPA - HEADLIGHTS LED, with Daytime Running Lights, Automatic Twilight Controlled
- 08WRB - HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on
- 08XHN - HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord

08 ELECTRICAL**(CONT.)**

- 08RPU - RADIO AM/FM/WB/SiriusXM/Clock/Bluetooth/USB Input/Auxiliary Input
- 08RMV - SPEAKERS (2) 6.5" Dual Cone Mounted in Doors
- 08WVG - STARTING MOTOR {Mitsubishi Electric Automotive America 105P} 12-Volt, with Soft-Start
- 08TPP - STOP, TURN, TAIL & B/U LIGHTS Multi-Function Lamp, with LED Lights for Stop, Turn, Tail and Backup Lights, Includes LED License Plate Light
- 08XHX - SWITCH, MARKER INTERRUPT for Marker Lights and Headlights, Located in Steering Wheel
- 08WPZ - TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights

09 FRONT END

- 09WAY - FRONT END Tilting, Fiberglass, with Three Piece Construction
 - * BUG SCREEN Front End; Mounted Behind Grille
 - * HOOD TILT ASSIST Includes Torsion Bar Spring System
- 09HAD - GRILLE Chrome
- 09AAB - LOGOS EXTERIOR Model Badges
- 09AAE - LOGOS EXTERIOR, ENGINE Badges

10 PAINT & MISCELLANEOUS

- 10AEU - INTELLIGENT FLEET CARE Telematics Device with Over the Air Programming; Includes Five Year Data Plan, Advanced Preventive Maintenance, Fleet Health Monitor Reporting and International 360
- 10HZN - FIFTH WHEEL, AIR SLIDE {Fontaine SL6NWB675012} 12" Slide, 6.75" Above Top of Frame, Left Hand Release
- 10WPR - MUD FLAP HOLDER Spring Loaded, Painted Black, with Red and White Reflective Tape, Less Flaps
- 10060 - PAINT SCHEMATIC, PT-1 Single Color, Design 100
 - * PAINT SCHEMATIC ID LETTERS "HW"
- 10761 - PAINT TYPE Base Coat/Clear Coat, 1-2 Tone

11 CLUTCH

- 11MHM - CLUTCH {Eaton Fuller 430MM} Maintenance Free, Self-Adjusting, 17" (430 mm) Dia Single Plate, Diaphragm Spring, Organic, 5-Spring Coaxial 254mm Damper with Pre-Damper, 2"-18 Tooth Spline, Pneumatic Push Type Control, 1850 lb-ft (2508 Nm) Torque Capacity

12 ENGINE

- 12BGA - ENGINE, DIESEL {International A26} EPA 2021, 410HP @ 1700 RPM, 1450 lb-ft Torque @ 900 RPM, 1800 RPM Governed Speed, 410 Peak HP (Max)
 - 12XBC - RADIATOR Aluminum, Welded, Down Flow, Front to Back System, 1325 SqIn, with 806 SqIn Charge Air Cooler
 - 12THJ - FAN DRIVE {Horton Drivemaster} Automatic On/Off Type, with Normally Closed Temperature Control
 - 12VBC - AIR CLEANER Single Element
 - * GAUGE, AIR CLEANER RESTRICTION Air Cleaner Mounted
 - 12703 - ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection
 - 12XBE - CRUISE CONTROL Predictive, Includes GPS Enhanced Cruise Control; Includes Module, Antenna and Wiring
 - 12WCX - HOSE CLAMPS, RADIATOR HOSES {Gates} Shrink Band Type
 - 12WYZ - RADIATOR DRAIN & FILL FITTING SPECIAL; To Vacuum Out or Fill the Cooling System from the Bottom of Radiator, for Use with Quick-Connect Radiator Drain Tool or Shop Coolant Evacuation-Fill System
- 13 TRANSMISSION**
- 13GYY - TRANSMISSION, MANUAL {Eaton Endurant EEO-14F112C} 12-Speed Fully Automated Manual, Aluminum Clutch Housing, Overdrive, Mechatronic Shift Controls, Pneumatic Clutch Actuation, Internal Lube Oil Pump, Hill Start Aid
 - 13WLW - TRANSMISSION OIL {EmGard 40W} Synthetic; 1 thru 21.99 Pints

Refer To General Info for Metric Conversion Tables



RH613 6x4

STANDARD EQUIPMENT

MODEL CODE: RH61F00

14A AXLE, REAR

- 14GVD - AXLE, REAR, TANDEM {Meritor MT-40-14X-3CFR} Single Reduction, Amboid Gearing in Rear-Rear Axle, 40,000-lb Capacity, .374"(9.5mm) Wall Housing Thickness, R Wheel Ends
- * RATIO: 2.47, 2.64, 2.79, 2.85, 3.08, 3.25, 3.36, 3.42, 3.55, 3.70, 3.90 OR 4.11
- * POWER DIVIDER LOCK Electric over Air Operated, Cab Control with Indicator Light

- 14WMJ - AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 50 thru 64.99 Pints

14B SUSPENSION, REAR

- 14UPZ - SUSPENSION, REAR, AIR, TANDEM {International} Ride Optimized Suspension (IROS), 40,000-lb Capacity, 52" Axle Spacing, 9.25" Ride Height, with Shock Absorbers

15 FUEL TANKS

- * FUEL LINE FITTINGS O-Ring Snap-On Quick-Connect Voss Fittings at Both Ends; Anchored to frame for Fuel Hoses
- 15SYK - FUEL TANK Top Draw, Non-Polished Aluminum, 26" Dia, 70 US Gal (265L), Mounted Left Side, Back of Cab/Under Sleeper
- 15WDM - DEF TANK 10.6 US Gal (40L) Capacity, Frame Mounted Outside Left Rail, Back of Cab/Under Sleeper
- 15LPR - FUEL/WATER SEPARATOR {Racor 6600} 12 VDC Electric Heater, Includes Pre-Heater, Fuel Heated with Fuel Blender Valve, with Sight Bowl, Includes Water-In-Fuel Sensor

16 CAB

- 16030 - CAB Conventional, Day Cab
- * CLEARANCE/MARKER LIGHTS (5) Flush Mounted
- * COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window
- * CONSOLE, CENTER Includes Two Cup Holders and One Additional Storage Area
- * COURTESY LIGHT (2) Driver and Passenger Door Mounted
- * DOME LIGHT, CAB Rectangular, Door and Instrument Panel Mounted Switch Activated, Timed Theater Dimming, Center Mounted, Integral to Console

16 CAB

(CONT.)

- * FLOOR COVERING Rubber, Black
- * GLASS, ALL WINDOWS Tinted
- * GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side
- * GRAB HANDLE, CAB INTERIOR (4) "B" Pillar and Door Mounted, Two Each Side
- * INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color
- * READING LIGHT, CAB Located in Overhead Console
- * STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door
- 16ZBS - ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab or Sleeper Cab
- 16BAM - AIR CONDITIONER with Integral Heater and Defroster
- * HOSE CLAMPS, HEATER HOSE {Mubea} Constant Tension Clamps
- 16VKB - CAB INTERIOR TRIM Classic, for Day Cab
- * DOOR TRIM, INTERIOR Black Handle
- * INSTRUMENT PANEL TRIM Black, Black Gauges with Black Bezels
- * SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap
- 16GEG - GAUGE CLUSTER Premium Level; English with English Electronic Speedometer
- * GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for Fuel/DEF, DPF Level
- * GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure
- * WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)

16 CAB

(CONT.)

- 16HCS - GAUGE, TEMPERATURE, AMBIENT Sensor Wiring with Display Unit Mounted in Cluster
 - 16XJP - INSTRUMENT PANEL Wing Panel
 - 16SNS - MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Black Heads and Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width
 - NOTE:** Mirror Dimensions are Rounded to the Nearest 0.5"
 - For U.S. Only
 - 16VVM - MONITOR, TIRE PRESSURE System Gives Warning that Tire Pressure is Below Set Pressure, Monitors Tire Pressure of Each Tire with Temperature Compensation, Data Displayed in the LCD of the Cluster, for 4x2, 6x4 and 6x2 Axle Configurations, Does Not Include Lift Axles or Spare Wheels
 - 16KAM - SEAT, DRIVER {National 2000 Model 295} Air Suspension, Intermediate Back, All Vinyl, 2 Arm Rests, Isolator, 7" Adjuster, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, 3-14 Degree Back Angle Adjust
 - 16REP - SEAT, PASSENGER {National 2000} Non Suspension, Intermediate Back, All Vinyl, 11 Degree Back Angle
 - 16WJU - WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature
- 27/28 WHEELS & TIRES**
- * WHEEL SEALS, FRONT {International} Oil Lubricated, Includes Wheel Bearings
 - * WHEEL SEALS, REAR {International} Oil Lubricated, Includes Wheel Bearings
 - 27DVN - WHEELS, FRONT {Accuride 42644} DISC; 22.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
 - 28DVN - WHEELS, REAR {Accuride 42644} DUAL DISC; 22.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

Refer To General Info for Metric Conversion Tables



INTERNATIONAL®

RH

SERIES HEAVY DUTY

RH613 6x4

STANDARD EQUIPMENT

MODEL CODE: RH61F00

27/28 WHEELS & TIRES (CONT.)

770249 5443 (02) 295/75R22.5

14-PR LR-G SINGLE FRONT

RADIAL TIRES {Continental

Tire ECOPLUS HS3+}

770249 5443 (08) 295/75R22.5

14-PR LR-G DUAL REAR RADIAL

TIRES {Continental Tire

ECOPLUS HS3+}

29 SPECIAL WHEELS

29CAG - WHEEL COVER, REAR

Aerodynamic, 22.5", Black

40 WARRANTY

40125 - WARRANTY Standard for

LT/RH Series, Effective with

Vehicles Built January 2,

2016 or Later, CTS-2010A

Refer To General Info for Metric Conversion Tables

INTERNATIONAL® RH SERIES SECTION 740 - STANDARD EQUIPMENT PRICES EFFECTIVE 04/01/2022

PLH-284 REVISION NO. 204A

PAGE 740-9

SUBJECT TO CHANGE WITHOUT NOTICE

Printed in the United States of America

All Taxes Extra, when Applicable