

Variable diameter high pressure pipe plug

Made of imported rubber and polymer aramid material, it has the characteristics of sustainable expansion. The variable diameter airbag adopts a mechanical die-casting integrated vulcanization mode. The rubber density is high and has a high pressure of 0.25mpa. The airbag can block pipes of different specifications separately. For example, DN300-600mm can block all pipes from 300-600 respectively. Convenient, fast and safe.



1. Prohibit the use of overpressure
2. Prohibit people from approaching when inflating
3. The inflation pressure on flat ground must not exceed 0.05MPa
4. Pay attention to traction airbag
5. Pay attention to clean up the debris in the pipeline before inserting the airbag
6. Pay attention to prevent poisonous gas in the pipeline
7. Pay attention to shading and store at room temperature



Flexible Various Diameter Pipe Plugs

Various Diameter

Pipe Plugs Specifications						
US Pipe Diameter (in)	Inflation (psi)	Water Depth (ft)	Initial Diameter (in)	Length (in)	Weight (lbs)	Cost
6"-12"	20	30'	5.31"	19.68"	6.61	\$765.00
8"-15"	20	30'	7.08"	23.62"	8.81	\$1,530.00
8"-21"	20	30'	7.08"	27.55"	11.02	\$1,806.00
12"-24"	15	25'	11.08"	29.52"	22.04	\$1,944.00
15"-28"	15	25'	14.96"	35.43"	39.68	\$3,126.00
21"-36"	15	15'	18.11"	41.33"	55.11	\$4,305.00

Shipping and handling will be added on an individual purchase order

Manufacturer's Warranty Included