

 Product
 Approx. Weight
 List Price

 DX255LC-7-US20
 25,300.00 KG
 249,359.11 USD

DX255LC-7 BASE MACHINE W/O BUCKET
19' 4" (5.9 m) MONO BOOM
9' 10" (3.0 m) ARM
31.5" (800 mm) TRIPLE GROUSER SHOES
12,125 LBS (5.5 METRIC TON) COUNTERWEIGHT
ONE/TWO WAY AUXILIARY HYDRAULIC PIPING TO END OF ARM

OPTIONAL EQUIPMENT - Factory Installed (29)			
Option	CODE	Description	List Price
TRACK SHOE	700	27.6" (700 mm) TRIPLE GROUSER SHOE	-1,650.00 USD
TRACK SHOE	900	35.4" (900 mm) TRIPLE GROUSER SHOE	1,675.00 USD
Water Separator	WIH	WATER SEPARATOR WITH HEATER	300.00 USD
BOOM FLOATING PIPING	BFL	BOOM FLOATING PIPING	1,100.00 USD
BREAKER FILTER	BRF	BREAKER FILTER	425.00 USD
CLAMSHELL PIPING	CLA	CLAMSHELL	300.00 USD
LEVER PATTERN CHANGE	LEV	LEVER PATTERN CHANGE	200.00 USD
LOCK VALVE	LBA	BOOM & ARM LOCK VALVE	1,700.00 USD
LOCK VALVE	LOB	BOOM LOCK VALVE	1,150.00 USD
ROTATING PIPING(PERO)	PER	ROTATING PIPING (PERO)	3,180.50 USD
ONE & TWO WAY PIPING	OEP	ONE & TWO WAY PILOT PIPING	5,210.88 USD
ONE & TWO WAY PIPING	PE3	TWO WAY WITH PEDAL	6,360.88 USD
STRAIGHT TRAVEL	STT	STRAIGHT TRAVEL	300.00 USD
HEATING & COOLING SEAT	HCS	Heating & Cooling Seat	725.00 USD
MICROPHONE	MIC	Microphone	1,000.00 USD
RAIN SHIELD	RAI	CAB RAIN SHIELD	175.00 USD
BOOM LAMP TYPE	BLE	LED Type Boom Lamp	575.00 USD
CAMERA	AVC	AROUND VIEW CAMERA	4,250.00 USD



CAMERA	SRC	SIDE AND REAR VIEW CAMERA	1,375.00 USD
CABIN FRONT GUARD	FUL	UPPER AND LOWER FRONT WINDOW GUARD	475.00 USD
CABIN FRONT GUARD	LOW	Lower Guard Only	275.00 USD
FOGS GUARD	FOG	FOG (FALLING OBJECT GUARD)	2,600.00 USD
ADDITIONAL WORK LAMP	6LE	6 ADDITIONAL WORKING LAMP(LED)	862.50 USD
ADDITIONAL WORK LAMP	4LE	4 ADDITIONAL WORKING LAMP(LED)	575.00 USD
OVERLOAD WARNING DEVICE	OWD	OVERLOAD WARNING DEVICE	100.00 USD
ROTATING BEACON	ROB	ROTATING BEACON	200.00 USD
AIR COMPRESSOR	ACO	AIR COMPRESSOR	2,650.00 USD
FUEL FILLER PUMP	FIL	FUEL FILLER PUMP	375.00 USD
SHOE CASE	SHC	Shoe Case	75.00 USD

Attachment	Description	Approx. Weight	List Price
5000033	TRIMBLE EARTHWORKS 2D MACHINE GUIDANCE; INDICATE KIT; w/ INSTALL, CALIBRATION	50.00	24,000.00 USD
AT250-072	1.13 CU. YD. 72" ANGLE TILT DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	2,200.00	14,624.56 USD
DC250-048	0.97 CU. YD. 48" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	1,703.00	4,868.15 USD
DC250-060	1.22 CU. YD. 60" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	2,117.00	5,764.34 USD
HD25-024	0.64 CU. YD. 24" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,726.00	8,857.90 USD
HD25-030	0.87 CU. YD. 30" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,897.00	7,504.95 USD
HD25-036	1.11 CU. YD. 36" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	2,099.00	8,143.88 USD
HD25-042	1.36 CU. YD. 42" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	2,289.00	8,717.10 USD
HD25-048	1.60 CU. YD. 48" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	2,504.00	9,252.55 USD
HDC250-066	2.16 CU. YD. 66" HD DITCH CLEAN UP BUCKET (WITH BOLT-ON EDGE)	3,022.00	12,126.84 USD
HDC250-072	2.58 CU. YD. 72" HD DITCH CLEAN UP BUCKET (WITH BOLT-ON EDGE)	3,206.00	10,253.41 USD
HT-25DM3T	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH BUCKET	1,350.00	13,018.92 USD



HT-25DM4T	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH BUCKET	1,350.00	13,018.92 USD
HT-25QC3T	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH COUPLER	1,350.00	13,376.57 USD
HT-25QC4T	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH COUPLER	1,350.00	13,376.57 USD
PL-25DM3T	PRO LINK THUMB; HYDRAULIC; 3 TINE; FOR 30"; 48" BUCKET; USED WITH BUCKET	1.00	10,381.14 USD
PL-25DM4T	PRO LINK THUMB; HYDRAULIC; 4 TINE; FOR 36"; 42" BUCKET; USED WITH BUCKET	1.00	10,381.14 USD
PL-25QC3T	PRO LINK THUMB; HYDRAULIC; 3 TINE; FOR 30"; 48" BUCKET; USED WITH COUPLER	1.00	10,677.74 USD
PL-25QC4T	PRO LINK THUMB; HYDRAULIC; 4 TINE; FOR 36"; 42" BUCKET; USED WITH COUPLER	1.00	10,677.74 USD
QC-80H1G3-432	HYD. QUICK COUPLER (INCLUDES SOFT PINS, JUMPER HOSE ONLY) FOR DX255	721.00	8,972.27 USD
SD25-024	0.64 CU. YD. 24" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,850.00	9,957.06 USD
SD25-030	0.87 CU. YD. 30" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	2,102.00	9,286.11 USD
SD25-036	1.11 CU. YD. 36" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	2,285.00	12,139.14 USD
SD25-042	1.36 CU. YD. 42" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	2,477.00	12,705.99 USD
SD25-048	1.60 CU. YD. 48" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	2,713.00	13,796.50 USD

STANDARD EQUIPMENT FOR BASE MACHINE (7)		
Item	Description	
Engine	Doosan DL06V; 5.9L 4-Cycle Water Cooled, Turbocharged and Intercooled T4f Emission Compliant with EGR Electronically Controlled Common Rail Direct Injected T4f Emissions: Diesel Oxidation Catalyst + DPF + Selective Catalytic Reduction with Ammonia Oxidation Catalytic 189 hp (141 kW) @ 1900 rpm (SAE J1995) Gross Flywheel Horsepower 185 HP(SAE J1349) Net @ 1900 rpm Displacement: 359 in3 (5890cc), 4 Cylinder Bore 3.94 in (100mm) Diameter x 4.92 in (125mm) Stroke Torque: 593 ft. lbs (82 kgf-m) @ 1,400 rpm High Idle 2000 ± 50 rpm, Low Idle 800 ± 50 rpm Auto Idle System Auto Shut Down Equipped with the Fuel Pre-filter with Water Separator Radiator Reserve Tank Large Capacity Double Element Air Cleaner with Evacuate Electronic Engine Speed Control Engine Derate and Shutdown if failure in Emission Control System Engine Overheat and Low Oil Pressure Prevention System	
	Pilot Operated Control Valves, (9) Spools Main Pump: Tandem Variable Axial Piston Type, Flow: 2 x [58 gpm (219 Lpm)]; Pressure Setting 4978 psi normal / 5263 psi boost Pilot Circuit, Gear Type Pump; Flow: 7 gpm (26 Lpm) Swing Motor, Axial Piston Type driving a 2-stage planetary gearbox to maximize torque	



Swing Maximum Speed: 10.0 RPM Fine Swing Control Maximum Swing Torque 71,462 lbf-ft. (9,880 kgf-m) Hydraulics Spring Set, Hydraulic-released Brakes Travel Motors: 2 x Axial Piston Type (High, Low, Auto) Travel Speed (High/Low): 3.5 mph/1.9 mph Maximum Tractive Force 62,832 lbf. (28,500 kgf) in low speed In-Shoe Design, Oil Disc Parking Brake One way/two way Auxiliary Hydraulics with 2-pump flow Smart Hydraulic Logic to prioritize flow to hydraulic attachments like a molcher or a grinder Working Mode for Tilt-Rotator Steel, All Weather Sound Suppressed ROPS Type Fully Automatic Heater and Air Conditioner with Radian Energy Photo Sensor 12V and 24V Power Sockets Door Locks Front Windshield Panto Wiper with Washer 8" Multi-function Color LCD Touch Screen Monitor Aerial, Side & Rear View Camera with dedicated LCD display Digital Blutetooth Audio Broadcasting MP3 Radio with Cell Phone integration Audio Control Panel On/Off Switch, Control Volume, Channel Select Switches: **Engine Speed Control Dial** Jog Switch for monitor display control Auxiliary Mode Switch Engine Emergency Stop Switch Work Light Switch Travel Speed Selector Switch Breaker, Power-up, Shear Switch Intelligent Floating Boom (optional) Engine After Treatment System Switch Wiper Control Panel Safety Lock Lever Ergonomic Leatherlike Operator Seat: 3-Stage Climate Controlled seat (optional) Cab 2-Stage Heated Seat (standard) Air Suspension with Seat Belt (2" Wide) Adjustable bottom cushion Lumbar Support Adjustment Adjustable Headrest Reclining, Height Adjustable Adjustable Arm Rests Sliding Control Console Height Adjustable Panels Pull Up Type Front Window Removable Lower Front Window with Storage Behind Seat Sliding Side Windows Front Window Air Defroster Travel Pedals with Hand Levers **Emergency Exit Glass Breaking Tool Quick Coupler Switch** Joystick Lever with 3 Switches, Two Button and One Rotate Front and Rear Cup Holders Room Light Serial Communication Port for Laptop PC Interface (DMS) Viscous Cab Mounts Sun Screens for Top Hatch, Front Windshield and Rear Window Advanced Mechatronics with Power Mode Control System to maximize machine efficiency and productivity Power Mode Select Button (P+,P,S,E) Work Mode Selector Button (Excavation, Lifting, Breaker and Shear) Electronic Power Optimizing System Cross Sensing Pump Control Machine Status Display with Integrated Self Diagnostics System Adjustable LCD Color Display

Auto Idle Control System plus One Touch Deceleration Button on Joystick



Electrical/Electronic Control System	Engine Speed Control Dial Power Boost Control Button on Joystick Limp Home Mode Control Switch Proximity Alarm Warning System Proportional control for auxiliary hydraulics via roll switch on both joysticks Adjustable Auxiliary Flow and Pressure up to 10 presets Alternator: 24 V, 100 amp Batteries: (2) 12 V, 150AmpH, 900CCA Starter: 24 V x 6 KW Engine Emergency Stop Switch accessible from ground level Panto Wiper to cover the entire front windshield window LED Lights: Working Light (2) Machine, (2) Boom and 3 w/Rear View Cameras Smart Ignition Switch Key for remote control of engine start/stop and door lock/unlock Electric Horn Hour Meter
Display Monitor and Warnings	Main Warning Lamp Warning Symbol Indicator for: Battery, Engine oil pressure, Coolant overheated, Engine, Stop engine, Low fuel level, Hydraulic oil temp, Fuel System, Air cleaner clogged, Machine lift overload, Quick Coupler, Regen request, Low DEF level, Problem in SCR, VBO angle sensor failure, VBO joystick pressure sensor failure, EPPR valve failure, AGS, clogged Fuel filter, Ultrasonic sensor, Engine RPM and starting restriction or TMS failure, Coolant level, Seat belt, No smart key, Failed to detect smart key, Low battery smart key, DEF pressure, Hydraulic return filter clogged, Regen prohibited, Regeneration active, Manual regen, GPS antenna failure, GSM antenna failure, Satelite antenna failure, Check machine, Stop engine Digital Clock Alarm Buzzer for: Engine Oil Pressure Coolant Temperature Electronic Monitor for: Engine Coolant Temperature Gauge Fuel Gauge Hydraulic Oil Temperature Gauge DEF (AdBlue®) Level Multi-function Touch Screen Display for: Funcion Symbol Indicator (Power Boost, Auxiliary Hydraulic Pedal/Joystick Selector, Travel Speed, Work Light, Intelligent Floating Boom, ISO/BHL Pattern Control, Fine Swing Indicator Display (USB, Auto Shutdown, ACC, Auto Warm Up, Joystic One-touch, VBO Limp Home Mode, Engine Preheat, EPOS/ECU/EPOS-ECU, Reverse Fan On, Mirror Heater, Bluetooth) Favorite Button Indicator Main Information Selector Button (Reset Trip, Trip Info, Soot Level, PM Service Info) Main Information Indicator Auxiliary Hydraulics Selector Button (Unidirectional-Hammer or Bi-directional-Shear) Auxiliary Hydraulics Selector Button (Unidirectional-Hammer or Bi-directional-Shear) Auto Idle Indicator Menu Selector Button
Undercarriage	Track Guards and Chains with Adjusters Track Rollers: (2) Upper, (10) Lower Each Side Triple Grouser Shoes, 51 Each Side
Other	Joystick Pattern Change Valve Centralized Lube Points Large Access Handrail to upper deck Steel Casted Lift Bracket integrated with Idler Linkage Punched Metal Anti-slip Plates Engine Restart Prevention System Manuals, Parts and Operator's Ultra-hard Wear-resistant Disc on both sides of bucket arm end Vandalism Protection (All panels and fill points lockable) Telematics: 3 Yr Free Cellular Subscription - 3.0 Global (Cell Only)