

| PACKAGE A | ARRANGEMENT | (1) |
|-----------|-------------|-----|
|-----------|-------------|-----|

 Product
 Approx. Weight
 List Price

 DX300LC-7-US20
 32,600.00 KG
 289,561.65 USD

DX300LC-7 BASE MACHINE W/O BUCKET
20' 6" (6.245 m) MONO BOOM
10' 2" (3.1 m) ARM
31.5" (800 mm) TRIPLE GROUSER SHOES
13,890 LBS (6.3 METRIC TON) COUNTERWEIGHT
ONE/TWO WAY AUXILIARY HYDRAULIC PIPING TO END OF ARM

| OPTIONAL EQUIPMENT - Factory Installed (32) | | | |
|---|------|------------------------------|--------------|
| Option | CODE | Description | List Price |
| MICROPHONE | MIC | Microphone | 1,050.00 USD |
| RAIN SHIELD | RAI | CAB RAIN SHIELD | 175.00 USD |
| ENGINE COOLANT HEATER | 110 | 110V Plug Heater | 240.00 USD |
| ENGINE COOLANT HEATER | 220 | 220V Plug Heater | 240.00 USD |
| PRE CLEANER | DRY | Dry Type Pre Cleaner | 400.00 USD |
| PRE CLEANER | OWC | Oil Washed Pre Cleaner | 1,725.00 USD |
| BOOM FLOATING PIPING | BFL | Boom Floating Piping | 1,350.00 USD |
| BREAKER FILTER | BRF | Breaker Filter | 450.00 USD |
| LEVER PATTERN CHANGE | LEV | Lever Pattern Change | 200.00 USD |
| LOCK VALVE | LBA | Boom & Arm Lock Valve | 1,800.00 USD |
| LOCK VALVE | LOB | Boom Lock Valve | 1,200.00 USD |
| ROTATING PIPING(PERO) | PER | Tilt/Rotationg Piping (PERO) | 3,350.50 USD |
| ONE & TWO WAY PIPING | PE3 | One/Two Way with Pedal | 6,360.88 USD |
| STRAIGHT TRAVEL | STT | Straight Travel Pedal | 300.00 USD |
| AIR COMPRESSOR | ACO | Air Compressor | 3,710.00 USD |
| AUTO GREASING UNIT | AGU | Auto Greasing Unit | 6,980.00 USD |
| SIDE PROTECTOR & CATWALK | PRO | Side Protector | 1,675.00 USD |
| FUEL FILLER PUMP | FIL | Fuel Filler Pump | 375.00 USD |



| SHOE CASE | SHC | Shoe Case | 75.00 USD |
|----------------------|-----|----------------------------------|---------------|
| BODY LAMP TYPE | HAL | Halogen Type Lamps | 150.00 USD |
| BODY LAMP TYPE | LED | LED Type Lamps | 1,025.00 USD |
| CAMERA | AVC | Around View Camera | 4,250.00 USD |
| CAMERA | SRC | Side & Rear View Camera | 1,375.00 USD |
| CABIN FRONT GUARD | FUL | Upper and Lower Guard | 500.00 USD |
| FOGS GUARD | FOG | Falling Object Guarding | 2,725.00 USD |
| ADDITIONAL WORK LAMP | 6LE | 6 Additional Working Lamps (LED) | 862.50 USD |
| ADDITIONAL WORK LAMP | 4LE | 4 Additiona Working Lamps (LED) | 575.00 USD |
| ROTATING BEACON | ROB | Rotating Beacon | 200.00 USD |
| TRACK SHOE | 600 | 600mm TG Shoe | -3,500.00 USD |
| TRACK SHOE | 60D | 600mm Double Grouser Shoe | -3,500.00 USD |
| TRACK SHOE | 700 | 700mm TG Shoe | -1,750.00 USD |
| TRACK SHOE | 900 | 35.4" (900 mm) TG Shoe | 2,650.00 USD |

| Attachments - Dealer Installed (19) | | | |
|-------------------------------------|---|----------------|---------------|
| Attachment | Description | Approx. Weight | List Price |
| 5000033 | TRIMBLE EARTHWORKS 2D MACHINE GUIDANCE; INDICATE KIT; w/ INSTALL, CALIBRATION | 50.00 | 24,000.00 USD |
| DC300-060 | 1.28 CU. YD. 60" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE) | 2,117.00 | 5,764.34 USD |
| DC300-072 | 1.55 CU. YD. 72" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE) | 2,496.00 | 6,684.28 USD |
| HD30-036 | 1.11 CU. YD. 36" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS) | 0.00 | 8,143.88 USD |
| HD30-042 | 1.36 CU. YD. 42" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS) | 2,289.00 | 8,717.10 USD |
| HD30-048 | 1.60 CU. YD. 48" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS) | 2,504.00 | 7,333.19 USD |
| HD30-054 | 1.85 CU. YD. 54" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS) | 2,676.00 | 9,684.57 USD |
| HD30-060 | 2.09 CU. YD. 60" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS) | 2,884.00 | 13,787.66 USD |
| HDC300-072 | 2.58 CU. YD. 72" HD DITCH CLEAN UP BUCKET (WITH BOLT-ON EDGE) | 3,206.00 | 12,531.57 USD |



| HT-30DM3T | MAIN PIN THUMB; HYDRAULIC; 3 TINE; FOR 48"; 54" BUCKET; USED WITH BUCKET | 1.00 | 14,151.64 USD |
|---------------|--|----------|---------------|
| HT-30DM4T | MAIN PIN THUMB; HYDRAULIC; 4 TINE; FOR 60" BUCKET; USED WITH BUCKET | 1.00 | 13,894.82 USD |
| HT-30QC3T | HYD. MAIN PIN THUMB; 3 TINE; FOR 48"; 54" BUCKET; USED WITH COUPLER | 1.00 | 14,311.88 USD |
| HT-30QC4T | HYD. MAIN PIN THUMB; 4 TINE; FOR 60" BUCKET; USED WITH COUPLER | 1.00 | 14,311.88 USD |
| QC-90H1G3-320 | HYD. QUICK COUPLER (INCLUDES SOFT PINS, JUMPER HOSE ONLY) FOR DX300 | 930.00 | 9,883.27 USD |
| SD30-036 | 1.11 CU. YD. 36" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS) | 2,285.00 | 10,031.29 USD |
| SD30-042 | 1.36 CU. YD. 42" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS) | 2,477.00 | 10,719.15 USD |
| SD30-048 | 1.60 CU. YD. 48" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS) | 2,713.00 | 13,350.76 USD |
| SD30-054 | 1.85 CU. YD. 54" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS) | 2,893.00 | 13,614.03 USD |
| SD30-060 | 2.09 CU. YD. 60" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS) | 3,129.00 | 13,134.23 USD |

| Item | Description | |
|------------|--|--|
| Engine | Doosan DL08V; 7.6L Wastegate Turbocharged and Intercooled T4f Emission Compliant Electronically Controlled Common Rail Direct Injected T4f Emissions: Diesel Oxidation Catalyst + Cooled EGR + Selective Catalytic Reduction with Diesel Exhaust Fluid 271 hp (202 kW) @ 1800 rpm (SAE J1995) Gross Flywheel Horsepower 199 HP(SAE J1349) Net @ 1800 rpm Displacement: 466 in 3 (7,640cc), 6 Cylinder Bore 4.25 in (108mm) Diameter x 5.47 in (139mm) Stroke Torque: 940 ft. lbs (130 kgf-m) @ 1,400 rpm High Idle 1900 ± 25 rpm, Low Idle 800 ± 10 rpm Auto Idle System Auto Shut Down Equipped with the Fuel Pre-filter with Water Separator Radiator Reserve Tank Large Capacity Double Element Air Cleaner with Evacuate Electronic Engine Speed Control Engine Derate and Shutdown if failure in Emission Control System Engine Overheat and Low Oil Pressure Prevention System | |
| Hydraulics | Pilot Operated Control Valves, (9) Spools Main Pump: Tandem Variable Axial Piston Type, Flow: 2 x 66 gpm; Pressure Setting 4978 psi normal 5263 psi boost Pilot Circuit, Gear Type Pump; Flow: 7 gpm (26 Lpm) Swing Motor, Axial Piston Type driving a 2-stage planetary gearbox to maximize torque Swing Maximum Speed: 9.7 RPM Fine Swing Control Maximum Swing Torque 87,787 lbf-ft. (12,137 kgf-m) Spring Set, Hydraulic-released Brakes Travel Motors: 2 x Axial Piston Type (High, Low, Auto) Travel Speed (High/Low): 3.4 mph/2.0 mph Maximum Tractive Force 77,162 lbf. (35,000 kgf) in low speed In-Shoe Design, Oil Disc Parking Brake One way/two way Auxiliary Hydraulics with 2-pump flow | |



Smart Hydraulic Logic to prioritize flow to hydraulic attachments like a molcher or a grinder Working Mode for Tilt-Rotator Steel, All Weather Sound Suppressed ROPS Type Fully Automatic Heater and Air Conditioner with Radian Energy Photo Sensor 12V and 24V Power Sockets Door Locks Front Windshield Panto Wiper with Washer 8" Multi-function Color LCD Touch Screen Monitor Aerial, Side & Rear View Camera with dedicated LCD display Digital Blutetooth Audio Broadcasting MP3 Radio with Cell Phone integration Audio Control Panel On/Off Switch, Control Volume, Channel Select Switches: **Engine Speed Control Dial** Jog Switch for monitor display control **Auxiliary Mode Switch** Engine Emergency Stop Switch Work Light Switch Travel Speed Selector Switch Breaker, Power-up, Shear Switch Intelligent Floating Boom (optional) Engine After Treatment System Switch Wiper Control Panel Safety Lock Lever Ergonomic Leatherlike Operator Seat: 3-Stage Climate Controlled seat (optional) Cab 2-Stage Heated Seat (standard) Air Suspension with Seat Belt (2" Wide) Adjustable bottom cushion Lumbar Support Adjustment Adjustable Headrest Reclining, Height Adjustable Adjustable Arm Rests Sliding Control Console Height Adjustable Panels Skylight Pull Up Type Front Window Removable Lower Front Window with Storage Behind Seat Sliding Side Windows Front Window Air Defroster Travel Pedals with Hand Levers **Emergency Exit Glass Breaking Tool** Quick Coupler Switch Joystick Lever with 3 Switches, Two Button and One Rotate Front and Rear Cup Holders Room Light Serial Communication Port for Laptop PC Interface (DMS) Viscous Cab Mounts Sun Screens for Top Hatch, Front Windshield and Rear Window Advanced Mechatronics with Power Mode Control System to maximize machine efficiency and productivity Power Mode Select Button (P+.P.S.E) Work Mode Selector Button (Excavation, Lifting, Breaker and Shear) Electronic Power Optimizing System Cross Sensing Pump Control Machine Status Display with Integrated Self Diagnostics System Adjustable LCD Color Display Auto Idle Control System plus One Touch Deceleration Button on Joystick **Engine Speed Control Dial** Power Boost Control Button on Jovstick Electrical/Electronic Control Limp Home Mode Control Switch System Proximity Alarm Warning System Proportional control for auxiliary hydraulics via roll switch on both joysticks Adjustable Auxiliary Flow and Pressure up to 10 presets Alternator: 24 V, 80 amp Batteries: (2) 12 V, 150AmpH, 950CCA

Starter: 24 V x 6 KW



| | Engine Emergency Stop Switch accessible from ground level Panto Wiper to cover the entire front windshield window LED Lights: Working Light (2) Machine, (2) Boom Smart Ignition Switch Key for remote control of engine start/stop and door lock/unlock Electric Horn Hour Meter |
|------------------------------|--|
| Display Monitor and Warnings | Main Warning Lamp Warning Symbol Indicator for: Battery, Engine oil pressure, Coolant overheated, Engine, Stop engine, Low fuel level, Hydraulic oil temp, Fuel System, Air cleaner clogged, Machine lift overload, Quick Coupler, Regen request, Low DEF level, Problem in SCR, VBO angle sensor failure, VBO joystick pressure sensor failure, EPPR valve failure, AGS, clogged Fuel filter, Ultrasonic sensor, Engine RPM and starting restriction or TMS failure, Coolant level, Seat belt, No smart key, Failed to detect smart key, Low battery smart key, DEF pressure, Hydraulic return filter clogged, Regen prohibited, Regeneration active, Manual regen, GPS antenna failure, GSM antenna failure, Satelite antenna failure, Check machine, Stop engine Digital Clock Alarm Buzzer for: Engine Oil Pressure Coolant Temperature Electronic Monitor for: Engine Coolant Temperature Gauge Fuel Gauge Hydraulic Oil Temperature Gauge DEF (AdBlue®) Level Multi-function Touch Screen Display for: Funcion Symbol Indicator (Power Boost, Auxiliary Hydraulic Pedal/Joystick Selector, Travel Speed, Work Light, Intelligent Floating Boom, ISO/BHL Pattern Control, Fine Swing Indicator Display (USB, Auto Shutdown, ACC, Auto Warm Up, Joystic One-touch, VBO Limp Home Mode, Engine Preheat, EPOS/ECU/EPOS-ECU, Reverse Fan On, Mirror Heater, Bluetooth) Favorite Button Indicator Main Information Selector Button (Reset Trip, Trip Info, Soot Level, PM Service Info) Main Information Indicator Power Mode Selector Button Indicator (Power+, Power, Standard, Economy) Power Mode Selector Button Indicator (Power+, Power, Standard, Economy) Power Mode Indicator Auxiliary Hydraulics Selector Button (Unidirectional-Hammer or Bi-directional-Shear) Autol Idle Indicator Menu Selector Button |
| Undercarriage | Track Guards and Chains with Adjusters Track Rollers: (2) Upper, (9) Lower Each Side Triple Grouser Shoes, 48 Each Side |
| Other | Joystick Pattern Change Valve Centralized Lube Points Large Access Handrail to upper deck Steel Casted Lift Bracket integrated with Idler Linkage Punched Metal Anti-slip Plates Engine Restart Prevention System Manuals, Parts and Operator's Ultra-hard Wear-resistant Disc on both sides of bucket arm end Vandalism Protection (All panels and fill points lockable) Telematics: 3 Yr Free Cellular Subscription - 3.0 Global (Cell Only) |