

**PACKAGE ARRANGEMENT (1)**

Product	Approx. Weight	List Price
DX800LC-7-US20	80,000.00 KG	797,580.61 USD

DX800LC-7 BASE MACHINE W/O BUCKET  
 25' 3" (7.7 M) BOOM  
 11' 8" (3.55 M) ARM  
 35.4" (900 mm) DOUBLE GROUSER SHOES  
 23,589 LBS (10.7 METRIC TON) COUNTERWEIGHT  
 ONE AND TWO WAY AUXILIARY PIPING TO END OF THE ARM WITH ONE WAY FLOW

**OPTIONAL EQUIPMENT - Factory Installed (17)**

Option	CODE	Description	List Price
REMOVAL COUNTERWEIGHT	RCW	REMOVABLE COUNTERWEIGHT	27,705.18 USD
RAIN SHIELD	RAI	CAB RAIN SHIELD	283.06 USD
ROTATING PIPING(PERO)	PER	ROTATE CIRCUIT PIPING	6,360.88 USD
ONE & TWO WAY PIPING	PE3	ONE & TWO WAY PILOT PIPING	6,360.88 USD
STRAIGHT TRAVEL	STT	STRAIGHT TRAVEL	763.31 USD
AIR COMPRESSOR	ACO	AIR COMPRESSOR	3,710.52 USD
AUTO GREASING UNIT	AGU	AUTO GREASING SYSTEM	5,830.81 USD
FUEL FILLER PUMP	FIL	FUEL FILLER PUMP	406.04 USD
CAMERA	AVC	AROUND VIEW CAMERA	3,741.70 USD
CABIN FRONT GUARD	FUL	UPPER AND LOWER FRONT WINDOW GUARD	1,186.95 USD
FOGS GUARD	FOG	FOG (FALLING OBJECT GUARD)	2,756.38 USD
ADDITIONAL WORK LAMP	6LE	6 ADDITIONAL WORKING LAMPS (LED)	1,662.98 USD
ADDITIONAL WORK LAMP	2LE	2 ADDITIONAL WORKING LAMPS (LED)	935.42 USD
LOWER WIPER	LOW	LOWER WIPER	254.43 USD
ROTATING BEACON	ROB	ROTATING BEACON	466.46 USD
TRACK SHOE	65D	25.6" (650 MM) DOUBLE GROUSER SHOE	-2,667.00 USD
TRACK SHOE	75D	29.5" (750 MM) DOUBLE GROUSER SHOE	-1,333.00 USD

**Attachments - Dealer Installed (10)**

Attachment	Description	Approx. Weight	List Price
HD80-048	3.21 CU. YD. 48" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	6,795.00	23,291.70 USD
HD80-054	3.73 CU. YD. 54" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	7,550.00	25,273.57 USD
HD80-060	4.10 CU. YD. 60" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	8,150.00	26,336.09 USD
HD80-066	4.62 CU. YD. 66" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	8,650.00	27,480.43 USD
HD80-072	5.14 CU. YD. 72" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	9,050.00	29,872.31 USD
SD80-048	3.21 CU. YD. 48" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	7,995.00	28,072.56 USD
SD80-054	3.73 CU. YD. 54" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	8,550.00	30,384.59 USD
SD80-060	4.10 CU. YD. 60" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	9,150.00	31,686.69 USD
SD80-066	4.62 CU. YD. 66" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	9,650.00	33,088.13 USD
SD80-072	5.14 CU. YD. 72" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	10,150.00	35,903.66 USD

**STANDARD EQUIPMENT FOR BASE MACHINE (7)**

Item	Description
Engine	<p>"Perkins 2506J: Turbocharged Water Cooled Mechanical Electronic Unit Injector System (MEUI)  T4: Cooled Exhaust Gas Recirculation + Diesel Oxidation Catalyst + Diesel Particulate Filter + Selective Catalytic Reduction with Diesel Exhaust Fluid  539HP (ISO 14396) Gross Flywheel Horsepower @ 2,100 rpm  Displacement: 928 cu.in., 6 Cylinder  Bore 137mm Diameter x 171mm Stroke  Torque: 1821ft. lbs @ 1,400 rpm  High Idle 1900 <math>\frac{3}{4}</math> 10rpm, Low Idle 900 <math>\frac{3}{4}</math> 10 rpm  Auto Idle System  Equipped with the Fuel Pre-filter with Water Separator  Radiator Reserve Tank  Large Capacity Double Element Air Cleaner with Evacuate  Electronic Engine Speed Control  Engine Overheat and Low Oil Pressure Prevention System"</p>
Hydraulic	<p>"Pilot Operated Control Valves, (10) Spools  Main Pump: Tandem Axial Piston Type, Pressure Setting 4975psi  2 X 133 gpm  Pilot Circuit, Gear Type Pump  Swing Motor, Axial Piston Type  Swing Speed Control up to 7.5 RPM  Maximum Swing Torque 228,563 ft.lbs.  Spring Set, Hydraulic-released Brakes  Travel Motor: Axial Piston Type (High, Low, Auto)  Travel Speed (High/Low): 3.0 mph / 1.9 mph  Maximum Tractive Force 155793 ft.lbs. in low speed  In-Shoe Design, Oil Disc Parking Brake"</p>

	<p>Cross Sensing Pump Control for Fuel Saving  Four Operating Modes, Four Power Modes  One-way Auxiliary Hydraulics  Adjustable Auxiliary Flow and Pressure up to 10 presets  Computer-aided Pump Power Control  e-EPOS (Electronic Power Optimizing System) Controller"</p>
Cab	<p>"Steel, All Weather Sound Suppressed  Fully Automatic Controlled Air Conditioner with Heat  8" Touch Screen Color LCD Monitor Panel  Rear View Camera  Cigarette Lighter  Door Locks  Front Windshield Wiper with Washer  Radio: MP3 Stereo with CD Player  Switches:  Smart Key Push Start Ignition  Engine Emergency Stop Switch  Work Light Switch  Travel Speed Selector Switch  Swing Priority Switch  Reversing Fan Switch  DPF Regeneration Switch  Auxiliary Mode Switch  Glass Antenna  Safety Lock Lever  Seat:  2 Stage Heated Air Suspension with Seat Belt (2 Wide)  Reclining, Height Adjustable  Adjustable Arm Rests  Sliding Control Console  Skylight  Pull Up Type Front Window  Removable Lower Front Window with Storage Behind Seat  Sliding Side Windows  Front Window Air Defroster  Travel Pedals with Hand Levers  Emergency Breakout Tool  Lunch Box with insulation  12V Power Socket  Height Adjustable Control Stands  Joystick Lever with Three Buttons  Cup Holder  LED Room Light  Serial Communication Port for Laptop PC Interface (DMS)  Viscous Cab Mounts  Operation Modes:  Power Mode Select Button (P+,P,S,E)  Work Mode Selector Button (Excavation, Lifting, Breaker and Shear)  Flow Rate Control  Auto Idle Select Button  4 Display Selection Buttons  Rear View Camera Button  Jog Switch to Control Monitor"</p>
Electrical	<p>"Alternator: 24 V, 115 amp  Batteries: (2) 12 V, 200 amp  Starter: 24 V x 9 KW  Lights: LED Working Light (6) Machine, (2) Boom  Electric Horn  Hour Meter"</p>
	<p>"Alarm Buzzer for:  Engine Oil Pressure  Coolant Temperature  Electronic Monitor for:  Engine Coolant Temperature Gauge  Fuel Gauge"</p>

Display Monitor and Warnings	Hydraulic Oil Temperature Gauge DEF Level DPF Soot Level Indicator Multi-function Display for: Engine RPM Radio Control Display Battery Warning Power Mode Selector Button Power Mode Indicator Hydraulic Oil Overheating Warning Fuel Shortage Warning Air Cleaner Clogging Warning Fuel Filter Clogging Warning Return Filter Clogging Warning Digital Clock Engine Check Warning Light Engine Oil Pressure Warning Light Coolant Temperature Warning Light Work Light Indicator Light Regeneration Notification Water in the Fuel Warning Light DEF Low Level Warning Symbol SCR Failure Warning Symbol"
Undercarriage	"Track Guards and Chains with Adjusters Track Rollers: (3) Upper, (8) Lower Each Side Double Grouser Shoes, 48 Each Side"
Other	"Joystick Pattern Change Valve Centralized Lube Points Headlamp Delay (Escort Lamp) Lamp Indicator on DEF Tank Large Handrail Punched Metal Anti-slip Plates Engine Restart Prevention System Self-Diagnostic System Manuals, Parts and Operator's Ultra-hard Wear-resistant Disc at the Bucket Pivot Vandalism Protection (All panels and fill points lockable) Telematics Unlimited Access with No Contracts & No Fees"