

**PACKAGE ARRANGEMENT (1)**

Product	Approx. Weight	List Price
DX50Z-7-US20	5,150.00 KG	71,333.33 USD

The Tier 4 compliant DX50Z-7 is configured with a 4' 9" (1.45 M) thumb ready arm. NOTE: Attachment not included.  
 Standard dozer blade and standard boom swing improves productivity.  
 15.7" (400 mm) Rubber Tracks are standard.  
 2-way Flow Auxiliary Hydraulics (i.e. clamp control) increases versatility.  
 5.7" Display Monitor  
 Bluetooth Audio  
 QC Piping

**OPTIONAL EQUIPMENT - Factory Installed (5)**

Option	CODE	Description	List Price
Gauge Panel(H)	80D	8" DIGITAL TOUCH SCREEN PANEL	1,146.88 USD
CAMERA	RVC	Rear View Camera	450.56 USD
ADDITIONAL WORK LAMP	LED	Additional Working Lamp	143.36 USD
REAR LAMP	RLA	Rear Lamp	143.36 USD
ROTATING BEACON	ROB	Rotating Beacon	266.24 USD

**Attachments - Dealer Installed (12)**

Attachment	Description	Approx. Weight	List Price
DC05-48	48" PIN ON DITCHING BUCKET; 10.63 CU. FT. CAPACITY	1.00	2,784.17 USD
HD05-12	12" HEAVY DUTY PIN ON BUCKET; 1.45 CU. FT. CAPACITY	1.00	1,769.85 USD
HD05-18	18" HEAVY DUTY PIN ON BUCKET; 2.00 CU. FT. CAPACITY	1.00	1,964.65 USD
HD05-24	24" HEAVY DUTY PIN-ONBUCKET; 3.53 CU. FT. CAPACITY	1.00	2,389.87 USD
HD05-36	36" HEAVY DUTY PIN ON BUCKET; 8.69 CU. FT. CAPACITY	1.00	2,941.58 USD
HT-05DM	HYDRAULIC THUMB; 2 TINE; COMPATIBLE W/ MANUAL QUICKHITCH COUPLER/PIN ON BUCKETS	1.00	3,718.16 USD
HT-05QC	HYDRAULIC THUMB; 2 TINE; USED WITH HYDRAULIC QUICK COUPLER (PIN GRABBER)	1.00	3,382.00 USD
QC45-50H1G4-9136	HYDRAULIC QUICK COUPLER (PIN GRABBER); INCLUDES SOFT PINS, JUMPER HOSE ONLY	1.00	4,292.89 USD
QH-05	QUICKHITCH QUICK COUPLER; MANUAL	1.00	1,049.69 USD

QH05-12	12" GENERAL PURPOSE QUICKHITCH BUCKET; 1.96 CU. FT. CAPACITY	1.00	844.46 USD
QH05-18	18" GENERAL PURPOSE QUICKHITCH BUCKET; 3.43 CU. FT. CAPACITY	1.00	926.95 USD
QH05-24	24" GENERAL PURPOSE QUICKHITCH BUCKET; 4.99 CU. FT. CAPACITY	1.00	1,026.19 USD

## STANDARD EQUIPMENT FOR BASE MACHINE (6)

Item	Description
Engine	<p>"D18 Turbo  High Pressure Common Rail  Tier 4 Compliance without aid of DPF  48.8 HP Gross @ 2,200 rpm  Max. Torque 133 ft. lbs @ 1,600 rpm  Auto Idle  Auto preheat cold start assist  High Idle 2200 rpm MAX, Low Idle 1150 <math>\pm</math> 25 rpm  Alternator: 12 V, 90 Amp.  Battery: 12V Battery, 540 CCA @ 0<math>\pm</math>AE F (-18<math>\pm</math>AE C)  Starter: 12 Volt, 2.7 Kw"</p>
Hydraulic	<p>"Control Valve: (9) Spools, closed center, individually compensated  Main Pump: Load Sensing, torque limiting, variable displacement piston pump with gear pump (36.6 US gpm)  Pressure Setting (3,553 PSI)  Auxiliary Hydraulics Flow (24 gpm)  Swing Motor: Axial Piston Type, with planetary reduction  Swing Speed Control up to 10 RPM  Swing Brake  Travel Motors: Axial Piston, 2-Speed  Travel Speed (High/Low), 2.7 mph / 1.6 mph  Travel Brake  Load Sensing System  2-Way Auxiliary Flow"</p>
Cab	<p>"ROPS Certified  Air Conditioner (Enclosed Cab ONLY)  AM/FM Stereo + Bluetooth (Enclosed Cab ONLY)  Power Socket, 12V  Cab Door Lock (Enclosed Cab ONLY)  Front Windshield Wiper with Washer (Enclosed Cab ONLY)  Safety Glass, Tinted (Enclosed Cab ONLY)  Controls - Safety Lock Lever  Seat:  Deluxe Cloth Seat with Seat Belt (Enclosed Cab ONLY)  Deluxe Vinyl Seat with Seat Belt (Canopy ONLY)  Fully Adjustable Arm Rests  Suspension  Slide-up Front Window (Enclosed Cab ONLY)  Sliding Side Windows (Enclosed Cab ONLY)  Travel Control: Hand Levers/Foot pedals  Emergency Breakout Tool (Enclosed Cab ONLY)"</p>
	<p>"ROPS Certified  Air Conditioner (Enclosed Cab ONLY)  AM/FM Stereo + Bluetooth (Enclosed Cab ONLY)  Power Socket, 12V  Cab Door Lock (Enclosed Cab ONLY)  Front Windshield Wiper with Washer (Enclosed Cab ONLY)  Safety Glass, Tinted (Enclosed Cab ONLY)</p>

Electrical	Controls - Safety Lock Lever Seat: Deluxe Cloth Seat with Seat Belt (Enclosed Cab ONLY) Deluxe Vinyl Seat with Seat Belt (Canopy ONLY) Fully Adjustable Arm Rests Suspension Slide-up Front Window (Enclosed Cab ONLY) Sliding Side Windows (Enclosed Cab ONLY) Travel Control: Hand Levers/Foot pedals Emergency Breakout Tool (Enclosed Cab ONLY)"
Undercarriage	"Track Adjusters Track Rollers: (1) Upper, (4) Lower each side 15.7 inch (400 mm) Rubber Tracks"
Other	"Dozer Blade Pattern Selector Valve Air Cleaner (Dual Filter) Joystick Lever, Dozer (High/Low Travel Speed Switch) Swing Boom (Left: 60 Degrees, Right: 53 Degrees) Auto-Shift, Two Speed Travel Fingertip Auxiliary Hydraulics & Boom Swing Password Protection System Rubber Tracks"