

PACKAGE ARRANGEMENT (1)

Product	Approx. Weight	List Price
DX62R-3-US10	6,250.00 KG	87,456.16 USD
DX62R-3-US10 BASE MACHINE W/O BUCKET 9' 6" (2.90 M) BOOM 6' 3" (1.90 M) ARM 15.75" (400 mm) Rubber Tracks Dozer Blade: 6' 6" x 1' 4" (1980 mm x 410 mm)		

OPTIONAL EQUIPMENT - Factory Installed (4)

Option	CODE	Description	List Price
TRACK SHOE	400	15.75" (400 MM) STEEL SHOE	1,091.95 USD
FUEL FILLER PUMP	FIL	FUEL FILLER PUMP	265.04 USD
FOGS GUARD	FOG	FOG (FALLING OBJECT GUARD)	1,519.19 USD
ROTATING BEACON	ROB	ROTATING BEACON	212.03 USD

Attachments - Dealer Installed (11)

Attachment	Description	Approx. Weight	List Price
5000037	QUICK COUPLER; MANUAL QUICKHITCH	1.00	889.12 USD
DC060-036	7.46 CU. FT. 36" DITCH CLEANING BUCKET	310.00	2,467.52 USD
DC060-048	10.32 CU. FT. 48" DITCH CLEANING BUCKET	475.00	2,784.17 USD
HD06-012	1.84 CU. FT. 12" HEAVY DUTY BUCKET	316.00	1,796.53 USD
HD06-018	3.19 CU. FT. 18" HEAVY DUTY BUCKET	358.00	1,939.23 USD
HD06-024	4.60 CU. FT. 24" HEAVY DUTY BUCKET	429.00	2,185.89 USD
HD06-030	6.03 CU. FT. 30" HEAVY DUTY BUCKET	478.00	2,260.11 USD
HT-06DM2T	MAIN PIN THUMB; HYDRAULIC; 2 TINE; USED WITH BUCKET	185.00	3,718.16 USD
HT-06QC2T	MAIN PIN THUMB; HYDRAULIC; 2 TINE; USED WITH COUPLER	185.00	2,620.60 USD
MT48TYPB	0.29 CU. YD. 48" WIDTH 90 DEGREE TILTING BUCKET	406.00	5,346.50 USD
QC45-50H1G4-9136	HYDRAULIC QUICK COUPLER (PIN GRABBER); INCLUDES SOFT PINS, JUMPER HOSE ONLY	1.00	4,292.89 USD

STANDARD EQUIPMENT FOR BASE MACHINE (6)

Item	Description
ENGINE	"Yanmar 4TNV98C; Naturally Aspirated Electronically Controlled Common Rail Direct Injected DPF / DOC Tier 4 Aftertreatment System 59.4 HP Gross @ 2,100 rpm 58.6 HP Net @ 2,100 rpm Max. Torque 178 ft. lbs @ 1365 rpm Displacement 202.5 cu.in., 4 Cylinder Auto Idle Auto preheat cold start assist Radiator Reserve Tank High Idle 2350 \pm 25 rpm, Low Idle 1050 \pm 25 rpm Alternator: 12 V, 80 Amp. Battery: 12V Battery, 900 CCA @ 0 \pm F (-18 \pm C) Starter: 12 Volt, 3.0 Kw"
HYDRAULIC	"Control Valve: Pilot Operated, (9) Spools Main Pump: Load Sensing - Tandem, Axial Piston (40 US gpm) Pressure Setting (3,627 PSI) Auxiliary Hydraulics Flow (22.5 gpm) Swing Motor: Axial Piston Type, 2 Stage Swing Speed Control up to 9.4 RPM Swing Brake Travel Motors: Axial Piston, 2-Speed Travel Speed (High/Low), 2.7 mph / 1.7 mph Travel Brake Overload Relief Valves Main Relief Valves Load Sensing System 2-Way Auxiliary Flow"
CAB	"ROPS / TOPS Steel, All Weather Air Conditioner with Heater AM/FM Stereo with CD Player & MP3 Port Power Socket, 12V Cab Door Lock Front Windshield Wiper with Washer Safety Glass, Tinted Controls - Safety Lock Lever Seat: Deluxe Reclining with Seat Belt (2") Reclining, Height Adjustable Fully Adjustable Arm Rests Tilting / Sliding Control Console Load Adjustment Knob Suspension Skylight Slide-up Front Window Sliding Side Windows Travel Control: Hand Levers/Foot pedals Emergency Breakout Tool"
ELECTRICAL	"Horn Lights: (1) Cabin, (2) Boom Alarm Buzzer for: Engine Overheat Engine Oil Pressure Electronic Monitor for: Air Filter Restriction Indicator Auto-Idle Indicator Auxiliary Flow Mode Indicator Clock - Day & Time DPF Status Indicator

	Engine Check Warning Light Engine Oil Pressure Light w/ Audible Alarm Engine Temperature Gauge w/ Audible Alarm Fuel Gauge with low fuel indicator Hour Meter Pre-Heat (cold start assist) Indicator Two Speed Travel Indicator Light"
UNDERCARRIAGE	"Track Adjusters Track Rollers: (1) Upper, (5) Lower each side 15.7 inch (400 mm) Rubber Tracks"
OTHER	"Dozer Blade, Front w/Float Joystick Pattern Selector Valve (ISO/STD) Air Cleaner (Dual Filter) Counterweight: 2,059 lb. (934 kg.) Sealed Pins and Bucket Linkages Joystick Lever, Dozer (High/Low Travel Speed Switch Swing Boom (Left: 70 Degrees, Right: 50 Degrees) Auto-Idle Auto-Shift, Two Speed Travel Auxiliary Hydraulics - w/ Quick Couplers & Selectable Flow Rates Boom Load Lock Valve Control Console Locks Fingertip Auxiliary Hydraulics & Boom Swing Mirrors - Left and Right Side Password Protection System Rubber Tracks Travel Motion Alarm"