

PACKAGE ARRANGEMENT (1)		
Product	Approx. Weight	List Price
DL380-7-US10	20,349.00 KG	279,230.81 USD
DL380-7-US10 20,349.00 KG 279,230.81 USD DL380-7-US10 Base Machine With Standard Front Differentials - Limited Slip Differential Front / Rear Without Bucket Steel Cab with Integrated ROPS/FOPS Tires: 23.5R25,L3, Triangle Air Suspension Seat Thumb Wheel Joystick Transmission: 4F / 3R Torque Converter Rear View Camera 3.0 Telematics Radio		

OPTIONAL EQUIPMENT - Factory Installed (19)			
Option	CODE	Description	List Price
ADDITIONAL COUNTERWEIGHT	400	882LB ADDITIONAL COUNTERWEIGHT	3,005.95 USD
CABIN HANDRAIL(TOP)	HDR	CABIN TOP HANDRAIL	514.56 USD
ENGINE COOLANT HEATER	110	110V PLUG HEATER	514.56 USD
EMERGENCY STEER	ESS	EMERGENCY STEER / SECONDARY STEERING	2,117.12 USD
LOAD ISOLATION SYSTEM	LIH	HYDRAULIC LOAD ISOLATION SYSTEM	4,505.60 USD
Additional Brake Pedal	ABP	ADDITIONAL BRAKE PEDAL	99.84 USD
AIR COMPRESSOR	ACO	AIR COMPRESSOR	2,803.20 USD
MIRROR	ADE	ADJUSTABLE MIRROR, REMOTE ELECTRIC	1,886.72 USD
NOISE KIT	NOF	NOISE KIT WITH FRONT	1,774.08 USD
Weighing System	WEI	DOOSAN INTEGRATED WEIGHING SYSTEM	1,344.00 USD
HEAD LAMP	LED	WORK LIGHTS 2 FRONT	399.36 USD
HEAD LAMP	4L4	WORK LIGHTS 4 FRONT AND 4 REAR	925.00 USD
HEAD LAMP	6L6	WORK LIGHTS 6 FRONT AND 6 REAR	1,497.50 USD
ROOF COVER	RFC	CAB ROOF COVER	1,144.32 USD
ROTATING BEACON	ROB	ROTATING BEACON	171.52 USD

## Price Page



CAMERA	AVC	AROUND VIEW CAMERA W/BACKUP SENSOR	2,565.00 USD
TRANSPARENT VIEW	ТРВ	TRANSPARENT BUCKET	3,005.44 USD
FENDER	FUL	REAR FULL FNDR W/FNT FNDR, FNT FNDR HAS MUD GUARD AND RUBBER PROTECTOR	3,320.32 USD
FENDER	RPF	FRONT FENDER WITH RUBBER PROTECTOR	972.80 USD

Attachments - Dealer Installed (23)			
Attachment	Description	Approx. Weight	List Price
109640-10-DL-A	L3180 LOADRITE SCALE	10.00	10,968.32 USD
109640-11-DL-A	L3180 LOADRITE SCALE AND LP950 PRINTER	12.00	12,730.72 USD
118031-10-DL-A	LP950 LOADRITE PRINTER	2.00	2,262.55 USD
186-1760D	AUTO LUBRICATON SYSTEM	0.00	6,546.00 USD
7203954	PALLET FORKS - JRB QC; 106 IN. WIDE CARRIAGE; 72 IN. TINE LENGTH	2,891.00	15,828.96 USD
7225063	PALLET FORKS - ISO QC; 106 IN. WIDE CARRIAGE; 72 IN. TINE LENGTH	2,830.00	14,389.96 USD
7235385	PALLET FORKS - ISO QC; 106 IN. WIDE CARRIAGE; 96 IN. TINE LENGTH	3,112.00	16,861.82 USD
7235387	PALLET FORKS - ISO QC; 106 IN. WIDE CARRIAGE; 84 IN. TINE LENGTH	2,969.00	15,753.34 USD
7235389	PALLET FORKS - JRB QC; 106 IN. WIDE CARRIAGE; 96 IN. TINE LENGTH	3,171.00	18,548.01 USD
7235391	PALLET FORKS - JRB QC; 106IN WIDE CARRIAGE; 84IN TINE LENGTH	3,028.00	17,328.68 USD
7243007	12' SNOW PUSHER; BKT MOUNT	2,200.00	5,304.00 USD
7243008	14' SNOW PUSHER; BKT MOUNT	2,400.00	5,610.00 USD
7254050	QUICK COUPLER, ISO STYLE (Standard Lift)	1,065.00	9,110.09 USD
7254074	QUICK COUPLER, JRB STYLE (Standard Lift)	1,441.00	10,021.09 USD
7273889	GPBKT; 120IN 4.5YD; PIN ON; BOCE	3,784.00	14,543.11 USD
7273890	GPBKT; 120IN 4.5YD; PIN ON; BOT	3,970.00	17,373.76 USD
7273891	GPBKT; 120IN 4.5YD; JRB QC; BOCE	3,506.00	14,936.35 USD
7273892	GPBKT; 120IN 4.5YD; JRB QC; BOT	3,691.00	17,373.76 USD
7273893	GPBKT; 120IN 4.5YD; ISO QC; BOCE	3,497.00	14,543.11 USD
7273892 7273893			

## Price Page



7273894	GPBKT; 120IN 4.5YD; ISO QC; BOT	3,682.00	17,373.76 USD
7389868	GRAPPLE BKT; 120IN 3.50YD; JRB QC; BOCE	4,947.00	18,915.71 USD
7389869	GRAPPLE BKT; 120IN 3.50YD; ISO QC; BOCE	4,924.00	18,915.71 USD
7389870	GRAPPLE BKT; 120IN 3.75YD; PIN ON; BOCE	5,368.00	20,807.28 USD

## STANDARD EQUIPMENT FOR BASE MACHINE (12)

Item	Description
ENGINE:	Doosan DL08: Turbo Charged, Air to Air Intercooled, T4 Electronically Controlled Common Rail Direct Injected 446 cu.in., 6 Cylinder 271 SAE Gross Flywheel Horsepower @ 1,800 RPM Air Cleaner: Dry Type (Double Stage) Engine Self Diagnostic System Reversible Fan Driven by Hydraulic Fan Motor Auto Idle
HYDRAULIC SYSTEM:	Variable Displacement Axial Piston Pump Closed-Center (LS) Hydraulic Systems with Variable Pumps, Pilot Control with Float Spool, 2 Spools 3rd Valve with Lines & Control (lines terminate at boom base) Automatic Boom / Lift - Kick-Out (Set and Adjust from inside the cab) Automatic Return-to-Dig Position (Adjustable Electro-Magnetic) Accumulator for Emergency Pilot System
BRAKE SYSTEM:	Dual Pedal Braking system 4 Wheel Outboard Wet Disc Brakes with Separate Front & Rear Circuits Accumulator for Emergency Stopping Parking Brake: Spring Apply Hydraulic Release, sliding caliper disc brake on the face of the transmission Heavy Duty Brakes, Increase brake force 6 Disc Wet
STEERING:	Load Sensing Type with a Flow Amplifier and a Priority Valve 40 Degree Articulation, Full Hydraulic Power Steering Steering Cylinder Cushion Valve Tilt and Telescopic Steering Wheel Electric Joystick Steering US50 / US51
CAB ROPS/FOPS	"Air Conditioner Heater & Defroster Double Filtered Air Cab Combination Lever Rear View Camera Accelerator Pedal Transmission Lever Rear Hinged & Locking Doors (Both sides) / Right side is emergency access door Switches: Transmission Shift Switch (Manual, Auto 1-4 and Auto 2-4) Economy Mode Switch (Power, Normal & Economy Modes) Headlight Switch Rear Work Light Switch Rear Work Light Switch Rear Wiper Switch Pilot Cutoff Switch Parking Brake Switch Transmission Cutoff Switch Mirror Heater Switch Reverse Fan Switch Display Screen Control Switch



	Hazard Warning Light Switch Boom Kick Out Switch Side View Mirrors with Heat Safety Glass, Tinted Fully Adjustable Air Suspension Seat with Heat Seat Belt (2 Wide) Sliding Door Windows (Left Side)"
TRANSMISSION / AXLES:	"Full Automatic Power Shift 4 Forward & 3 Reverse Speeds, with Torque Converter; US10, US11, US20, US21 5 Forward & 3 Reverse Speeds, with Lock Up Torque Converter; US50, US51 Differentials - US10 / US20 / US50 = Limited slip front and rear Differentials - US11 / US21 / US51, Hydraulic locking front with open rear Self Adjusting Brake Disc Clearance Torque Converter, Fixed Wheel Stator Electrical T/M Clutch Disconnect with Service Brake T/M Down Shift on Shift Control and Joy Stick Control Transmission Oil Level Gauge"
ELECTRICAL:	*Alternator, 80 Amp., 28 Volt Batteries, (2) 12 Volt, 200 Amp, 1300 CCA Starter, 24 Volt 6 KW Horn Key Fob; Entry and starting Lights: (2) Front Headlights with High / Low Beams (2) Stop Lights, Tail Lights & Directional Indicators (2) Front Floodlights (LED) (4) Rear Floodlights (2 roof mounted, 2 mounted in rear grill Alarm Buzzer for: Transmission Overheat Engine Oil Pressure Coolant Temperature Electronic Monitoring & Display for: Fuel Level Gauge DEF Level Gauge DEF Level Gauge Engine Coolant Temperature Gauge Transmission Oil Temperature Gauge Speedometer ECO Bar Transmission Actual Gear Transmission Gear Select Preheat Indicator Light Air Cleaner Clogging Warning Light Multi Function Gauge (can display one of the following at a time) Trip Meter Battery Voltage Total Time of Operation Left Turn and Hazard Warning Light Right Reverse Fan Indicator Light Reverse Fan Indicator Light Reverse Fan Indicator Light Mirror Heater Indicator Light Mirror Heater Indicator Light Mirror Heater Indicator Light Parker Voltage Total Time of Operation Left Turn and Hazard Warning Light Reverse Fan Indicator Light Mirror Heater Indicator Light Mirror Heater Indicator Light Parking Brake Indicator Light Parking Brake Indicator Light Mirror Heater Indicator Light Darke Fluid Pressure Warning Symbol Engine Oil Pressure Warning Symbol DEF Low Level Warning Symbol SCR Failure Warning Symbol Back-Up Alarm*

## Price Page



TIRES:	23.5R25,L3,Triangle		
OTHER STANDARD EQUIPMENT:	Single Lever Control Air Cleaner with Pre- Engine Side Covers Boom / Float Drawbar and Pin Neutral Safety Start Muffler Fenders, Front & Re Ladders & Service P Manuals, Parts & Op Remote Drain Ports"	System ar latforms	ons
OPERATING WEIGHT:	41,502 lbs		
	Installation Options: 1. By your dealers should take about 2 days. Once fa	ship, install video incluc miliar with install, about	ealer Installed Options, price is the kit only (186-1760D). ded. Install cost, based on your labor rate. First time install a day endor, Air and Hydraulics (AHE), \$2,200-\$2800
	Kit comes with pump valve bracket from p 110406-07214A 110406-05501 S05090666 S0509066 S5010513 S5102503 S0558166 S5010503 120804-00078		on is required, for factory fit, order pump bracket and front 1 ea 1 ea 3 ea 4 ea
	Approximate cost for	above parts \$72"	
AUTO LUBE/GREASE SYSTEM (NOT STANDARD EQUIPMENT)	Installation Options: 1. By your dealershi should take about 2	p, install video includeo days. Once familiar wit	aler Installed Options, price is the kit only (186-1760D) I. Install cost, based on your labor rate. First time install h install, about a day dor, Air and Hydraulics (AHE), \$2,200-\$2800
Kit comes with pump bracket but modification is required, for factory fit, order pump bracket a valve bracket from parts. Part #'s are as follows			
	110406-05501	Front Valve Bracket	1 ea
	S05090666 S0509066	Bolt Bolt	3 ea 4 ea
	S5010513 S5102503	Washer Washer	3 ea 4 ea
	S0558166 S5010503 120804-00078	Bolt Washer Washer	4 ea 4 ea 4 ea
Approximate cost for above parts \$72"			
	Loadrite Scales: Order is placed through Doosan		



LOADRITE SCALE SYSTEM (NOT STANDARD EQUIPMENT	PO cut to Loadrite. Loadrite will coordinate with your dealership for installation. Install will be done at your dealership or at customer location. Price is inclusive of Install, Calibration and Customer training.
	Warranty is covered by Loadrite"