

PACKAGE ARRANGEMENT (1)

| Product | Approx. Weight | List Price |
|--------------|----------------|----------------|
| DL420-7-US10 | 22,930.00 KG | 322,281.24 USD |

DL420-7-US10
 Base Machine With Standard Front
 Differentials - Limited Slip Differential Front / Rear
 Without Bucket
 Steel Cab with Integrated ROPS/FOPS
 Tires: 26.5R25,L3, Triangle
 Air Suspension Seat
 Thumb Wheel Joystick
 Transmission: 4F / 3R Without Lock-up torque converter
 Rear View Camera
 3.0 Telematics
 Radio

OPTIONAL EQUIPMENT - Factory Installed (19)

| Option | CODE | Description | List Price |
|--------------------------|------|--------------------------------------|--------------|
| ADDITIONAL COUNTERWEIGHT | 050 | 0.5 TON ADD. COUNTERWEIGHT | 3,719.68 USD |
| EMERGENCY STEER | ESS | EMERGENCY STEER / SECONDARY STEERING | 2,117.12 USD |
| LOAD ISOLATION SYSTEM | LIH | LOAD ISOLATION SYSTEM | 4,505.60 USD |
| CABIN HANDRAIL(TOP) | HDR | CABIN HANDRAIL(TOP) | 514.56 USD |
| ENGINE COOLANT HEATER | 110 | ENGINE COOLANT HEATER | 514.56 USD |
| Additional Brake Pedal | ABP | ADDITIONAL BRAKE PEDAL | 99.84 USD |
| AIR COMPRESSOR | ACO | AIR COMPRESSOR | 2,803.20 USD |
| MIRROR | ADE | ADJUSTABLE MIRROR, REMOTE ELECTRIC | 1,886.72 USD |
| NOISE KIT | NOF | NOISE KIT W/FRONT | 1,774.08 USD |
| Weighing System | WEI | DOOSAN INTEGRATED WEIGHING SYSTEM | 1,344.00 USD |
| HEAD LAMP | LED | LED HEAD LAMP; FRONT ONLY | 399.36 USD |
| HEAD LAMP | 4L4 | LED HEAD LAMP; 4+4 | 925.00 USD |
| HEAD LAMP | 6L6 | LED HEAD LAMP; 6+6 | 1,497.50 USD |
| ROOF COVER | RFC | ROOF COVER | 1,144.32 USD |
| ROTATING BEACON | ROB | ROTATING BEACON | 171.52 USD |
| CAMERA | AVC | AROUND VIEW CAMERA W/BACKUP SENSOR | 2,565.00 USD |

| | | | |
|------------------|-----|--|--------------|
| TRANSPARENT VIEW | TPB | TRANSPARENT BUCKET | 3,005.44 USD |
| FENDER | FUL | REAR FULL FNDR W/FNT FNDR, FNT FNDR HAS MUD GUARD AND RUBBER PROTECTOR | 3,776.00 USD |
| FENDER | RPF | FENDER WITH RUBBER PROTECTOR | 1,057.28 USD |

| Attachments - Dealer Installed (27) | | | |
|-------------------------------------|--|----------------|---------------|
| Attachment | Description | Approx. Weight | List Price |
| 109640-10-DL-A | L3180 LOADRITE SCALE | 10.00 | 10,968.32 USD |
| 109640-11-DL-A | L3180 LOADRITE SCALE AND LP950 PRINTER | 12.00 | 12,730.72 USD |
| 118031-10-DL-A | LP950 LOADRITE PRINTER | 2.00 | 2,262.55 USD |
| 186-1760D | AUTO LUBRICATON SYSTEM | 0.00 | 6,546.00 USD |
| 7203955 | HD PALLET FORKS - JRB QC; 106 IN. WIDE HD CARRIGE; 72 IN. TINE LENGTH | 3,594.00 | 17,765.75 USD |
| 7203956 | ROCK BUCKET; 129IN 4.0YD; PIN ON; WOT | 7,472.00 | 28,417.91 USD |
| 7225064 | HD PALLET FORKS - ISO QC; 106 IN. WIDE HD CARRIAGE; 72 IN. TINE LENGTH | 3,745.00 | 16,150.68 USD |
| 7235384 | HD PALLET FORKS-ISO QC; 106IN WIDE CARRIAGE; 96IN TINE LENGTH | 4,127.00 | 19,394.74 USD |
| 7235386 | HD PALLET FORKS - ISO QC; 106 IN. WIDE CARRIAGE; 84 IN. TINE LENGTH | 3,936.00 | 17,076.02 USD |
| 7235388 | HD PALLET FORKS - JRB QC; 106 IN. WIDE CARRIAGE; 96 IN. TINE LENGTH | 3,975.00 | 21,334.21 USD |
| 7235390 | HD PALLET FORKS - JRB QC; 106 IN. WIDE CARRIAGE 84 IN. TINE LENGTH | 3,784.00 | 17,373.74 USD |
| 7243007 | 12' SNOW PUSHER; BKT MOUNT | 2,200.00 | 5,304.00 USD |
| 7243008 | 14' SNOW PUSHER; BKT MOUNT | 2,400.00 | 5,610.00 USD |
| 7254051 | QUICK COUPLER, ISO STYLE (Standard Lift) | 1,725.00 | 11,811.76 USD |
| 7254075 | QUICK COUPLER, JRB STYLE (Standard Lift) | 1,523.00 | 11,774.84 USD |
| 7273933 | GPBKT; 129IN 5.0YD; PIN ON; BOCE | 5,098.00 | 17,476.58 USD |
| 7273934 | GPBKT; 129IN 5.0YD; PIN ON; BOT | 5,351.00 | 22,239.10 USD |
| 7273935 | GPBKT; 129IN 5.0YD; JRB QC; BOCE | 4,872.00 | 17,476.58 USD |
| 7273936 | GPBKT; 129IN 5.0YD; JRB QC; BOT | 5,125.00 | 22,239.11 USD |
| 7273937 | GPBKT; 129IN 5.0YD; ISO QC; BOCE | 4,897.00 | 17,476.58 USD |

| | | | |
|---------|----------------------------------|----------|---------------|
| 7273938 | GPBKT; 129IN 5.0YD; ISO QC; BOT | 5,149.00 | 21,180.10 USD |
| 7273939 | GPBKT; 129IN 5.5YD; PIN ON; BOCE | 5,327.00 | 19,084.74 USD |
| 7273940 | GPBKT; 129IN 5.5YD; PIN ON; BOT | 5,566.00 | 22,492.07 USD |
| 7273941 | GPBKT; 129IN 5.5YD; JRB QC; BOCE | 5,086.00 | 20,140.73 USD |
| 7273942 | GPBKT; 129IN 5.5YD; JRB QC; BOT | 5,338.00 | 22,492.07 USD |
| 7273943 | GPBKT; 129IN 5.5YD; ISO QC; BOCE | 5,060.00 | 18,175.94 USD |
| 7273944 | GPBKT; 129IN 5.5YD; ISO QC; BOT | 5,313.00 | 22,492.07 USD |

STANDARD EQUIPMENT FOR BASE MACHINE (12)

| Item | Description |
|--|---|
| AUTO LUBE/GREASE SYSTEM (NOT STANDARD EQUIPMENT) | Auto Lube (SKF / Lincoln): Listed under Dealer Installed Options, price is the kit only (186-1760D) Installation Options: 1. By your dealership, install video included. Install cost, based on your labor rate. First time install should take about 2 days. Once familiar with install, about a day 2. At NACUP (Savannah), by our SKF vendor, Air and Hydraulics (AHE), \$2,200-\$2800 Kit comes with pump bracket but modification is required, for factory fit, order pump bracket and front valve bracket from parts. |
| | 110406-02237A Pump Bracket 1 ea 110406-05499 Front |
| | Valve Bracket 1 ea S0509066 Bolt 3 ea S0509066 Bolt |
| | 4 ea S5010513 Washer 3 ea S5102503 Washer |
| | 4 ea S0512066 Bolt 4 ea S5010503 Washer |
| | 4 ea 120804-00078 Washer 4 ea |
| | Approximate cost for above parts \$72 |
| | |
| | |
| | |
| ENGINE | Scania DC13: Turbo Charged, Air to Air Intercooled T4 Electronically Controlled Common Rail Direct Injected 345 SAE Gross Flywheel Horsepower @ 1,800 RPM 775 cu.in., 6 Cylinder Air Cleaner: Dry Type (Double Stage) Engine Self Diagnostic System Reversible Fan Driven by Hydraulic Fan Motor Auto Idle Auto Shut Down" |
| HYDRAULIC | Variable Displacement Axial Piston Pump Closed-Center (LS) Hydraulic Systems with Variable Pumps, Pilot Control with Float Spool, 2 Spools 3rd Valve with Lines & Control (lines terminate at boom base) Automatic Boom / Lift - Kick-Out (Set and Adjust from inside the cab) Return-to-Dig Position (Adjustable Electro-Magnetic Switch outside cab) Accumulator for Emergency Pilot System Thumbwheel Joystick (US10, US11, US20, US21, US50) Fingertip Three Lever (US51)" |

| | |
|----------------------|---|
| BRAKE SYSTEM | <p>"Dual Pedal Braking system 4 Wheel Outboard Wet Disc Brakes with Separate Front & Rear Circuits Accumulator for Emergency Stopping Parking Brake: Spring Apply Hydraulic Release, sliding caliper disc brake on the face of the transmission"</p> |
| STEERING | <p>"Load Sensing Type with a Flow Amplifier and a Priority Valve 40 Degree Articulation, Full Hydraulic Power Steering Steering Cylinder Cushion Valve Tilt and Telescopic Steering Wheel Electric Joystick Steering (US50 and US51 only)"</p> |
| CAB ROPS/FOPS | <p>"Air Conditioner Air Ride Seat (US10, US11, US20, US21) Air Ride Seat w/ Two Way Isolator (US50, US51) Heater & Defroster Double Filtered Air Cab Combination Lever Rear View Camera Accelerator Pedal Transmission Lever Rear Hinged & Locking Doors (Both sides) / Right side is emergency access door Radio, AM-FM Stereo, MP3, with CD Switches: Transmission Shift Switch (Manual, Auto 1-4 and Auto 2-4) (US10, US11, US20, US21) Transmission Shift Switch (Manual, Auto 1-5 and Auto 2-5) US50, US51 Economy Mode Switch (Power, Normal & Economy Modes) Headlight Switch Front Work Light Switch Rear Work Light Switch Rear Wiper Switch Pilot Cutoff Switch Parking Brake Switch Transmission Cutoff Switch Mirror Heater Switch Reverse Fan Switch Display Screen Control Switch Display Screen Selector Switch Hazard Warning Light Switch Boom Kick Out Switch Rear View Mirrors with Heat Safety Glass, Tinted Fully Adjustable Air Suspension Seat with Heat Seat Belt (2 in. Wide) Sliding Door Windows (Left Side) Sound Suppression Sun Visor, retractable Windshield Wipers & Washers - Front and Rear Digital Clock Arm Rest 12 Volt Power Supply Cup Holders"</p> |
| TRANSMISSION / AXLES | <p>"Full Automatic Power Shift 4 Forward / 3 Reverse with Torque Converter (US10, US11, US20, US21) 5 Forward / 3 Reverse with Lock Up Torque Converter (US50, US51) Limited Slip Differential Front and Rear (US10, US20, US50) Hydraulic Locking Front Differential / Open Rear (US11, US21, US51) Self Adjusting Brake Disc Clearance Electrical T/M Clutch Disconnect with Service Brake T/M Down Shift on Shift Control and Joy Stick Control Transmission Oil Level Guage"</p> |
| | <p>"Alternator, 100 Amp., 28 Volt Batteries, (2) 12 Volt, 200 AH, 1300 CCA Starter, 24 Volt 6 kw Horn Hour Meter"</p> |

| | |
|---|---|
| ELECTRICAL | <p>Lights:</p> <ul style="list-style-type: none"> (2) Front Headlights with High / Low Beams (2) Stop Lights, Tail Lights & Directional Indicators (2) Front & Rear Floodlights (Front Floods LED) <p>Alarm Buzzer for:</p> <ul style="list-style-type: none"> Transmission Overheat Engine Oil Pressure Coolant Temperature <p>Electronic Monitoring & Display for:</p> <ul style="list-style-type: none"> Fuel Level Gauge DEF Level Gauge Engine Coolant Temperature Gauge Transmission Oil Temperature Gauge Speedometer Tachometer ECO Bar Transmission Actual Gear Transmission Gear Select Preheat Indicator Light Air Cleaner Clogging Warning Light Multi Function Gauge (can display one of the following at a time) <ul style="list-style-type: none"> Trip Meter Battery Voltage Total Time of Operation Left Turn and Hazard Warning Light Right Turn and Hazard Warning Light High Beam Indicator Light Work Light Indicator Light Reverse Fan Indicator Light Mirror Heater Indicator Light Parking Brake Indicator Light F/R (Forward/Reverse) Selector Indicator Light Brake Fluid Pressure Warning Light Charge Warning Symbol Engine Oil Pressure Warning Symbol Transmission Warning Symbol Engine Warning Symbol Water in Fuel Warnings Symbol Back-Up Alarm DEF Low Level Warning Symbol SCR Failure Warning Symbol" |
| TIRES | Triangle 26.5R25 Radial L3 |
| OTHER STANDARD EQUIPMENT | <p>"Single Lever Control with FNR Air Cleaner with Pre-cleaner Steel Engine Side Covers Boom / Float Drawbar and Pin Neutral Safety Start System Muffler Steel Fenders, Front & Rear Ladders & Service Platforms GPS with 1 Year Subscription Remote Drain Ports"</p> |
| OPERATING WEIGHT | 51,553 LBS |
| LOADRITE SCALE SYSTEM (NOT STANDARD EQUIPMENT) | <p>Loadrite Scales: Order is placed through Doosan PO cut to Loadrite. Loadrite will coordinate with your dealership for installation. Install will be done at your dealership or at customer location. Price is inclusive of Install, Calibration and Customer training. Warranty is covered by Loadrite"</p> |