



Compact Track Loader Attachments

Versatility for Your CTL and Skid Steer !

Bull Hog® Mulchers • Tree Shears • Stump Hogs • Grapples





fecon.com
sales@fecon.com
+1 513 696 4430
800 528 3113

Bull Hog®	Required Hydraulic Flow	Number Of Tools	Working Width / Overall Width	Weight
BH62SS	24 - 45 gpm	24	50" / 63"	2050 lbs
BH74SS	24 - 45 gpm	30	61" / 74"	2425 lbs
BH85SS	24 - 45 gpm	36	72" / 85"	2580 lbs
Tree Shear	Cutting Capacity	Accumulating Capacity	Approximate Cycle Time	Weight
FBS1200 - Dual Knife	12" Diameter	128 sq. in.	10 Sec. w/ 20 gpm	1250 lbs
FBS1400 - Single Knife	14" Diameter	350 sq. in.	8 Sec. w/20 gpm	1800 lbs
FBS1500 - Dual Knife	15" Diameter	350 sq. in.	10 Sec. w/20 gpm	1900 lbs
Rotating Grapple	Opening Area	Clamped Opening	Maximum Load	Weight
FFG60	60"	2"	9900 lbs	800 lbs
Grapple Rake	Length	Depth	Clamp Height (Open)	Weight
FRG72	72"	41"	37"	863 lbs
Grapple Bucket	Length	Depth	Opening	Weight
FBG72	72"	32"	37"	815 lbs
Stump Hog®	Flow	Work Zone	Wheel Diameter / Thickness	Weight
SH270	30-50 @ 3500 psi	48" W x 30" D	25" / 4"	1700 lbs
Stumpex	Flow (GPM)	Speed (RPM)	Depth/Min - 3/4" Bit	Depth/Min - 1" Bit
SHX30SS (30" dia)	20-42	7.3-16.1	5.5"-12.1"	7.3"-16"

BULL HOG® MULCHERS

- Tool design that boosts cutting force by limiting the number of tools contacting the material at any time.
- Counter comb design to size material faster.
- Perfect for Site Prep, R.O.W. & Park Trails.

TREE SHEARS

- Shear trees up to 15" in diameter.
- Shear, Lift, Bunch and Carry Multiple Trees
- Conversion kit available for excavator application.

STUMPEX

- Mounts on skid steers 20-42 GPM
- Bores 20" in ground
- No High Speed Flying Debris for Safer Work Zone

GRAPPLE RAKE / GRAPPLE BUCKET

- Dual independent arms for awkward shaped material.
- Ideal for clearing, brush, debris, logs and rock removal.
- Rigid frame construction for difficult applications.

STUMP HOG

- 60" Wide Swing
- Grind stumps and root balls up to 24" deep.

ROTATING GRAPPLE

- Available in 48", 60" and 72" openings
- 360 degree rotation
- Ideal for moving fallen trees, rocks and brush piles quickly with plug-n-go installation.



- Operator's cab must be protected with both properly maintained 1/2" LEXAN® Glass (or equal) and Falling Object Protection.
- Always ensure that your carrier manufacturers safety features (including Falling Object Protection, and Roll-Over Protection) meet your job safety requirements.
- Certain guarding and features may have been removed for illustrative purposes, always run with proper guarding. • Weights may vary based on options.
- Safety Is The Responsibility Of The Operator. • Specifications subject to change without notice. • Photographs may have been altered for marketing purposes.



GS-30F-0019S