

FECON®



FTX150 Tracked Forestry Mulcher

fecon.com • 800.528.3113

FECON® FTX150 PRODUCT SPECIFICATION

	FTX150	FTX150R
Standard Bull Hog®	BH85SD	BH85SD
GENERAL		
Overall Height	96" / 2439mm	105" / 2667mm
Length - Tractor w/ Bull Hog®	212" / 5385mm	
Weight - Tractor w/ Standard Bull Hog®	18480 lb / 8382 kg	19780 lb / 8972 kg
Width - Tractor w/ Standard Bull Hog®	87" / 2210mm	
ENGINE		
Air Cleaner	Dual with Pre-Cleaner	
Cooling	Water Cooled	
Fuel Consumption	5.0- 6.0 gph / 18-22 lph	
Fuel Tank	45 gal. / 170 ltr	
Horsepower	140hp / 104 kw	
Engine Make / Model	Cummins QSB4.5	
Maximum Rated Torque @ RPM	453 Lbs-ft @ 1400 rpm	
Maximum RPM	2000	
Number of Cylinders	4	
HYDRAULIC		
Hi-Flow Circuit PSI / GPM	5000 psi / 60 gpm • 345 bar / 227 lpm	
Low Flow Circuit PSI / GPM	3000 psi / 26 gpm • 207 bar / 98 lpm	
Hydraulic Cooling Fan	Reversing Std	
Hydraulic Reservoir	55 gal. / 208 ltr	
UNDERCARRIAGE		
Ground Pressure (per SAE J1309)	3.7 psi / 26 kpa	4.7 psi / 33 kpa
Rollers Top / Bottom	1 top / 8 bottom	2 top / 7 bottom
Track Width	20" / 500mm	
Travel Speed	4 mph / 6.4 km/h	
Ground Clearance	16" / 410mm	23" / 584mm
CAB		
Cab Pressurized	Yes	
ROPS, FOPS & OPS	Yes	
Heater / Defroster	Yes	
Air Conditioning	Yes	



Fecon® Advantages

DURABILITY

- Engineered and Built to Withstand All Types of Mulching Conditions.
- High-Strength Steel Construction without Sacrificing Ground Pressure Requirements.

PERFORMANCE

- Best-In-Class Cutting and Track Power.
- Excellent Operator Visibility.

Fecon® FTX150

QUALITY FEATURES

- ✓ Cummins 4.5 Tier 4 Final Engine
- ✓ In Cab Adjustable Flow for Attachment Versatility with Presets
- ✓ Adjustable Hydraulic Pressure Available
- ✓ Fecon Power Management® System
- ✓ Large Engine Compartment Doors for Ease of Service
- ✓ Cab Equipped with New Adjustable Joystick Pods attached to the seat, suspension seat and 4 points of egress
- ✓ New Larger Touchscreen IQAN Display
- ✓ 20" Track Shoes - Single or Triple Grouser

FECON®

fecon.com • sales@fecon.com
800 528 3113 • +1 513 696 4430



- Operators cab must be protected with both properly maintained 1/2" LEXAN® Glass (or equal) and Falling Object Protection.
 - Always insure that your carrier manufacturers safety features (including Falling Object Protection, and Roll-Over Protection) meet your job safety requirements.
 - Certain guarding and features may have been removed for illustrative purposes, always run with proper guarding.
- Weights may vary based on options.
 - Safety Is The Responsibility Of The Operator.
 - Pictures may contain optional accessories
 - Specifications subject to change without notice.
 - Photographs may have been altered for marketing purposes.