

FECON[®]



FTX300 Tracked Forestry Mulcher

fecon.com • 800.528.3113

FECON® FTX300 PRODUCT SPECIFICATION

Standard Bull Hog®	BH120H2
GENERAL	
Overall Height	125" / 3175mm
Length - Tractor w/ Bull Hog®	225" / 5715mm
Weight - Tractor w/ Standard Bull Hog®	31750 lbs / 14402 kg
Width - Tractor w/ Standard Bull Hog®	101" / 2533mm
ENGINE	
Air Cleaner	Dual with Pre-Cleaner
Cooling	Water Cooled
Fuel Consumption	7-9 gph / 26 -34 lph
Fuel Tank	100 US GAL / 378 ltr
Horsepower	310 hp / 231 kW
Engine Make / Model	Cummins B6.7 Stage 5
Maximum Rated Torque @ RPM	950 ft lbs @ 1,500 rpm
Maximum RPM	2500
Number of Cylinders	6
HYDRAULIC	
Hi-Flow Circuit PSI / GPM	5400 psi / 115 gpm • 372 bar / 435 lpm
Low Flow Circuit PSI / GPM	3000 psi / 33 gpm • 206 bar / 124 lpm
Hydraulic Cooling Fan	Variable Speed Reversing
Hydraulic Reservoir	50 US GAL / 189 ltr
UNDERCARRIAGE	
Ground Pressure (per SAE J1309)	3.9 psi / 27 kPa
Rollers Top / Bottom	2 / 8
Track Width	30" / 800mm
Travel Speed	4.5 MPH / 6.4 km/h
Ground Clearance	23" / 585mm
CAB	
Cab Pressurized	Yes
ROPS, FOPS & OPS	Yes



Fecon® Advantages

DURABILITY

- Engineered and Built to Withstand All Types of Mulching Conditions.
- High-strength Steel Construction for Lightweight Durability.

PERFORMANCE

- Strong Cutting and Track Power.
- Operator Visibility.

Fecon® FTX300 QUALITY FEATURES

- ✓ Oscillating Undercarriage with 30" Track Shoes
- ✓ Front Mount Lift Height 44" Under Cutting Tools
- ✓ Large Tilting Cab for Service Access
- ✓ Wide Engine Compartment Doors Sides and Rear
- ✓ Air Suspension, Heated Seat
- ✓ Large 7" Touchscreen Display
- ✓ Keyless Ignition with Security
- ✓ Factory Service Remote Connectivity Standard
- ✓ IQAN controls with Fecon Power Management

FECON®

fecon.com • sales@fecon.com
800 528 3113 • +1 513 696 4430



- Operators cab must be protected with both properly maintained 1/2" LEXAN® Glass (or equal) and Falling Object Protection.
 - Always insure that your carrier manufacturers safety features (including Falling Object Protection, and Roll-Over Protection) meet your job safety requirements.
 - Certain guarding and features may have been removed for illustrative purposes, always run with proper guarding.
- Weights may vary based on options. • Safety Is The Responsibility Of The Operator. • Pictures may contain optional accessories
- Specifications subject to change without notice. • Photographs may have been altered for marketing purposes.