GOLIGHT® LED Search Lights

Spot Beam with White LEDs Includes Wireless Handheld Remote







EWL30514ST



Chrome Housing EWL30064ST



White Housing

EWL30004ST





Features

- Ten high flux LEDs
- Wireless remote control
- 370° rotation x 135° tilt
- 320,000 candela; max beam distance of 3,711 feet
- Eight degree beam angle
- UV ray and saltwater resistant
- Weatherproof for land and sea applications

WARRANTY	Five-year
MOUNT	Permanent mount
Depth	8" (20.32 cm)
Height	7" (17.78 cm)
Length	7" (17.78 cm)
DIMENSIONS	
AMPERAGE	2.8 Amp
BEAM PATTERN	Spot
WATTS	40
LED COUNT	10 LED
INPUT VOLTAGE	12 Vdc

1.800.338.7337

WL4, WL5 and WL9

700, 900 and 1800 Lumen LED Lights



WL4 Flood and Spot Lens



WL5 Spot Lens

900 Lumen

EWL5SBDS0W



WL9 Flood and Spot Lens

1800 Lumen, Flood Pattern EWL9SBDF0W 1800 Lumen, Spot Pattern EWL9SBDS0W

Features

- Deliver super bright output with low amp draw
- Weatherproof design
- Adjustable mounting brackets make these lights ideal for multiple vehicle applications

INPUT VOLTAGE	10-30 Vdc
CURRENT DRAW	
WL4	.6 Amp @ 13.5 Vdc, .3 Amp @ 28 Vdc
WL5	.97 Amp @ 13.5 Vdc, .47 Amp @ 28 Vdc
WL9	1.5 Amps @ 13.5 Vdc, .8 Amp @ 28 Vdc
LED COUNT	
WL4	4 LEDs
WL5	5 LEDs
WL9	9 LEDs
ILLUMINATION PATTERNS	WL4 and WL9: Flood and spot patterns W5: Spot pattern
OPERATING TEMPERATURE	-40° to +65° C / -40° to +149° F
COLOR TEMPERATURE	6500k
DIMENSIONS	WL4: Height 4.1" Width 2.8" Depth 1.8"
	WL5: Height 5.8" Width 4.3" Depth 1.8"
	WL9: Height 5.5" Width 4.4" Depth 2.9"
MOUNT	One bolt with rubber mounting pad
CERTIFICATION	EMC ECE Reg. 10 certified
WARRANTY	Three-year

soundoffsignal.com 68