


PISTON/ROTARY/ENGINE DRIVEN COMPRESSORS



SINGLE-STAGE PISTON SERIES




Model 8P

- 8 cfm @ 100 psi
- Hyd. req: 7 gpm @ 1800 psi
- Max. pressure: 150 psi
- Single-stage, Two-cylinder
- Embedded air filter
- 23"L x 14.5"W x 17"H
- Weight: 125 lbs
- Uses Model 143 Pump



Model 30P

- 30 cfm @ 100 psi
- Hyd. req: 11 gpm @ 1850 psi
- Max. pressure: 150 psi
- Single-stage, Four-cylinder
- Canister air filter
- 26.75L x 19.75W x 19.5H
- Weight: 225 lbs



Model 13P


- 13 cfm @ 100 psi
- Hyd. req: 7 gpm @ 1800 psi
- Max. pressure: 150 psi
- Single-stage, Two-cylinder
- Embedded air filter
- 26"L x 14.5"W x 17"H
- Weight: 125 lbs
- Uses Model 200 Pump



Model 70P


- 70 cfm @ 100 psi
- Hyd. req: 18 gpm @ 2650 psi
- Max. pressure: 150 psi
- Single-stage, Four-cylinder
- Canister air filter
- 31"L x 22.5"W x 22"H
- Weight: 300 lbs
- Uses Model HV60 Pump

TWO-STAGE PISTON SERIES



Model 23P

- 23 cfm @ 175 psi
 - Hyd. req: 8 gpm @ 2300 psi
 - Max. pressure: 175 psi
 - Two-stage, Two-cylinder
 - 28"L x 19.5"W x 27.5"H
 - Weight: 325 lbs
- (Shown with optional 8-gal. hyd reservoir)




Model 60P

- 60 cfm @ 175 psi
- Hyd. req: 16 gpm @ 2300 psi
- Max. pressure: 175 psi
- Two-stage, Two-cylinder
- 46"L x 24"W x 35"H
- Weight: 655 lbs



Model 46P

- 46 cfm @ 175 psi
- Hyd. req: 17-19 gpm @ 2500 psi
- Max. pressure: 175 psi
- Two-stage, Four-cylinder
- 33.5"L x 25"W x 27.5"H
- Weight: 425 lbs



Model 110P

- 110 cfm @ 175 psi
- Hyd. req: 24 gpm @ 2300 psi
- Max. pressure: 175 psi
- Two-stage, Four-cylinder
- 43"L x 28"W x 36.5"H
- Weight: 900 lbs

ROTARY SERIES



- Model 30R**
- Single-stage oil injected
 - 30 cfm @ 100 psi @ 7250 rpm
 - Hyd. req: 12 gpm @ 1750 psi
 - Max. pressure: 150 psi
 - 24L x 19.75W x 20.75H
 - Weight: 175 lbs



- Model 130R**
- Single-stage oil injected
 - 100-150 psi
 - 130 cfm @ 150 psi
 - 26 gpm @ 2400 psi
 - 43.5”L x 31”H x 28”W
 - Weight: 325 lbs



- Model 45R**
- Single-stage oil injected
 - 40-45 cfm @ 100 psi @ 5500-6000 rpm
 - Hyd. req: 10-12 gpm @ 2600 psi
 - Max. pressure: 150 psi
 - 30.38”L x 26”H x 22”W
 - Weight: 325 lbs



- Model VR70 Underhood**
- Single-stage oil injected rotary screw compressor
 - 70 cfm @ 150/175 psi



- Model 65R**
- Single-stage oil injected
 - 55-65 cfm @ 100 psi @ 7000-7500 rpm
 - Hyd. req: 16-18 gpm @ 2750 psi
 - Max. pressure: 150 psi
 - 30.38”L x 26”H x 22”W
 - Weight: 345 lbs



C130GEH34HC



RS180GEC30

Gas Engine Reciprocating Compressors

	Engine HP	CFM	Air Tank Size
C80GEH33	8	15.5 @ 175 PSI	30
C130GEH34HC	13	23 @ 175 PSI	30
C140GEC36HC	14	32 @ 175 PSI	30
SGD-2340	23	40 @ 175 PSI	5

Diesel Engine Reciprocating Compressors

	Engine HP	CFM	Air Tank Size
C110GED34HC	10	22 @ 175 PSI	30
C180GED36HC	17	35 @ 175 PSI	30

Gas Engine Rotary Screw Compressors

	Engine HP	CFM	Air Tank Size
RS130GEH30	13	28 @ 150 PSI	30
RS180GEC30	18	39 @ 150 PSI	30
RS28GEC30	28	80 @ 150 PSI	30
RS38GECBM	38	130 @ 150 PSI	No Tank

Diesel Engine Rotary Screw Compressors

	Engine HP	CFM	Air Tank Size
RS180GED30	17	39 @ 150 PSI	30
RS250GED30	26	80 @ 150 PSI	30

740 North State Street
 P.O. Box 169
 Garner, IA 50438
 Telephone: 800-392-3015
 E-mail: sales@americaneagleacc.com



Designed & Manufactured in the U.S.A.
 *Specifications may change without notification.
 Copyright © 2020 American Eagle Accessories Group.