



## Heavy Duty Starting Equipment, Hydraulic Powered for Service Trucks

Powerful Charging and Jump Starting Systems to Get Your Vehicles Up and Running

### 700 Amps • 12/24 Volts • Hydraulic

JUMP STARTING	12/24 volt, 700/400 AMP
HYDRAULIC REQUIREMENTS*	15 GPM @ 2,500 PSI
CABLES	30' 1/0 ga.
CLAMPS	1,000 AMP
DIMENSIONS	36" W x 18" D x 12" H 199 lbs.

\*Minimum hydraulic requirements: 35 gal. hydraulic tank, 3/4" pressure hose and 1" return hose.



11-807



## Heavy Duty Wheeled Starting Equipment Battery Powered

Portable Jump Starting Solutions for Repair Shops, Parking Lots and Garages

### 1800 Amps • 12/24 Volts

POWER SOURCE	(2) Group 31 AGM batteries
JUMP STARTING	12/24 volt
CABLES	10' 4/0 ga.
CLAMPS	1,000 AMP
DIMENSIONS	20" W x 26" D x 48" H 77 lbs.

#### Features:

- Fully automatic internal AC charger to keep battery in ready-to-use condition
- Extra large pneumatic tires for easy mobility
- Volt metered to monitor battery charge level of the Boost-All® or vehicle

Requires 2 group 31 AGM batteries, 3/8" threaded top post, 900 CCA or higher (batteries not included)



Plug it in and leave it plugged in. Ready when you need it. Integrated, fully-automatic 120 volt AC charger.

13-224

**FREIGHT NOT**  
**INCLUDED IN**  
**PRICE OF UNIT.**  
**FREIGHT WILL**  
**BE BILLED UPON**  
**PURCHASE.**