



Heavy Duty Starting Equipment Battery Powered Permanent Mount on Service Trucks

Vehicle-Mounted, Battery Powered, Heavy-Duty, Turn-Key Starting Solutions

12/24 Volts

| | |
|--------------|--|
| POWER SOURCE | 2 or 4 auxiliary jump starting batteries |
| CABLES | 25' 2/0 ga. |
| CLAMPS | 1,000 AMP |
| DIMENSIONS | 10" W x 12" D x 10" H 50 lbs. (w/o batteries) |

Output dependent on number of auxiliary batteries.



13-425

12/24 Volts

| | |
|---------------|---|
| POWER SOURCE | 2 or 4 Group 31 batteries |
| JUMP STARTING | 12/24 Volt |
| CABLES | 25' 2/0 ga. |
| CLAMPS | 1,000 AMP |
| DIMENSIONS | 15" W x 9" D x 16" H 48 lbs. (with cables) |



PROTECT-ALL
Safety Technology

13-492-001

Make it a complete kit: battery box, group 31 batteries, booster cables, and connecting cables available.



Capacitor Powered Heavy Duty Engine Starting Systems for Instantaneous Starting Power

Battery Driven

1500 Amps • 24 Volts

| | |
|---------------|--|
| POWER SOURCE | Super Capacitor & (2) Group 31 AGM batteries |
| JUMP STARTING | 24 volt |
| CABLES | 26' 4/0 ga. |
| CLAMPS | 1,000 AMP Full Power |
| DIMENSIONS | 44" W x 20" D x 14" H 309 lbs. |



13-097-10

Features:

- Capacitor can be recharged 500,000 times
- Power cells are maintenance free
- Operating temperature range from -49° F to 122° F
- Quick disconnect red plug for plug-to-plug operation
- Includes reverse polarity and dead start circuitry protection

FREIGHT NOT
INCLUDED IN
PRICE OF UNIT.
FREIGHT WILL
BE BILLED UPON
PURCHASE.