



PTO SHAFT DRIVEN AIR COMPRESSOR, GENERATOR & SAE B PUMP PAD

AIR COMPRESSOR			
Capacity (CFM)	125	160	175
Air (PSI)	100-150	100-150	100-150
Compressor Input (RPM)	1900	2325	2500
Oil Capacity (Gal.) Initial Fill	2.5	2.5	2.5

GENERATOR (TEFC)			
Output (continuous)	6.6 kW	OR	9.6 kW
Voltage	120 or 120/240	120 or 120/240	
Phase	Single Phase	Single Phase	
Speed	3600 RPM	3600 RPM	
Protection Degree	IP54	IP54	
Type	Brushless AVR	Brushless AVR	

SAE B PUMP PAD (pump sold separately)
Limited to 77 Ft. Lbs.

Dry Weight (Lbs.): 595(min.) - 636(max.)

XCITE
PTO GENERATORS



RAM

ISUZU



PTO SHAFT DRIVEN GENERATOR

GENERATOR						
kW	6.8	10	16.9	20	25	
Voltage	120 or 120/240	120 or 120/240	120 or 120/240	120 or 120/240	120 or 120/240	
Phase	Single	Single	Single	Single	Single	
AMPs	54/27	84/42	140/70	166/83	208/104	
Speed (RPM)	1800	1800	1800	1800	1800	
Weight (Lbs.)	80	123	270	295	339	

Dimensions (In.): 12H x 11.5W x 17L (6.8 kW - 10kW), 12H x 12W x 24L (16.9 kW), 12H x 12W x 25L (20 kW - 25 kW)
Consult factory for additional kW options

HYDRAULIC DRIVEN GENERATOR

4 kW, 7.5 kW and 8.5 kW available for Ford® Super Duty 350/450/550 models
All options available for Ford® Super Duty 650/750 models



GENERATOR						
kW	4	7.5	8.5	10	12	15
Voltage	120 or 120/240	120 or 120/240	120 or 120/240	120 or 120/240	120 or 120/240	120 or 120/240
Phase	Single	Single	Single	Single	Single	Single
AMPs	33/16	62/31	72/36	84/42	105/52.5	126/63
Hydraulic Flow (GPM)	8.5	14.5	16	19	20	24
Pressure (PSI)	1800	1800	1800	2000	2000	2000
Weight (Lbs.)	78	105	114	121	129	141

Dimensions (In.): 10H x 8W x 23L (4 kW), 10H x 8W x 28L (7.5 kW - 10 kW), 11H x 11W x 29L (12 kW - 15 kW)
Consult factory for additional kW options

FREIGHT NOT
INCLUDED IN
PRICE OF UNIT.
FREIGHT WILL
BE BILLED UPON
PURCHASE.