



## SPECIFICATIONS

### V185-UT➤

|                                |       |
|--------------------------------|-------|
| Rated Delivery (CFM)           | 185   |
| Rated Operating Pressure (PSI) | 100   |
| Length (in.)                   | 80    |
| Width (in.)                    | 35    |
| Height (in.)                   | 55.39 |
| Weight (lbs.)                  | 2,340 |

### V210-UT➤

|                                 |       |
|---------------------------------|-------|
| Rated Delivery (CFM)            | 210   |
| Rated Operating Pressures (PSI) | 100   |
| Length (in.)                    | 80    |
| Width (in.)                     | 35    |
| Height (in.)                    | 55.39 |
| Weight (lbs.)                   | 2,550 |

### V260-UT➤

|                                |       |
|--------------------------------|-------|
| Rated Delivery (CFM)           | 260   |
| Rated Operating Pressure (PSI) | 100   |
| Length (in.)                   | 83    |
| Width (in.)                    | 35    |
| Height (in.)                   | 55.39 |
| Weight (lbs.)                  | 3,070 |

## FEATURES

- Curbside Serviceability
- Large, 108mm Diameter Twin Screw Air End
- Automatic 0 to 100% Capacity Control
- Two Stage Dry Type Air Filter - External Access
- Two 3/4" Service Connections
- Oil Level Sight Gauge
- Isuzu Engine for 185 CFM, John Deere Engine for 210 and 260 CFM
- Steel Fuel Tank
- Side by Side Coolers for Compressor and Engine
- Compact Size for Truck Mounting
- Curbside Fuel Fill & Air Filter Access
- Noise Level Limited to Maximum of 76 dBA at 7 Meters
- All Drains End Mounted
- Automatic Shutdown and Protection System
- Automatic Blowdown Valve
- Unloaded Starting
- SAE Pad Available on Select Models

Product improvement is a continuing goal. Design and specifications are subject to change without notice or obligation. UTILITYMOUNT\_ 012021\_CMG

FREIGHT NOT  
INCLUDED IN  
PRICE OF UNIT.  
FREIGHT WILL  
BE BILLED UPON  
PURCHASE.