

# **EXPAND PARKING LOT PRODUCTIVITY**

Quickly and easily expanding from 8 to 10 feet at the touch of a button, the BOSS EXT is equipped to clean up parking lots and wide open spaces. A true 10-foot width combined with pitched-forward wings lets the EXT take wider passes, carrying and moving more snow more efficiently. At 30 inches high with 9 vertical ribs, the EXT moves a high volume of snow with resilience, making it a versatile and flexible addition to your fleet. Another powerful tool in your plowing arsenal that's built to BACK YOU UP.

















> 10' expanded



> Independent wing extension



## **PRODUCTIVITY BOOSTER**

Quickly expand to a true 10-foot blade for wider passes that efficiently move more snow.



## STANDARD FEATURES

- Expandable, Fully Hydraulic, Pitched-Forward Wings expand from 8' to 10' to cover more ground.
- SmartLight<sup>™</sup> 3 LED Headlight System uses DOT-compliant 100% LED lights and Ice Shield Technology<sup>™</sup> to prevent snow and ice build-up.
- Reinforced Moldboard increases blade rigidity for increased durability.
- Heavy-Duty Push Frame and Attachment Bar adds strength and increases performance by spreading loads out over a wider area.
- Open Plow Back Design prevents snow and ice build-up to maintain optimal wing retraction.

### > MODEL

Steel 8' Retracted, 10' Expanded



10' Expanded With Pitched-Forward Wings



left-hand adjustment.

## PROFESSIONAL-USE PLOWS

**EXT**VEHICLE APPLICATION: 4WD, %- AND 1-TON TRUCKS



Specifications	8' Retracted / 10' Expanded Steel		
Blade Width (Retracted)	96" (244 cm)		
Blade Width (Extended)	120" (305 cm)		
Plowing Width @ 30° Angle	83" (211 cm) / 103" (262 cm)		
Blade Height	30" (76.2 cm)		
Blade Thickness	11-ga steel		
Cutting Edge (AR450)	½" x 6" (1.3 cm x 15 cm)		
Reinforcement Ribs	9 vertical		
Plow Shoes	Optional		
Trip Springs	4		
Angle Cylinders	1½" x 10" (4 cm x 25 cm)		
Wing Cylinders	1½" x 1½" x 12¾" (4 cm x 3 cm x 32 cm)		
Lift Cylinder	2" x 11/6" x 10" (5 cm x 3 cm x 25 cm)		
Shock Absorber			
Attachment System	SmartHitch® 2		
Plow Weight*	970 lb <sup>8</sup> (440 kg)		
Plow Lights	SL3 LED with Ice Shield Technology™		

 $<sup>^*</sup>$ Plow weight does not include vehicle mount weight.  $^8$ Vehicle mount weight range: 75-105 lb (34-48 kg).



## SUPER-DUTY FULL-TRIP STRAIGHT-BLADE VEHICLE APPLICATION: 4WD, %- TO 1-TON TRUCKS

Specifications	7'6" Super-Duty Steel / Poly	8' Super-Duty Steel / Poly	8'6" Super-Duty Steel	9' Super-Duty Steel
Blade Width (Straight)	90" (229 cm)	96" (244 cm)	102" (259 cm)	108" (274 cm)
Plowing Width @ 30° Angle	78" (198 cm)	83" (211 cm)	88" (224 cm)	93½" (238 cm)
Blade Height	29" (74 cm)	29" (74 cm)	29" (74 cm)	29" (74 cm)
Blade Thickness	11-ga steel / 3/8" (0.95 cm) poly	11-ga steel / 3/8" (0.95 cm) poly	11-ga steel	11-ga steel
Cutting Edge	½" x 6" (1.3 cm x 15 cm)	½" x 6" (1.3 cm x 15 cm)	½" x 6" (1.3 cm x 15 cm)	½" x 6" (1.3 cm x 15 cm)
Reinforcement Ribs	7 vertical, 2 diagonal	7 vertical, 2 diagonal	7 vertical, 2 diagonal	7 vertical, 2 diagonal
Plow Shoes	Cast iron	Cast iron	Cast iron	Cast iron
Trip Springs	4	4	4	4
Angle Cylinders	1½" x 10" (4 cm x 25 cm)	1½" x 10" (4 cm x 25 cm)	1½" x 10" (4 cm x 25 cm)	1½" x 10" (4 cm x 25 cm)
Lift Cylinder	2" x 11/8" x 10" (5 cm x 3 cm x 25 cm)	2" x 11/8" x 10" (5 cm x 3 cm x 25 cm)	2" x 11/8" x 10" (5 cm x 3 cm x 25 cm)	2" x 11/8" x 10" (5 cm x 3 cm x 25 cm)
Shock Absorber	- 1	.1		
Attachment System	SmartHitch® 2	SmartHitch® 2	SmartHitch® 2	SmartHitch® 2
Plow Weight*	680 lb <sup>B</sup> (308 kg) / 706 lb <sup>B</sup> (320 kg)	698 lb <sup>8</sup> (317 kg) / 722 lb <sup>8</sup> (328 kg)	720 lb <sup>8</sup> (327 kg)	742 lb <sup>8</sup> (337 kg)
Plow Lights	SL3 LED with Ice Shield Technology™	SL3 LED with Ice Shield Technology™	SL3 LED with Ice Shield Technology™	SL3 LED with Ice Shield Technology™
D-Force®	Optional	Optional	Optional	Optional

# FREIGHT NOT INCLUDED IN PRICE OF UNIT. FREIGHT WILL BE BILLED UPON PURCHASE.