

K&K
MANUFACTURING



Single Axle Utility Trailer

Side Rail: 2" x 3" x 3/16 Angle

Crossmembers: 2" x 3" x 3/16 Angle

Floor: 2" Pressure Treated Pine

Tongue: 3" x 11 ga. Square Tubing

Coupler: 2" Ball Coupler

(1) Dexter 3,500 lb. Idler Hub with Double Eye Type Springs

205/75R15 Radial 6 ply on 15" Silver Mod Wheels

3,000 lb. Swivel Jack

1/4" Safety Chains with Clevis Hooks

Double Axle Utility Trailer

Side Rail: 2" x 3" x 3/16 Angle

Crossmembers: 2" x 3" x 3/16 Angle

Floor: 2" Pressure Treated Pine

Tongue: 3" x 11 ga. Square Tubing

Coupler: 2" Ball Coupler

(2) Dexter 3,500 lb. Axles with Slipper Type Springs

Electric Brakes on All Wheels

205/75R15 Radial 6 ply on 15" Silver Mod Wheels

3,000 lb. Swivel Jack

1/4" Safety Chains with Clevis Hooks

LED Lights

Low Pro Equipment Trailer

Main Frame: 6" x 4" x 3/8" Angle

Crossmembers: 3" Channel

Floor: 2" Nominal Oak

Front Plate: Adjustable 4 Bolt, 3 Position

Coupler: 4 Bolt Pintle Ring

(2) 7,000 lb. Dexter Axles 95" H/F x 80" S/C with Slipper Style Springs

Brakes: 12" Electric Brakes on all Wheels

235/80R16 Radial 10 ply on 16" Silver Mod Wheels

10,000 lb. Jack

3/8" Safety Chains with Clevis Hooks

Dump Trailer

Main Frame: 6" Channel

Cross Members: 3x2 Tubing

Floor Plate: 3/16" Smooth

Sides: 24" with Barn Doors

Slide Under Ramps

Hoist: Electric Hoist Champion CS620T-15 EMDA

7K Axles with Electric Brakes

235-80R-16-G Tires (14 ply)

Adjustable Hitch

12K Drop-Leg Jack

Mudflaps

LED lighting Shipped Loose

Paint: Black



83x16-DT-KK BELOW, UT-60X10U13K ABOVE

