LEVEL-RIDE CANTILEVER LIFT

ML - 2200 lbs

LMM - 2200 / 3300 lbs LMH - 3300 / 4400 lbs

LMS - 4400 / 5500 / 6600 lbs





APPLICATION

DHOLLANDIA's cantilever liftgates combine industry leading simplicity, reliability & safety, with ease of use for operators and technicians in mind. The lifts are designed for the harshest weather & operational conditions.

Fleets will love that no circuit boards or sensors are used in any DHOLLANDIA cantilevers. With capacities ranging from 2200 - 6600 lbs., numerous platform sizes available, and **STANDARD** galvanized finish, DHOLLANDIA has a solution for any application.



Dual lift cylinders for great load stability



Fully galvanized finish - STANDARD



Level-ride with auto-tilt at ground level



NO Complicated Circuit Boards / Sensors



Self-locking valves on all cylinders



Automatic leveling of platform



STANDARD FEATURES

- Galvanized finish on steel components
- · Level-ride plus auto-tilt at ground level
- Automatic leveling
- 3-Piece under ride guard
- 3-Button remote control
- Self-locking valves on all cylinders, with a manual override function
- Cylinders with piston rods in hard-chromed stainless steel
- Sealed weather-proof pump unit with thermoprotected electromotor
- Low-maintenance bushings & zerks in pivot points
- · Full length ground and power cables
- 250 amp inline mega fuse circuit protection
- NO Complicated circuit boards or sensors

MAIN OPTIONS

- Hand-held remote control with spiral cable
- · Dual spring loaded cart stops
- Cab shutoff switch and harness
- Cycle counter for hydraulic power pack
- Aux. battery kit (truck or trailer)
- Foot activated controls on platform
- Full or flip door seal kit
- Bridge kit for swing doors
- Platform warning lights



Heavy duty steel platforms available



Optional flip-up door kits



Platform lights (option)

Model	Capacity Ibs	Platform	Size	Floor Height	Floor to Tube	Lift Overhang	Approx. Weight
LML	2200	Aluminum	49" x 94"	29" - 43"	11" - 22"	21" - 29"	440 lbs.
		Aluminum	72" x 94"	29" - 43"	11" - 22"	21" - 29"	510 lbs.
LMM	2200 / 3300	Aluminum	49" x 98"	32" - 47"	13" - 25"	27" - 38"	590 lbs.
			57" x 94"	32" - 47"	13" - 25"	27" - 38"	615 lbs.
			61" x 98"	34" - 51"	15" - 28"	25" - 35"	640 lbs.
			73" x 94"	32" - 47"	13" - 25"	23" - 32"	715 lbs.
			73" x 98"	32" - 47"	13" - 25"	23" - 32"	745 lbs.
LMH	3300 / 4400	Steel	73" x 98"	36" - 59"	17" - 32"	29" - 40"	1200 lbs.
		Aluminum	85" x 94"	34" - 55"	15" - 30"	27" - 38"	1080 lbs.
		Steel or Full Alu	85" x 98"	34" - 55"	15" - 30"	27" - 38"	1450 / 1030
LMS	4400 / 5500 / 6600	Aluminum	85" x 94"	33" - 56"	13" - 30"	31" - 43"	1100
		Steel or Full Alu	85" x 98"	33" - 56"	13" - 30"	31" - 43"	1550 / 1130

Other configurations available, please contact DHOLLANDIA for more information.

DHOLLANDIA US Inc. • 270 Southridge Parkway, Bessemer City, NC 28016 • sales.USA@dhollandia.com



Toll free (855) 856-8225 • Tel: (909) 251-7979 • Fax: (909) 357-1554