LEVEL-RIDE VAN LIFT

LSP & LSPZ Series 1100 / 1320 lbs.





APPLICATION

The **DHOLLANDIA LSP/LSPZ** was the first external liftgate ever in the liftgate industry, engineered specifically for vans. DHOLLANDIA still continues to lead the innovations in this field today.

Available in 1-piece (LSP) or folding platform (LSPZ) configurations. Van specific mount plates for MB Sprinter, Ford Transit, Ram ProMaster and Nissan NV make for a simplified installation.

DHOLLANDIA offers the largest possible platform surface for factory built vans, making the LSP(Z) suitable for all types of cargo, including pallets.



61" or 71" deep platforms available



1100 / 1320 capacities available



Level-ride with auto-tilt at ground level



Hinged or 1-piece platform



Aluminum platform with anti-slip surface



NO complicated circuit boards or sensors



STANDARD FEATURES

- Aluminum platform with anti-slip surface
- Self-locking valves on the cylinder, with a manual override function
- Van specific mounting plates
- · Level-ride plus auto-tilt at ground level
- Sealed weather-proof pump unit with thermoprotected electromotor
- 250 amp inline mega fuse circuit protection
- Full length ground and power cables
- · Cab shutoff switch
- Spring loaded cart stop(s)
- 2 Button (LSP) 3 Button (LSPZ) handheld remote
- Warning light on non-folding platforms (LSP)
- Bridge plate for smooth transition from lift
- 3 Button flush mount control (LSP)

MAIN OPTIONS

- Auxiliary battery kits (required by OEM)
- · Hinged safety railings on platform
- · Door-less closure with seal kit
- Foot controls on platform
- License plate light on rear of platform






Door-less closure available



Spring loaded cart stop



Side railings (optional)



Capacity Ibs.	Platform	Platform Size	Floor Height	Lift Overhang	Approx. Weight
1100 / 1320	Full Alu	61" x 55"	32"	27" - 33"	420 lbs.
1100 / 1320	Full Alu	71" x 55"	32"	27" - 33"	440 lbs.

DHOLLANDIA US Inc. • 270 Southridge Parkway, Bessemer City, NC 28016 • sales.USA@dhollandia.com



Toll free (855) 856-8225 • Tel: (909) 251-7979 • Fax: (909) 357-1554