

PTN SERIES RAIL GATE



MEDIUM DUTY

1,250 lb. - 1,600 lb. Capacities

**THE STRONGEST, MOST DURABLE
LIFTGATE FOR TRANSPORTING
BULKY, TOP-HEAVY LOADS.**



Optional Aluminum Platform Shown

STANDARD PTN SERIES ADVANTAGES INCLUDE:

- Applications - Pickup trucks and cargo vans.
- Gate is level with truck side panels (photo).
- Safer: — level-ride, greater load stability
 - fewer pinch points
 - anti-skid steel treadplate platform
- Exclusive above floor lift option with a maximum above floor travel of 9”.
- Chain and sprocket drive ensures smooth operation and eliminates costly cable replacement.
- Platform side chains eliminated — user has unimpeded side access.
- Existing receiver style hitch won't impede installation - most models.
- UHMW - slide pads on runners.

Exclusive above floor lift option will reach most dock heights.



PTN Series Gate in stowed position with the optional aluminum platform

OTHER STANDARD FEATURES:

- Power unit installed, tested and enclosed in weather protected housing.
- Torsion bar assisted platform makes it easier to open and close.
- Pressure compensated flow control valve controls platform descent regardless of load weight.
- Built-in toe deflector.
- Weather sealed controls.
- Charge line circuit protection.
- Meets TMC specifications.
- Powder coat finish on key liftgate components produces a high-quality finish that is exceptionally resistant to corrosion and abrasion.



Designed Simplicity - Maximum Performance

www.waltco.com

PTN SERIES MEDIUM DUTY GATE



SPECIFICATIONS

Bed Ht: 25"-38"

Model	Capacity	Platform	Ramp	Weight
PTN - 12	1,250 lbs.	24" x 57"	6"	399 lbs.
PTN - 16	1,600 lbs.	30" x 57"	6"	424 lbs.
PTN - 16	1,600 lbs.	36" x 57"	6"	444 lbs.
AP (Aluminum Platform)				
PTN/AP - 12	1,250 lbs.	24" x 57"	8"	368 lbs.
PTN/AP - 12	1,250 lbs.	38" x 57"	8"	407 lbs.
PTN/AP - 16	1,600 lbs.	38" x 57"	8"	407 lbs.
PTN/AP - 16	1,600 lbs.	44" x 57"	8"	422 lbs.

OPTIONAL EQUIPMENT:

- Platform Material:
 - Aluminum
 - Expanded Metal
 - Bar Grating
- Above floor lift raises platform with a maximum above floor travel of 9".
- Oversized Ramp in aluminum or steel:
 - Fixed
 - Hinged
 - With Cart Stop
- Non-standard liftgates, deeper, narrower or wider platforms.
- Remote hand held toggle switch control with 15 ft. coil cord.
- Customized Options - contact factory.

Waltco Lift Corp.
 Corporate Office United States
 1777 Miller Parkway
 Streetsboro, OH 44241
 P: 330.633.9191
 F: 330.633.1418

Waltco Sales
 T: 800.211.3074
 F: 800.211.3075
 Email: sales@waltco.com

Waltco.com

