

UDSM 60-200 CFM OPTIONS

- External, spin-on air-oil separating element
- Dual pressure
- Service/control line moisture separators
- Air hoses, hose reels, and fittings
- OSHA safety valve (velocity fuse)
- Sullair® air tools
- Tool oiler/lubricator
- Post drivers
- Dual Pressure Option 100/150 PSI
- Dual Voltage Option 120/240V 6.6 kW
- Dual Voltage Option 120/240V 9.6 kW
- Cold Weather Kit For Air Compressor - Single Pressure - (Consists of Thermal Valve & Heating Blankets for Tank & Regulator)
- Cold Weather Kit For Air Compressor - Dual Pressure - (Consists of Thermal Valve & Heating Blankets for Tank & Regulator)
- Initial 50 Hour Service Kit (Four Gal. of Vanguard™ Oil & Oil Filter)
- Vanguard™ Lifetime Warranty Service Kit (Four Gal. Vanguard™ Oil, Oil Filter and Air Filter)
- Air Aftercooler without Moisture Separator 125/200 CFM
- Air Aftercooler with Moisture Separator 125/200 CFM
- Service Airline De-Icer
- Filter Lubricator Regulator (FLR) 1”
- Hose Reel - for 3/4” Hose - 50’; Hose not included
- Hose Reels: Vanair carries many different models (Call for configuration)
- Moisture Separator (Service line)