



SPECIFICATIONS

V185-UT➤

Rated Delivery (CFM)	185
Rated Operating Pressure (PSI)	100
Length (in.)	80
Width (in.)	35
Height (in.)	55.39
Weight (lbs.)	2,340

V210-UT➤

Rated Delivery (CFM)	210
Rated Operating Pressures (PSI)	100
Length (in.)	80
Width (in.)	35
Height (in.)	55.39
Weight (lbs.)	2,550

V260-UT➤

Rated Delivery (CFM)	260
Rated Operating Pressure (PSI)	100
Length (in.)	83
Width (in.)	35
Height (in.)	55.39
Weight (lbs.)	3,070

FEATURES

- Curbside Serviceability
- Large, 108mm Diameter Twin Screw Air End
- Automatic 0 to 100% Capacity Control
- Two Stage Dry Type Air Filter - External Access
- Two 3/4" Service Connections
- Oil Level Sight Gauge
- Isuzu Engine for 185 CFM, John Deere Engine for 210 and 260 CFM
- Steel Fuel Tank
- Side by Side Coolers for Compressor and Engine
- Compact Size for Truck Mounting
- Curbside Fuel Fill & Air Filter Access
- Noise Level Limited to Maximum of 76 dBA at 7 Meters
- All Drains End Mounted
- Automatic Shutdown and Protection System
- Automatic Blowdown Valve
- Unloaded Starting
- SAE Pad Available on Select Models

Product improvement is a continuing goal. Design and specifications are subject to change without notice or obligation. UTILITYMOUNT_ 012021_CMG