

Standard LX VMS Standard Builder VMS

VALVE MAINTENANCE SKIDS

sales@turnvalves.com



Customize your VMS with the Standard Builder for utility flatbed vehicles



Powerful Heavy Duty TM-7 Hydraulic Valve Exerciser Side-Mounted for Easy Access

STANDARD BUILDER

Our Standard Builder allows you to choose and customize your own VMS.

- Power Pack Diesel or Gas Engine
- Hyd Reservoir
- Spoils Tank 150, 250 or 350 gal
- ERV-750 Valve Exerciser
- HC-100 controller
- Bluetooth tether controller to valve exerciser
- Programmable arrow board and work lights
- Hydraulic hose reel

LX & BUILDER OPTIONS

- TM-7 HD 2,500 Ft-lb torque valve exerciser
- GPS Pathfinder Pro6t Submeter accuracy
- Hot Water Heater
- Job Box (n/a with TM-7 on LX)
- 45 LB Hydraulic Breaker (trailer mount not available)

The Valve Maintenance Experts



Wachs Valve Maintenance Systems (VMS) strategic design contains everything needed to perform a valve maintenance program. Maximize every inch of your utility flatbed or valve truck for the highest level of efficiency. No more extra trips for additional equipment needed to access, locate, operate the valve, and record for maintenance and reporting.

STANDARD LX FEATURES

- Available in two types of engines:
 - Diesel: Kubota 1.1L, I-3 4-stroke liquid cooled twin cylinder (EPA Tier 4F & EU Stage IIIA emission compliant)

Gas: Kohler 27 HP (20.1 KW) overhead cam, air cooled

- ERV-750 extended reach, 750 ft/lbs valve exerciser
- Ruggedized HC-100 controller/data logger with built in GPS
- HTMA Class II circuit, 10 gal reservoir, fan cooled heat exchanger, 8gpm @1800psi
- Positive displacement blower provides 500 CFM-11in Hg vacuum
- 250 gal spoils tank utilizing exclusive hydraulic slide, tilt & powered dump system & latching door
- 2.5 GPM@3000 PSI pressure washer with 80 gal fresh water tank
- 2 1/2in, 1 1/4in & 7/8in suction wands with 20 ft vacuum hose
- Bluetooth Tether Controller for valve exerciser
- Programmable arrow board and work lights
- Hydraulic hose reel

SPECIFICATIONS (not including options)

- Size: Length 102-3/16" (260 CM), Height 66-3/16 (168 CM) Gas or 73-1/2" (187 CM) Diesel, Width 72-1/4" (184 CM)
- Dry Weight (Standard LX): 3,800 lb. (1,724 kg) Gas, 4,094 lb. (1,875 kg) Diesel
- Ladened Weight (Standard LX spoils & fresh water tanks full of water): 6,624 lb. (3,005 kg) Gas, 6,918 lb. (3,138 kg) Diesel

^{*} E.H. Wachs does not make truck recommendations. E.H. Wachs will provide size, weight, mounting information and other technical information to support modifiers/upfitters deliver you a quality valve maintenance vehicle.