

HPT DUMP BODIES



HPT shown with optional equipment.



www.duraclass.com

Durability that Means Business



HPT

The DuraClass **HPT** delivers more payload on the job and more profit to your bottom line. With its interlaced understructure and vertical side braces, the HPT offers durability, productivity, and better resale value at trade-in time. The HPT uses high-tensile steel throughout for superior strength and lighter body weight than comparable dump bodies.



HPT features fully enclosed front corner posts.



DuraClass bodies come with full depth corner posts and enclosed tailgate hardware.

ADDITIONAL BODY OPTIONS

- Aluminum (Cab Shields & Tailgates only)
- Sloped Tailgate
- Reverse Asphalt Taper
- Sloping Side Panels
- Hi-Lift Tailgate, Air or Hydraulic
- Dual Action Side Swing Tailgate
- Body Side Steps and Handles
- Tarp Rails and Walk Rails
- Variety of Sliding Door Options
- Custom Side and Tailgate Heights
- Custom Body Bracing
- Air Operated Hoist Controls
- Variety of Cylinder/Doghouse Configurations
- Stainless Steel Bodies available

PREMIUM STEEL CONSTRUCTION

All DuraClass dump bodies have high-tensile, minimum 45,000 psi steel. Additional steel and stainless steel options are available.

HPT HOISTS

- Increased capacity
- Better stability
- Increased productivity
- Improved longevity



Greaseable Rear Hinge with Optional Removable Pin.

HPT DUMP BODY

Inside Length	13'	14'	15'	15'	16'	17'
Width	7'	7'	7'	7'	7'	7'
Body Capacity, yards	10-12	10-12	10-12	12-14	12-14	12-14
Material	10 ga					
Side/Front/Rear Height, in.	38/52/46	36/52/44	32/52/40	38/52/46	36/56/44	34/62/42
Hoist Model	HPT53-120 or HPT63-120		HPT53-130 or HPT63-130		HPT63-140	HPT63-150
Weight (Includes Hoist), lbs**	3746	3978	4013	4107	4704	4760

All bodies shown with some optional equipment. Models and options are subject to change without notice.

HOIST MODEL	NTEA CLASS	WEIGHT** (LBS)	CAPACITY* (TONS)											
			13'		14'		15'		16'		17'		18'	
Body Length			6"	12"	12"	18"	12"	18"	12"	18"	12"	18"	12"	18"
HPT53-120	80	745	23.3	25.6	23.7	26								
HPT53-130	80	750					23.4	25.3						
HPT63-120	120	1020							38.1	41.1	36.5	38.8		
HPT63-130	120	1040									38	40.6	36	38.2

*Capacity is based on water-level load and approximately 50° dump angle.

**Weight is less oil and PTO

Inverted telescopic hoists also available.



P.O. Box 49
1425 Highway 25 North
Tishomingo, MS 38873
800.255.4345
Fax: 800.728.4345
www.duraclasse.com

CONTACT YOUR DISTRIBUTOR