

YARDBIRD & SUPER DUTY YARDBIRD DUMP BODIES



DuraClass Yardbird shown with available accessories.

DuraClass Super Duty Yardbird shown with available material spreader.



www.duraclasse.com

Durability that Means Business

YARDBIRD



SUPER DUTY



Durability in a Light Duty Package.

The DuraClass **Yardbird** and **Super Duty Yardbird** are the premium light duty choices for contractors and municipalities who don't want to compromise on quality and durability. DuraClass's patented design features a continuous formed body sidewall and fully enclosed top rail, offering superior resistance to moisture and corrosion. Plus, an interlaced understructure and double-wall body side give Yardbirds uncommon strength and rigidity in a light duty dump body.

FEATURES

- Quick release upper tailgate pins
- 1/4 cabshield with window
- Fully welded construction
- 1" diameter tailgate pin
- 5/16" GR43 tailgate chains
- Chain brackets are banjo eye plates
- Pipe handle



The Yardbird's heavy-duty platform hinge is greasable.



Stainless Steel Model

YARDBIRD SPECIFICATIONS

| | | |
|-------------------------------------|--------------|--------------|
| Inside Length | 8' 1" | 10' |
| Width | 6' 8" | 6' 8" |
| Material | 10 gauge | 10 gauge |
| Body Capacity (yards) | 2 - 3 | 2 - 3 |
| Side / Front / Rear Height (inches) | 14 / 20 / 20 | 12 / 18 / 18 |
| Weight, including hoist (lbs) | 1700 | 2002 |

SUPER DUTY YARDBIRD SPECIFICATIONS

| | | | | | | |
|-------------------------------------|--------------|--------------|--------------|--------------|--------------|--------------|
| Inside Length | 8' 1" | 9' | 9' | 10' | 11' | 11' |
| Width | 7' | 7' | 7' | 7' | 7' | 7' |
| Material | 10 gauge |
| Body Capacity (yards) | 3 - 4 | 2.5 - 3.5 | 3.5 - 4.5 | 3 - 4 | 2.5 - 3.5 | 3.5 - 4.5 |
| Side / Front / Rear Height (inches) | 18 / 24 / 24 | 14 / 20 / 20 | 18 / 24 / 24 | 14 / 20 / 20 | 12 / 18 / 18 | 14 / 20 / 20 |
| Weight, including hoist (lbs) | 1999 | 1831 | 2101 | 2090 | 2122 | 2182 |

1520 FLM HOIST CAPACITY* (TONS)

| | | | | | |
|---------------|------|------|------|-----|-----|
| Body Length | 8' | 9' | 10' | 11' | 12' |
| Rear Overhang | 6" | 6" | 6" | 6" | 6" |
| Capacity* | 13.5 | 11.6 | 10.3 | 9.3 | 8.4 |

1520 FLM HOIST SPECIFICATIONS

- NTEA Class: 30
- Cylinder Bore: 5"
- Cylinder Stroke: 20"
- GPM (at 1000 RPM): 4
- Weight: 635 lbs (less oil & PTO)
- Mounting Height: 12 3/4"

*Capacity is based on water-level load and approximately 50° dump angle.

All bodies shown with some optional equipment. Models and options are subject to change without notice.



1425 Highway 25 North
Tishomingo, MS 38873
800.255.4345
Fax: 800.728.4345
www.duraclclass.com

CONTACT YOUR DISTRIBUTOR